FORTH PORTS LIMITED OIL SPILL CONTINGENCY PLAN "CLEARWATER FORTH"

VERSION 03

CONTROLLED DOCUMENT

NB: Copies of the plan are uncontrolled if printed.

2022

Post Holder Responsible for this plan: Marine Compliance Manager Forth and Tay Navigation Service Grangemouth Docks Grangemouth FK3 8TQ

Tel: 01324 498584 Email: <u>ftns@forthports.co.uk</u> website: https://www.forthports.co.uk/marine/emergency-plans/





FORTH PORTS LIMITED OIL SPILL CONTINGENCY PLAN MCA Approval Document

Maritime & Coastgua Agency	S.				IE ISSUE OF A CONTINGENCY	PPR		
PARTICUL	ARS OF PORT /	HARBOUR /	OIL-H	IANDING F	ACILITY *			
Name of Port				CL	EARWATER FORTH			
Oil-Handling F Category of Po	-				A & B			
Name of Oper	ator / Company *			FOF	RTH PORTS LIMITED			
Address				Forth 8	& Tay Navigation Service			
				G	Frangemouth Docks			
					Grangemouth			
Post Code					FK3 8TQ			
Regulations 1998 Date of Plan	3 and the Guidelines is 15 October 2021	Plan version (where applicable) Version 1						
MCA File refere	ence MPCU 023 / 0	025/003						
The Plan shall	be accepted as valid	until 14	Octob	er 2026]	F		٦
	ABERDEEN]		
	Office		L	(Signature of	Counter Pollution Officer)	_		
15 October 2021				GA	ARY SPARK]		
Date				(Name of Co	ounter Pollution Officer)	L	Official Stamp	
(Signature of Authorised Official reviewing the declaration) (Name of Authorised Official reviewing the declaration)								
	Date							

MSF3302 / Rev0715



FORTH PORTS LIMITED

Clearwater Forth

Approval Num	ber: 3303 /	1				ABD/3302/2100043	
Maritime & APPROVAL OF OIL SPILL CONTINGENCY PLAN Agency							
the	Issued in accordance with the requirements of the Merchant Shipping (Oil Pollution Preparedness Response and Co-operation Convention) Regulations 1998, under the authority of the Government of the United Kingdom of Great Britain and Northern Ireland by the Maritime and Coastguard Agency an Executive Agency of the Department for Transport.						
	Port / Harbour / Iling Facility *				CLEARWATER FORTH		
Category					A & B		
	Operator / Compa	any *			FORTH PORTS LIMITED		
Address					Forth & Tay Navigation Service		
					Grangemouth Docks Grangemouth		
Post Code					FK3 8TQ		
FUSI COUR	5				110014		
Regulation	to the Merchant Sh	ontingency P	'lan submi		ss Response and Co-operation Conventior above is hereby approved by the Secretar		
Date of Pla	an 15 Octobe	er 2021	Plan vers (where app		Version 1		
This Plan	is valid until	14 Octobe	r 2026				
Issued by	the Maritime and (Coastguard /	Agency.				
Issued at	ABE	RDEEN		Signed	i 		
	(Place o	of issue)		(Signa	ature of duly authorised official issuing the Approval)		
Date	15 Oct	ober 2021		Name	GARY SPARK	Official Stamp	
	(Date of	f issue)			(For and on behalf of the Secretary of State)		
* Delete as ap	ppropriate						
MSF3303 / F	Rev0715				1/1		



Record of Amendments

AMENDMENT NUMBER	DATE	PAGE NUMBERS AMENDED	AMENDED BY
1	June 2021	Amendments throughout – full review including appendices	S. Cameron
2	August 2022	Towage Fleet Updated	C.Campbell
3	December 2022	Job Titles and FTNS Phone numbers updated	C.Campbell



CLEARWATER FORTH DISTRIBUTION LIST				
Copy No.				
1	FORTH PORTS, HARBOUR MASTER (MASTER COPY)			
2	FORTH AND TAY NAVIGATION SERVICE			
3	MARITIME & COASTGUARD AGENCY CP&SO (ABERDEEN)			
4	INEOS GRANGEMOUTH MARINE ASSURANCE MANAGER			
5	INEOS GRANGEMOUTH INCIDENT MANAGEMENT ROOM			
6&7	FORTH PORTS, MEC (x2)			
8	INEOS FORTIES PIPELINE SYSTEM			

A controlled copy of Clearwater Forth is maintained on the Internet via the following link: https://www.forthports.co.uk/marine/emergency-plans/_____

Forth Ports Limited will advise the following organisations of any changes to the plan by email:			
MARINE SCOTLAND			
NATURESCOT			
SCOTTISH ENVIRONMENT PROTECTION AGENCY (SEPA)			
FIFE COUNCIL			
CLACKMANNANSHIRE COUNCIL			
FALKIRK COUNCIL			
WEST LOTHIAN COUNCIL			
THE CITY OF EDINBURGH COUNCIL			
EAST LOTHIAN COUNCIL			
FORTH PORTS PUBLIC RELATIONS PROVIDER			
INEOS FORTIES PIPELINE SYSTEM			
INEOS GRANGEMOUTH			
TARGE TOWING LTD			
SHELL (UK) EXPLORATION & PRODUCTION			
ADLER AND ALLAN			
POLICE SCOTLAND			
SCOTTISH FIRE & RESCUE			
SCOTTISH SOCIETY FOR PREVENTION OF CRUELTY TO ANIMALS			
SCOTTISH SOCIETY FOR PROTECTION OF BIRDS			
INTERNATIONAL TANKER OWNERS POLLUTION FEDERATION			
DEPARTMENT OF TRANSPORT (MARINE ACCIDENT INVESTIGATION BRANCH)			
SCOTTISH POWER PLC			
FPS MARINE LABORATORY			
FORTH PILOTS			



CONTENTS OVERVIEW

- PREFACE: DOCUMENT CONTROL
- SECTION 1: DEFINITION OF PLAN AND RESPONSIBILITIES
- SECTION 2: RISK ASSESSMENT
- SECTION 3: MANAGEMENT AND RESPONSE STRUCTURE
- SECTION 4: ACTION CHECKLISTS
- SECTION 5: SPILL ASSESSMENT AND HEALTH AND SAFETY GUIDELINES
- SECTION 6: RESPONSE OPTIONS AND GUIDELINES
- SECTION 7: EQUIPMENT RESOURCES
- SECTION 8: EMERGENCY CONTACT DIRECTORY
- SECTION 9: ENVIRONMENTAL DATABASE AND PRIORITY PROTECTION AREAS
- **APPENDIX 1: THE LEGAL PERSPECTIVE**
- **APPENDIX 2: EQUIPMENT**
- **APPENDIX 3: MEDIA STATEMENTS**
- APPENDIX 4: OIL SPILL TREATMENT PRODUCTS APPROVED FOR USE IN THE UK
- **APPENDIX 5: PROFORMAS**
- **APPENDIX 6: PLACE OF REFUGE**
- **APPENDIX 7: TIER 2 RESPONDER**
- **APPENDIX 8: STOP NOTICE LINKS**
- **APPENDIX 9: ABBREVIATIONS**
- **APPENDIX 10: EMERGENCY CONTACTS DIRECTORY**
- APPENDIX 11: GRANGEMOUTH SUPPLEMENTARY INFORMATION
- APPENDIX 12: LEITH SUPPLEMENTARY INFORMATION
- **APPENDIX 13: STATEMENTS OF PLAN APPROVAL**
- **APPENDIX 14: MARINE HAZARD SAFETY DATA SHEETS**



Section 1: Definition of Plan and Responsibilities

1.1 Policy Statement

Under the *Merchant Shipping (Oil Pollution Preparedness, Response and Co-operation Convention) Regulations 1998.* (OPRC Regulations) Forth Ports Limited has a statutory duty to prepare for and respond to pollution incidents "at sea" within its area of jurisdiction and to take every possible action to prevent oil impacting on the shoreline. In this respect, there must also be a dedicated oil spill plan in place, which is co-ordinated with the national system.

Clearwater Forth is the oil spill contingency plan and co-ordination scheme for response to oil pollution incidents in the Firth of Forth Harbour Area. The plan is written in accordance with the requirements of the above legislation and lays down procedures that will be adhered to by Forth Ports Limited in order to fulfil these requirements.

1.2 Purpose, Scope and Responsibility of Clearwater Forth

Oil in the context of this plan includes petroleum in any form including crude oil, fuel oil, sludge, oil refuse and refined products.

The purpose of the plan is to provide guidance to Forth Ports Limited response teams with respect to the steps to be taken when an oil pollution incident has occurred in the Forth Ports Harbour Area.

The Forth Ports Limited Harbour Area includes the waters of the Forth Estuary and Firth of Forth between the Kincardine Bridge to the west and a line joining the North and South Carr beacons to the east (Map 1). The Forth Ports Limited area of jurisdiction also includes the following ports:

- Port of Leith;
- Port of Grangemouth;
- Port of Methil;
- Port of Burntisland;
- Port of Rosyth;
- Port of Kirkcaldy;

Supplementary information is provided in Appendix 11 and Appendix 12 for site specific detail for the Ports of Grangemouth and Leith.



Where a spillage is a part of a wider emergency, such as vessel grounding or collision, then the emergency should be addressed utilising the appropriate emergency procedures that may include:

- Forth Ports Limited Marine Emergency Plan (Emergency Forth)
- Shipboard Oil Pollution and Emergency Plan (SOPEP).
- Where oil is approaching the shoreline or has beached, protection of sensitive areas and amenity beaches and shoreline clean up will be co-ordinated by local authorities based on arrangements outlined in their shoreline clean-up oil spill contingency plans.
- The plan identifies the risks and resources of the Forth Ports area and recommends methods by which the resources can best be protected from oil spills to sea. In accordance with the *Contingency Planning for Marine Pollution Preparedness and Response Guidelines for Ports* (Maritime and Coastguard Agency, August 2020 update) this plan includes the following:
 - Identification of responsibilities and lines of communication;
 - Command and control arrangements (allowing for upgrading or downgrading of response actions);
 - Reporting arrangements;
 - Response actions and tactical response plan;
 - Identification of ecologically sensitive areas, commercial and recreational amenity sensitive areas and identifying from these sensitivities, priority protection areas;
 - Identification of available counter pollution resources;
 - Contact lists.

The Appendices provide the following information:

- Places of Refuge
- Compensation and Legal Matters
- Equipment Inventories
- Media guidance and holding press statements
- UK Approved Treatment Products
- Incident Log Proforma and MCA Annual Return Forms
- MCA STOp Notices
- Marine Hazard Safety Data Sheets



1.3 Consultations

This plan has been prepared in consultation with:

- Maritime and Coastguard Agency (MCA)
- NatureScot
- Scottish Environment Protection Agency (SEPA)
- Marine Scotland
- Local Authorities with a shoreline on the Forth
- INEOS Forties Pipeline System
- INEOS Grangemouth
- Shell

1.4 Oil Spill Planning Legislation

The Clearwater Forth oil spill planning has been drawn up to be in compliance with current oil spill planning legislation. Key legislation governing planning for ports and harbours is outlined in summary form in Table 1.1 below.

Legislation	Key Elements	Key Offences
Merchant Shipping (Oil Pollution Preparedness, Response and Co-	Requirement for harbours and ports to have in	Failure to submit an oil spill plan
	place dedicated oil spill plans and an oil spill response system that includes an element of pre-positioned equipment, training and regular	Failure to maintain the oil spill plan in terms of the legislation
operation Convention	exercise.	Failure to report an accidental oil spill
Regulations) 1998		Failure to have in place and utilise Tier 2 response resources
Section 293 of the Merchant Shipping as amended by the	Gives government powers to intervene in the event of an incident involving a salvage operation in a harbour area.	Failure to comply with a direction given by the Secretary of State's Representative (SOSREP)
Merchant Shipping and Maritime Security Act 1997		Obstruction of direction from the SOSREP
Marine Safety Act 2003	Provides powers of intervention and direction to the Secretary of State's Representative for Maritime Salvage and Intervention working with the MCA's Counter Pollution and Response Branch. This intervention includes direction for places of refuge.	Failure to comply with a direction given by the Secretary of State's Representative (SOSREP) Obstruction of direction from the SOSREP
	places of foldger	

Table 1.1 Summary Key Legislation Governing Accidental Oil Pollution Events



1.5 Use of Plan

This Plan is specifically for operations within Harbour area, for all vessels entering the jurisdiction area (map 1). The Plan is designed to initiate an appropriate oil spill response in the event of an incident. It details a tiered response strategy that is in accordance with UK legislative requirements and takes into account the spill risk associated with the operation; the nature of the hydrocarbons that could be spilt; the prevailing meteorological and hydrographic conditions and the environmental sensitivity of the surrounding areas.



Map 1: Forth Ports Limited Harbour Area



1.6 Responsibilities and Definition of Ports, Harbours and Oil Handling Facilities

Forth Ports Limited is the Statutory Harbour Authority for the Firth of Forth area.

The Firth of Forth Harbour Area also contains several oil handling facilities:

- Hound Point Marine Terminal (INEOS FPS)
- Braefoot Bay (Shell Expro)
- INEOS Grangemouth
- INEOS FPS RLPG (berth within Grangemouth operated by INEOS FPS which handles Refrigerated Liquefied Petroleum Gas)

In addition there are a number of small ports and harbours in the Firth of Forth Harbour Area.

Under the *Merchant Shipping (Oil Pollution Preparedness, Response and Co-operation Convention) Regulations 1998*, a number of the ports, as well as the oil handling facilities, within the harbour area are required to have in place dedicated oil spill contingency plans that will enable the facility / port to respond to oil spills. Under Clearwater Forth these facilities and ports accept responsibility for responding to Tier 1 spills within their areas of jurisdiction. These facilities and ports are outlined in Table 1.2 overleaf and include.

Clearwater Forth will be activated to co-ordinate the response to larger spills. The oil handling facility areas will therefore be covered by both their individual facility plans and Clearwater Forth.

For spills from the smaller ports that are not required to have dedicated resources, response to all spills into the sea will be made by Forth Ports Limited under Clearwater Forth. This tiered plan activation is outlined in Table 1.2 overleaf.



Table 1.2: Tiered Response Plans for the Firth of Forth Harbour Area					
Facility	Definition of Facility Type	Plan Responsibility			
Port of Rosyth	Port comprised of riverside berths	Tier 1 - Clearwater Forth (CWF) Tier 2 - CWF Tier 3 - CWF / MCA National Contingency Plan			
Port of Leith	Port enclosed by lock gates	Tier 1 – CWF Tier 2 – CWF Tier 3 – CWF / MCA National Contingency Plan			
Port of Methil	Port is open to tidal conditions but can be enclosed by dock gates	Tier 1 - CWF Tier 2 - CWF Tier 3 - CWF / MCA under National Contingency Plan			
Port of Burntisland	Port is open to tidal conditions but can be enclosed by dock gates	Tier 1 - CWF Tier 2 - CWF Tier 3 - CWF / MCA under National Contingency Plan			
River traffic and anchorages		Tier 1 - CWF Tier 2 - CWF Tier 3 - CWF / MCA under National Contingency Plan			
Port of Grangemouth	Enclosed port with major oil handling facility	Tier 1 - CWF Tier 2 - CWF Tier 3 - CWF / MCA under National Contingency Plan			
Hound Point Marine Terminal	Crude oil loading terminal	Tier 1 – Hound Point MT OSCP Tier 2 – Hound Point MT OSCP / CWF Tier 3 – Hound Point MT OSCP / CWF / MCA National Contingency Plan			
Braefoot Bay	Loading terminal for LPG and gasoline	Tier 1– BBMT OSP Tier 2 – CWF / BBMT OSP Tier 3 – CWF / MCA under National Contingency Plan			
Port of Kirkcaldy	Port is open to tidal conditions	Tier 1 - CWF Tier 2 - CWF Tier 3 - CWF / MCA under National Contingency Plan			
Newhaven	Harbour is open to tidal conditions	Tier 1 - CWF Tier 2 - CWF Tier 3 - CWF / MCA under National Contingency Plan			

Table 1.2: Tiered Response Plans for the Firth of Forth Harbour Area



FORTH PORTS LIMITED

Clearwater Forth

1.7 Activation of the Clearwater Forth

1.7.1 Categorisation of Oil Pollution Incidents

The scale of response required for a spill incident will depend on the category of spill. Oil pollution incidents are categorised in Table 1.3.

Tier	Scale of Incident	Mobilisation level
Tier 1	Small operational type spills that may occur within a location as a result of daily activities. These spills will be dealt with using local resources.	 Will be dealt with by Forth ports or local responder (Methil & Burntisland); Spills from small ports not required to have dedicated oil spill plans will be dealt with by Clearwater Forth; 3rd party spills or vessels in transit will be dealt with by Forth Ports Limited.
Tier 2	A medium sized spill were immediate resources are insufficient to cope with the incident and further resources may be called in on a mutual aid basis.	Will be dealt with by dedicated port/facility plan in conjunction with Clearwater Forth Requires mobilisation of further resources and may involve local government
Tier 3	A large spill were substantial further resources are required.	A Tier 3 spill is beyond the resources of both local and regional resources and is an incident that requires the involvement of the Maritime and Coastguard Agency (MCA) and activation of the National Contingency Plan.

1.7.2 Plan Activation

Clearwater Forth will be activated to provide the response to Tier 1 spills as specified in Table 1.3 above. The degree to which the incident response organisation will require activation to respond to Tier 1 spills will be at the discretion of the Forth Ports Limited Chief Harbour Master.

In the event of a large spill in the Firth of Forth Harbour Area, (Tier 2 & 3) Clearwater Forth will be implemented, and the response to the incident will be co-ordinated by Forth Ports Limited. The decision to escalate an incident from a Tier 1 to Tier 2 incident will lie with the Chief Harbour Master or his deputy and will depend on a range of factors which may include oil type (e.g. heavy fuel oil, crude oil, and refined products), prevailing metocean conditions, and equipment resources required for the response.

The decision to escalate an incident from Tier 2 to a Tier 3 lays with the MCA's duty Counter Pollution and Salvage Officer (CPSO) in consultation with the Chief Harbour Master. Aberdeen MRCC will have informed the duty CPSO if there is any pollution or threat of pollution i.e. a drifting ship, a grounded ship etc. The CPSO will then decide the relevant course of action, and instigate the appropriate level of response.



1.8 Oil Pollution Responsibilities & Contingency Plan Activation for the Forth Ports Harbour Area

In the U.K. there is an established national system in place for responding promptly to oil pollution incidents with this system detailed in the National Contingency Plan. The Maritime and Coastguard Agency (MCA) is the competent U.K. authority responsible for responding to pollution from shipping and offshore installations and for implementing the National Contingency Plan. The "*National Contingency Plan; a Strategic Overview for Responses to Marine Pollution from Shipping and Offshore Installations"* was published under a slightly different title in January 2000, with the latest reissued version in September 2014. The NCP sets out revised command and control procedures for incident response. These procedures have built-in thresholds to allow for flexibility of response to different degrees of incident. This system as it applies to harbour areas has oil pollution responsibilities shared amongst:

- Harbour and port authorities
- Oil handling facilities
- Government Departments and Agencies:
 - Maritime & Coastguard Agency (MCA)
 - Scottish Environment Protection Agency (SEPA)
 - Marine Scotland
 - NatureScot
- Local authorities
- The oil pollution responsibilities of these organisations are summarised in Figure 1.1 and are laid out in detail in the NCP, which should be referred for additional detail as, required. The September 2014 version of the NCP is solely electronic with the core document containing hyperlinks that point to additional information. This new format allows for updating of new information and better practices to be undertaken quicker and therefore be more readily available without the need for a length updating exercise. An extract of cleanup responsibilities from the NCP is as follows:

Location of Pollution	Responsibility for Ensuring Clean-up
On the water, jetties, wharves, structures, beach or shoreline owned by the harbour authority within the port/harbour area	Harbour authority
Shoreline (including land exposed by falling tide)	Local authority
Jetties, wharves, structures, beach or shoreline which is privately owned	Owner of the property/land
All other areas at sea (inside the EEZ/UK pollution Control Zone and the UK Continental Shelf	MCA



Figure 1.1 Definitions of Oil Pollution Responsibilities for Clearwater Forth





1.9 Clearwater Forth Contingency Plan Interfaces

The contingency plans that would be activated in response to the range of possible oil pollution incidents in the Forth Ports Harbour Area. This Hound Point Oil Spill Plan describes the contingency procedures that would be initiated by Forties Pipeline System (FPS) in the event of spillages arising from export operations at Hound Point Marine Terminal or spills from vessels from first line ashore until last line gone at Hound Point Terminal. In the event of a major spill Forth Ports will assume the overall command and co-ordination of the incident through Clearwater Forth while FPS On-Scene Commander will support the FPS on-site response. FPS will also contribute to the CWF response.

Interfacing Plans:

- Falkirk Council Oil Spill Plan
- INEOS FPS Hound Point Marine OSCP
- Shell Braefoot Bay Marine Terminal Pollution Response Contingency Plan
- East Lothian Council Oil Pollution Plan
- Fife Harbours Oil Pollution Emergency Plan
- Edinburgh Council Oil and Chemical Pollution Emergency Plan
- Babcock OPRC

1.10 Oil Spill Response Training and Exercises

Forth Ports Limited has implemented a rolling programme of training and exercising for all personnel likely to be involved in the response organisation to a spill incident. Each year, a review of training is undertaken and any specific oil spill training needs addressed.

Identified key personnel in the response organisation attend oil spill response courses and personnel already trained attend refresher courses at three yearly intervals. Training records are held by Forth Ports training department.

Training includes oil spill management training, practical response training and foundation courses. Key oil spill response personnel undergo training depending on their position as specified in Table 1.4.

The training courses for Forth Ports Limited are to UK national oil spill response training standards (every three years) and are tailored courses focusing on marine and management issues of oil spill response within the Firth of Forth area as well as the general principles of oil spill response.



Table 1.4: Firth of Forth Oil Spill Response Training Arrangements

Position	Course	UK Accreditation Level
Chief Harbour Master	Response Management	MCA 5P
Harbour Master Forth and Tay	Response Management	MCA 5P
Marine Manager	On Scene Commander	MCA 4P
Assistant Marine Manager	On Scene Commander	MCA 4P
Marine Compliance Manager	On Scene Commander	MCA 4P
Marine Officer	On Scene Commander	MCA 4P
Assistant Harbour Master	First Responder	MCA 2P
Marine Services Manager	First Responder	MCA 2P
Conservancy Manager	First Responder	MCA 2P
Conservancy Surveyor	First Responder	MCA 2P
Operations Supervisor	First Responder	MCA 2P
Tug Crew	First Responder	MCA 2P
Coxswain	First Responder	MCA 2P
Port Marine Operative	Basic Response	MCA 1P
Console Controllers	Basic Response	MCA 1P
Lock side Staff	Basic Response	MCA 1P
Vessel Traffic Services Operator	Basic Response	MCA 1P
All Personnel	Refresher Course (as required)	MCA R



1.10.1 Drills and Exercises

Exercises are regularly conducted at every level to test the response and validate the plan. Exercise programmes follow the recommendations in the MCA Guidelines for OPRC plans and are as follows:

Exercise Type	Description	Frequency
Oil Spill Modelling Software Test	Oil spill release simulation	Monthly
Notification exercises	Exercising MEC control communications	Twice per year
Mobilisation Exercise	Equipment deployment and clean- up involving small boat handling and Tier 1 equipment deployment. Can involve tier 2 contractor.	Twice per year
Table-top Exercise	Test the emergency management knowledge and capability. Can be used to test co-ordination with local authorities and the emergency services. Can be combined with an equipment mobilisation / deployment exercise.	Once per year
Incident Management / Tier 2 exercises* These exercises will normally be conducted as joint exercises with Clearwater Forth partners	Multi agency response and communications exercise	Annually

Table 1.5 Forth Ports Limited Exercise Program	ıme
---	-----

Annual returns of post incident / exercise reports and annual return form will be made by the Marine Compliance Manager. The MCA pro-formas for these reports are provided in Appendix 5. Logs of all reports are maintained by the Harbour Master Forth Inner. Both training and exercise records are updated annually.



1.11 Document Control and Review Procedure

This controlled document will be revised and re-issued in accordance with the OPRC Guidance requirements and the *Merchant Shipping (Oil Pollution Preparedness, Response and Co-operation Convention) Regulations 1998.* OPRC guidelines require the plan to be reviewed on at least an annual basis in order to remain valid and accurate. All revisions must be submitted to MCA for approval. Hard controlled copies of the revised plan will be sent to the organisations listed in `Document Control`. A controlled copy will also be placed on the website and an email notification of the revision sent to the listed organisations.

OPRC requirements are as follows:

- Each organisation must fully review its oil spill plan every five years BUT
- Where any major change occurs which could affect the validity of the plan or its effectiveness then the plan must be reviewed, amendments made and resubmitted within 3 months of such a change occurring. Such changes would include:
 - A change in the risk i.e. with construction of port facilities; introduction of new third parties;
 - Changes in environmental sensitivities, which would change designation of priority protection areas.

Responsibility for plan revision lies with the Forth Ports Limited Marine Compliance Manager. In particular CWF will be reviewed 9 months before the approval expiry date.



1.12 Environmental Statement

As part of Forth Ports Limited, the Marine Department is committed to fulfilling its' environmental duties as required by the Harbours Act 1964 and other compliance obligations. Ports are required by Government policy to adopt an appropriate balance between conservation of the environment and enabling sustainable economic growth.

Forth Ports Marine Department provide Navigation and Conservancy in the Firths of Forth and Tay and Pilotage and Towage services in the Firth of Forth. To fulfil its commitment to the protection of the environment, including through the prevention of pollution, the department commits to continual environmental improvement, and aims to achieve these commitments through the following:

- Committing adequate resources to departmental activities to allow for effective environmental stewardship to be carried out in line with the provision of departmental services.
- Pursuing continual environmental performance improvement through the company's procurement process by reviewing the environmental performance attributes of plant and equipment prior to selection.
- Undertaking a biennial review of selected department activities to identify opportunities for improving environmental performance.
- Ensuring that all departmental activities, as well as the activities of those carrying out work on behalf of the department, at least match adopted compliance obligations, and where possible exceed them.
- Executing an annual competency review to ensure that there are sufficient human resources within the department to allow for adopted environmental commitments and statutory responsibilities to be effectively met.
- Undertaking and regulating marine movements in such a way as to safeguard water users, the marine and adjacent land environment and local communities.
- Maximising response capabilities by regularly exercising contingency plans (whether pollution prevention or emergency plans) and ensuring that selected emergency exercise scenarios drive continual improvement in departmental and other stakeholder capabilities.
- Undertaking appropriate assessments under the Habitats Directive for new projects, as required.
- Where appropriate, consulting with identified interested parties such as relevant statutory authorities, regulators and stakeholders, as well as local community groups where there are areas of common interest.



- Maintaining membership of the Forth Estuary Forum and Tay Estuary Forum and taking an active role in the management of these organisations and the initiatives they develop.
- Ensuring that all waste is disposed of responsibly, or where practical, recycled or re-used.
- Communicating this Environmental Policy to identified interested parties such as Marine Department staff and where necessary provide guidance and appropriate training.
- Reviewing this Policy at regular intervals.



Section 2: Risk Assessment

2.1 Approach and Methodology

This risk assessment has been carried out for the Forth Ports Harbour Area to:

- Identify sources of potential oil pollution in the Firth of Forth;
- Provide an estimate of the likely frequency of oil spills in various size ranges;
- Identify and rank key areas of relative oil spill risk in the Firth of Forth Harbour Area.

As data on numbers and amounts of spills in UK ports and harbours are incomplete, detailed statistical analysis is not feasible. Emphasis is therefore placed in the following assessment on identifying trends and providing a qualitative estimate of oil spill risk. The following approach and databases have been used to develop the risk assessment:

- 1. The Advisory Committee on Pollution of the Sea (ACOPS) maintains a database of confirmed cases of marine oil pollution annually. This database is the most consistent available record for spills in ports, harbours, estuarine areas and nearshore waters. Because however the spill reports to ACOPS are based on submission of questionnaires, it cannot be taken as a complete record of all spills and is not therefore treated in this analysis as a complete historical database of all spills into ports and harbours. The data can, however, be used to identify trends. Data has therefore been extracted from the ACOPS reports to provide an indication of the main sources of oil pollution in UK ports, harbours and estuarine waters. The data in the ACOPS reports reveals a high degree of consistency between years of reporting.
- 2. Field survey, identification and mapping of the point sources of risk; analysis of the Harbour records of traffic; and identification of the types of hydrocarbons that can be spilt from the point sources has formed a fundamental basis for the risk assessment. Risk assessment data for oil handling facilities and oil tanker traffic has been based on data for product carriers, small crude oil and large crude oil carriers from ITOPF, Lloyds Register of Shipping World Fleet Statistics, World Casualty Statistics and BP data.
- 3. Environmental database and the priority protection areas in the Forth Ports Harbour Area.
- 4. Slick trajectory analysis to determine times to beaching given a range of oil spill scenarios.



Clearwater Forth

2.2 Sources of Marine Pollution for Ports, Harbours and Nearshore Waters in the UK

The ACOPS empirical data provides an overview of spills in UK ports, harbours and nearshore waters as it is not confined to data on spills associated with tankers alone. Reported locations of all vessel-source oil discharges are provided for UK ports and harbours and nearshore waters in Table 2.1 and Figure 2.1.

Enumeration Area	Open Sea	Tidal river / estuary	Bay / nearshore waters	Beach / shore	Port / harbour	Total
Eastern Scotland	2	-	-	-	17	19



Clearwater Forth



Figure 2.1: Locations of reported oil discharges attributed to vessels (ACOPS, 2017) Twenty discharges from vessels were recorded in the Eastern Scotland region during 2017, four fewer than the previous year's total. Seventeen of these spills occurred in port and harbours and two in the open sea/nearshore. The sources of pollution in identified cases included fishing vessels, offshore support vessels, coastal tanker, offshore oil and gas installation, pleasure craft and other types of vessels (http://www.acops.org.uk, accessed 2017).

2.3 The Firth of Forth Spill Report Data

As with the data for the UK, spills from `other vessels` are the most commonly occurring sources of spillage; spills from tankers and oil handling facilities do occur but represent a small percentage of the total number of spills.

Bunker oil and diesel oil are the hydrocarbons most commonly spilt, although in predominantly small quantities such spills groups together bunker, diesel, fuel and gas oils.



2.4 Shipping and Tanker Oil Spill Data- Worldwide

The number of large spills has decreased significantly over the last few decades during which records have been kept. The average number of major spills for the decade 2010-2019 is 1.8 which is less than a tenth of the average for years in the 1970s. 54% of the large spills recorded in the 1970s. This figure has decreased each decade to 8% in the 2000s. No large spills were recorded in 2020. A decline can also be observed with medium size spills (7-700 tonnes) in Figure 2.5.



Figure 2.5: Number of medium and large spills per decade from 1970 to 2020 (ITOPF, 2020).



2.5: Shipping and Tanker Spill Risk- Firth of Forth

2.5.1 Forth Estuary Spill Risk Assessment

Most spills from tankers result from routine operations such as loading, discharging and bunkering which normally occur in ports or at all terminals (ITOPF). Data from the Forth Estuary suggests that the trend identified for the ITOPF worldwide data is reflected in the likely spill risk for the Forth Ports Harbour associated with tanker operations and oil terminals and jetty operations (Forth Estuary Oil Spill Risk Analysis Report No. HSQ/SE/90/025). Sources of spills associated with these facilities and associated operations include:

- Leak / failure of risers to jetties
- Leaks from valves and pipe work on jetties
- Loading arm / connection seals leakage / failure
- Vessel tank overflow
- Vessel sea valve leakage
- Structural damage to vessel due to collision or grounding.

The Hound Point Marine Terminal in the Firth of Forth Harbour Area has a separate Oil Spill Contingency Plan. This includes an oil spill risk assessment for tanker operations at the Hound Point Jetties.

At INEOS Grangemouth there is a fully operational tanker berthed at Jetty E1. This vessel acts as a Floating Storage Unit (FSU). Daughter vessels berth alongside the FSU to load and discharge oil products. Four Yokohoma fenders of appropriate specification will be positioned alongside the FSU before the Daughter vessel berths.

 Table 2.2: Spill frequency data for shipping, including vessels in transit

Jetties	Spill Range	Expected Frequency
Oil tanker spill Total risk	Spills of 900 tonnes spills of up to 2400 tonnes spills of up to 4500 tonnes spills of up to 9000 tonnes spills of up to 12000 tonnes spills of up to 15000 tonnes	1.5 x 10^{-3} 1.3 x 10^{-3} 5.2 x 10^{-3} 2.4 x 10^{-3} 7.3 x 10^{-5} 1.3 x 10^{-6} 1.04 x 10^{-2}

The above table provides a quantitative assessment of leak occurrence frequency for various spill sizes for shipping incidents in the Firth of Forth, including vessels in transit. The spill risk assessment suggest that, for traffic associated with the 2 jetties, the risk is one major spill every 100 years.



2.6: Oil Spill Modelling

A range of spill scenarios have been modelled for the Firth of Forth using oil spill modelling software:

LOCATION: 0.25 NAUTICAL MILES NORTH EAST OF GRANGEMOUTH DOCKS ENTRANCE					
Oil type and volume	State of Tide	Wind Direction & Speed	Location of Beaching and Time Taken		
Heavy fuel oil	Spring ebb.	225° (S.W)	Initial impact: Longannet Point		
50 tonnes		09 Knots (F. 3)	Time taken: 1 hour 10 minutes		
Forties blend 10 tonnes	Neap flood	090° (E) 09 Knots (F.3)	Initial impact: 0.8 nautical miles south of Kincardine Bridge		
			Time taken: 5 hours 12 minutes		
Forties blend	Neap flood	300° (E.N.E)	Initial impact: Foreshore of Grangemouth Refinery		
10 tonnes		09 Knots (F.3)	Time taken: 3 hours 49 minutes		
LOCATION: H	Iound Point o	IL TERMINAL			
Forties blend	Spring ebb	225° (S.W)	Initial impact: Inchcolm Island		
10 tonnes		10 Knots (F.3/4)	Time taken: 2 hours		
Forties blend	Spring flood	090° (E)	Initial impact: North Queensferry		
10 tonnes		10 Knots (F.3/4)	Time taken: 1 hour		
Forties blend	Neap flood	225° (S.W)	Initial impact: North west of Ross Point		
10 tonnes		30 Knots (F. 7)	Time taken: 3 hours		
Forties blend 100 tonnes	Neap ebb	090° (E) 30 Knots (F.7)	Initial Impact: North Queensferry to Port Laing Sands		
			Time taken: 55 minutes		

Table 2.3: Slick trajectory analysis summary of results

LOCATION: BRAEFOOT TERMINAL					
Heavy	Spring flood	315° (N.W)	Initial impact: Dalgety Bay		
fuel oil 100 tonnes		9 Knots (F.3)	Time taken: 52 minutes		
Heavy	Neap ebb	000° (N)	Initial impact: Braefoot Terminal foreshore and beyond		
fuel oil 100 tonnes		19 Knots (F.5)	Time taken: 52 minutes (all oil ashore in 4 hours)		
LOCATIO	DN: FAIRWAY B	UOY (APPROXIMATE	ELY 7 NAUTICAL MILES NORTH EAST OF LEITH DOCKS)		
Oil type / volume	State of Tide	Wind Direction & Speed	Location of Beaching and Time Taken		
Heavy	Neap ebb	180° (S)	Initial impact: Largo Bay		
fuel oil 100 tonnes		9 Knots (F.3)	Time taken: 47 hours		
Heavy fuel oil	Spring flood	090° (E)	Initial Impact: Inchcolm Island		



100 tonnes		19 Knots (F.5)	Time taken: 13 hours 16 minutes			
LOCATION: OPEN WATER APPROX 4 NAUTICAL MILES NORTH OF Nth BERWICK) 056° 08' 09" N - 002° 44' 32" W						
Heavy fuel oil 100 tonnes	Neap ebb	000° (N) 15 Knots (F.4)	Initial impact: North Berwick Time taken: 5 hours 12 minutes			
Forties blend 100 tonnes	Spring flood	135° (S.E) 15 Knots (F.4)	Initial impact: East end of Largo Bay Time taken: 6 hours			

The data suggests that under a range of tidal conditions and wind speeds, oil spilt from the above point sources will beach rapidly and, in several cases, within 2 hours of the spill taking place.

2.7: Risk Assessment for the Forth Ports Harbour Area

The Risk Assessments for CWF are now included in the Forth Ports Risk Assessment matrix which is kept live online. The latest version of Risk Assessments can be found on the Forth Ports website.



2.8: Risk Management

Forth Port Limited as a Statutory Harbour Authority complies with the provisions of the Port Marine Safety Code this compliance being independently audited. Within the Port Marine Safety Code Safety Management System a wide range of procedures based on risk assessment are in place to ensure that risks to vessels, and therefore risks of major and minor liquid hydrocarbon spillages to sea, are reduced to "As Low as Reasonably Practicable" (ALARP). These include the following:

Forth and Tay Navigation Service is manned 24 hours a day, 365 days a year by five fully qualified Assistant Harbour Masters and five fully qualified VTS Officers. The service they provide includes radar surveillance of the Forth Estuary from the Eastern Port Limits (Tantallon Castle on the south shore to Fife Ness on the north shore). Their duties include enforcement of the Forth General Directions and Navigation Byelaws. These ensure a safe and speedy passage of all commercial and naval shipping.

Forth Ports monitor shipping with AIS, CCTV, VHF and Radar. The radars covering the Forth Estuary are located at Gullane, Leith, Burntisland, Grangemouth and Rosyth. In addition, Forth and Tay Navigation Service personnel monitor meteorological and tide stations located at strategic positions around the Forth and maintain and update an Integrated Port Operating System (IPOS) that records all details of ship voyages in the estuary. Radar picture and IPOS database can be viewed and accessed by the Harbour Masters in the main ports in the Estuary.

As responsible operators, INEOS Grangemouth and Forth Ports exercise extensive precautions to prevent accidental spillages associated with operations at the Port of Grangemouth. As part of these precautions, INEOS Grangemouth ensures strict attention to controls for tanker arrival, berthing, loading and departure and to operating and maintenance procedures at the jetties. These controls include ship vetting, mooring procedures during berthing (including tug provision), jetty regulations, preloading checklists for jetties, visual inspections and safety checklists for the vessel, constant supervision and checks during (un)loading and the provision of a dedicated OSCP.

Procedures (including but not restricted to the following):

- 1. At least 24 hours before a ship arrives on the Forth it must provide prearrival information e.g. Name, IMO number etc. A ship must have a passage plan to the port to which they are stemmed. Checks are made at the Eastern Limits of the Firth and recorded on the VHF, the checks verifying the information sent in the pre-arrival message.
- 2. Ship wishing to bunker must comply with the Forth Ports Bunkering Procedure. This procedure can be viewed on the Forth Ports website.
- 3. The Marine Guidelines and Port Information document contains comprehensive guidelines for the safe docking and undocking of vessels in the Harbour Area and for safety in transit. This information can also be viewed on the Forth Ports website.
- 4. Jetty regulations and Oil Spill Contingency Plans of the Marine Terminals at Hound Point and Braefoot Bay.



Section 3: Incident Management System

3.1: Firth of Forth Incident Command System

The management response to larger oil spill incidents in the Firth of Forth Harbour area will invariably require a co-ordinated response by a range of organisations which, depending on the source and location of the incident, may include:

- 1. Police Scotland;
- 2. East Lothian, Edinburgh, West Lothian, Falkirk, Clackmannan and Fife Councils;
- 3. INEOS Forties Pipeline System (Hound Point Marine Terminal);
- 4. Shell (Braefoot Bay Terminal);
- 5. MRCC;
- 6. Marine Scotland;
- 7. Scottish Environment Protection Agency;
- 8. NatureScot;
- 9. Maritime and Coastguard Agency;
- 10. Secretary of State's Representative (SOSREP);
- 11. Towage contractors and salvors;
- 12. INEOS Grangemouth.

As the Clearwater Forth response for oil pollution incidents is likely to require the integration of a multiple agency response, the management system has a unified command structure. This is designed to allow all parties who have responsibility in a multi-jurisdictional incident to contribute to:

- the process of determining overall incident objectives;
- selection of response strategies;
- joint planning for tactical situations.

There is therefore a mechanism for joint decision making by Forth Ports Limited in consultation with participating members of Clearwater Forth to ensure that maximum use is made of all available resources within the Clearwater Forth Scheme.





Figure 3.1 Clearwater Forth Incident Management Team Organisations

3.2: Clearwater Forth Incident Management Team

The Clearwater Forth Incident Management Team (IMT) has a structure as shown in Figure 3.1. This is divided into "Strategic", "Tactical" and "Operational" levels to conform to the normal practice in Integrated Emergency Management. The IMT will normally operate from the Marine Emergency Centre at Forth and Tay Navigation Service.



The Incident Commander (IC) is in overall charge but delegates the tactical management of the response to the Incident Manager. The Incident Commander is then able to consider matters from a strategic aspect and will liaise with other organisations at executive levels such as the Strategic Co-ordination Groups. The IC will also deal with the media through the company's media consultants.

The Incident Manager is responsible for the response to the incident at a tactical level. He will consult with the IC regarding the development of the incident including whether to mobilise additional support functions in the IMT. He will co-ordinate the activities of the Team Leaders and any additional Support Functions. He will brief the partner organisation representatives on their arrival.

In particular he will ensure that the Incident Secretary maintains the Incident Log and directs the preparation of the SITREPs. The Incident Manager will ensure that the process of the IMT operates effectively.

The Marine Operations Team Leader reports to the Incident Manager and is responsible for all-tactical command and co-ordination of the waterborne response in accordance with the joint approved incident action plan. Typically this Team will manage containment, recovery and clean up.

Units within the Marine Operations Team include Marine On-Scene Commander & the members of the water borne response team at the scene of the incident.

The MEC Operations Team Leader reports to the Incident Manager and is responsible for the efficient running of the MEC. This includes the collection, evaluation, and use of information about the development of the incident and status of resources. The Incident Manager will rely on him to assess the situation and develop potential plans of future action.

The MEC Operations Team Leader will ensure that communications are established with the Local Authority IMT, that the status boards and charts are kept up to date and that the oil spill modelling software predictions are run. FTNS staff will be trained in the various roles and called in as required by the scale of the incident.

Support Functions from Forth Ports and representatives from partner organisations may join the IMT as required by the nature of the incident. This may include for example personnel from ship managers or owners, the emergency services or Local Council Emergency Planning Officers.

Depending upon the circumstances of the incident, the Incident Manager and teams may be required to co-ordinate actions with the Salvage Control Unit which implies the close co-ordination of search and rescue, salvage and oil pollution response operations.

Teams may be further subdivided into Units (managed by Unit Heads) as required by the nature and size of the incident and supplemented by additional support teams as indicated in Figure 3.1. It will be the responsibility of the Incident Manager to make a decision as the requirements of the units. This system pertains to all levels of plan activation from Tier 1 to Tier 3 spills.



Tier 3 Incidents

During Tier 3 incidents, advice and support will be provided to the Incident Management Team by the MCA. The presence of the duty Counter-Pollution and Salvage Officer (CPSO) within the Marine Emergency Centre would be the most effective method of providing such support.

In addition, the following Unit will be required to support the Incident Management Team:

The *Public Relations and Information Unit* will provide information on the incident to the public and news media. This group will prepare news releases, pre-agreed under the unified command structure, and will handle all inquiries from the media and other non-government agencies.

3.3 Team Expansion and Down-Manning

If, because of the size of the incident, an additional support function is not directly staffed then that functional responsibility becomes the direct responsibility of the incident. If therefore the Incident Manager can manage all the areas of responsibility required for the incident response, no further response personnel will be required. If the incident is of a size that one or more of the areas of functional responsibility require independent management then an individual must be assigned to that function.

In the Incident Management Team, sub units should be no larger than 3-7 personnel. Team functions likely to require larger manning levels are subdivided into Units, led by Unit Heads.

According to the circumstances of the case additional groups such as a "Scientific and Technical Advice Cell (STAC)" might be established to advise the Incident Management Team. However additional groups are unlikely to be present in the MEC with the exception of a liaison officer.



3.4: Matrix of Roles

In order to ensure integration of all participating members into the functional teams and units, functions have been pre-planned for Forth Ports and participant members. The allocation of functional roles is not intended to be definitive and is likely to change dependent on the nature of the incident and the availability of participants able to respond.

The MEC Team leader is responsible to the Incident Manager for ensuring that a duty roster is prepared to ensure that the MEC continues to operate efficiently over an extended period. This may include ensuring that additional personnel are available to carry out the duties as specified in table 3.1 through the following measures (but not limited to these)

- 1. Standing down personnel who have reported for duty as part of the initial response.
- 2. Contacting personnel who are on their rest days or on leave.
- 3. Arranging for assistance from qualified personnel from other Forth Ports Limited operations (e.g. Dundee or Tilbury).
- 4. Suspending operations on a temporary basis to free-up personnel including recalling personnel from training courses.

The MEC Team Leader is also responsible to ensure that suitable accommodation is available for personnel who have been brought in from other areas. In addition personnel who have been on duty for an extended period may require to rest before travelling home. During a protracted, long running incident then all available trained personnel (large pool of responders) will be called upon and management personnel will be placed on rotations. Back up resources can be sources from anti-pollution contractors. Accommodation and facilities/ resources will be provided where required and will be the responsibility of the Logistics Team as per the action cards.

Catering requirements can be met through the normal company procedures; tea, coffee and other refreshments are always available.



Clearwater Forth

Table 3.1: Incident Response Functions Matrix

Tier 1	Incident	INCIDENT	MARINE	MEC	Additional	Partner
Tier 2	Commander	Manager	Operations	Operations	Support	Organisation
Tier 3			Leader	Leader	Functions	e gameaton
Chief Harbour Master (CHM)	1 & 2 & 3					
Harbour Master Forth & Tay (HMFT	1 & 2 & 3 (CHM Depute)	1 & 2 & 3	1 & 2 & 3			
Marine Manager (MM)	1 & 2 & 3 (CHM Depute)	1 & 2 & 3	1 & 2 & 3			
Assistant Marine Manager (AMM)	1 & 2 & 3 (CHM Depute)	1 & 2 & 3	1 & 2 & 3			
Marine Compliance Manager (MCM)	1 & 2 & 3 (CHM Depute)	1 & 2 & 3	1 & 2 & 3	1 & 2 & 3		
Assistant Harbour Masters (AHM)	1 & 2 & 3 (Until Relieved)	1 & 2 & 3 (Until Relieved)	1 & 2 & 3 (Until Relieved)	1 & 2 & 3		
Vessel Traffic Service Officers (VTSO)				1 & 2 & 3 (Sitreps etc)		
Marine Officer	1 & 2 (Until Relieved)	1 & 2 & 3 (Until Relieved)	1 & 2 & 3 (Until Relieved)	1&2&3	1 & 2 & 3	
Conservancy Manager		/	1 & 2 & 3	1 & 2 & 3	1 & 2 & 3	
Available Forth Ports Staff					1 & 2 & 3	
Secretary to the CHM		1 & 2 & 3 (Incident Secretary)				
Forth Ports Limited PR Consultants	1 & 2 & 3 (Media)					
Police Scotland						2&3
MCA MRCC Aberdeen		1 & 2 & 3				2&3
INEOS Forties Pipeline System (FPS)						2&3
INEOS Grangemouth						2 & 3
Shell						2 & 3
NatureScot						2 & 3
Marine Scotland						2 & 3
SEPA						2&3
Council EPO's						2&3
Council OPCO's						2&3
Council Waste Disposal Officers						2 & 3
MCA						2&3



3.5: Incidents Involving Mobilisation of the Salvage Control Unit and the Secretary of State's Representative (SOSREP)

3.5.1: SOSREP

Section 293 of the Merchant Shipping as amended by the Merchant Shipping and Maritime Security Act 1997 gives the Secretary of State powers to intervene in the event of an incident where there is a significant threat of pollution to the UK's pollution control zone, territorial waters or coastline. This legislation has arisen in the event that a salvage operation for a vessel is required and that the spill must minimise spillage of oil and must not interfere with pollution response operations.

In accordance with the recommendations contained within "Lord Donaldson's Review of Salvage and Intervention and their Command and Control" a recommendation was made that a single representative should be authorised to act on behalf of the Secretary of State for Trade and Industry. This is the Secretary of State's Representative (SOSREP).

In the case of ports and harbours the SOSREP's duties are in respect of salvage only. SOSREP will formally intervene if the salvor does not act in the public interest, tacit approval can be given by SOSREP under the proviso that SOSREP is kept informed of all intended actions. The SOSREP's role is to represent the over-riding interests of the State and to prevent or reduce pollution. His role does not extend to dealing with the clean-up operation, this responsibility remains with the operator through their own oil spill response arrangements, detailed in the OSCP.

Incidents involving the SOSREP, or his deputy, include incidents involving a vessel where there is, or may be a risk of, significant pollution, or where the Harbour Authority is failing or has failed to implement effective control and preventative operations. This means that the SOSREP, or deputy SOSREP, could be activated even in the event that an incident has not yet occurred but where is there is a risk of such pollution occurring.

The SOSREP could therefore become involved in any of the Tiers of Incident defined in Section 1.

3.5.2: Notification of Incidents

When the MCA (Aberdeen MRCC) is notified of an incident where there is or may be a risk of significant pollution, they will immediately inform and liaise with the duty CPSO to:

- 1 evaluates the scale of the incident;
- 2 decide if the SOSREP should be notified of the incident.

The final decision to notify SOSREP will be the responsibility of the Duty CPSO.


3.5.3: Intervention

Once SOSREP or MCA has decided that it may be necessary to intervene in an incident, he will advise the parties in charge of the casualty, or to whom directions are likely to be given, accordingly. Initial intervention is likely to follow a prior warning to the casualty or her owners that the powers of Intervention may be exercised. This will be accompanied by an offer of help from the MCA and a request for information about the situation and the Master's intentions.

Initial intervention is likely to be a formal Direction that the owners/salvors plans and intentions are submitted to and approved by SOSREP.

The process of intervening means that the Secretary of State can then issue specific "Directions" to certain specified persons or bodies including:

- Masters
- Owners
- Salvors
- Pilots
- Operators
- Managers
- Insurers
- Persons in Control of Land
- Harbour Authorities

Under the Dangerous Vessels legislation SOSREP could also give Directions to a Harbour Master for the purposes of securing the safety of any person or vessel. This will override Directions which may already have been issued by the Harbour Master to a casualty.

The nature of the directions can be wide ranging provided they are for the purposes of preventing pollution or the risk of pollution and are as respects the ship or its cargo.

3.5.4: Establishment of the SCU

When intervention has been triggered, SOSREP will establish a Salvage Control Unit or SCU. This Unit is led by SOSREP who will oversee, control and if necessary, intervenes in salvage operations where there is a risk of significant pollution. SOSREP works with a very small team of advisors to encourage salvage contracts and requires that the salvor prepares a salvage plan for agreement by SOSREP prior to any action taking place.

The SCU will be located adjacent to the Marine Emergency Centre, FTNS Building, Grangemouth.

3.5.5: Composition of the SCU

The Salvage Control Unit (SCU) is a small group of key people. Normally they will be:

- SOSREP
- A Salvage Manager representing the on board Salvage Master



- The Harbour Master or Marine Manager if the incident is in or near a harbour or if his harbour is likely to be used as a place of safety to which the casualty may be brought
- An Owner's Representative
- A CPSO with expertise in pollution cleanup this person will also liaise with the Maritime and Coastguard Agency's Marine Response Centre, which will be co-ordinating, the at sea cleanup.
- An Environmental representative who will advise SOSREP and form the liaison with the various environmental groups,
- A personal Salvage Advisor who SOSREP has engaged.

This team will interact with an on-board team who will normally consist of:

- the Salvors,
- SOSREP's representative and
- in certain cases a Shipowner's Casualty Representative.

3.5.6: Places of Refuge

Places of refuge are locations into which a ship, which is in need of assistance can be brought, so that its condition can be stabilised and consequential pollution damage to the seas and coasts be averted. In addition, please refer to Appendix 6.

In the UK, the Marine Safety Act 2003 provides powers of intervention and direction to the Secretary of State's Representative for Maritime Salvage and Intervention (SOSREP), working with the MCA's Counter Pollution and Response Branch.

SOSREP oversees all incidents in UK waters where there is significant risk of pollution, and he or the MCA directs vessels to places of refuge when he judges it appropriate. When a ship in need of assistance requires a place of refuge, SOSREP will take account of all the factors which relate to the specific incident, such as the weather, the geographical whereabouts of the incident and the type of threat posed by the vessel and its cargo, with a view to determining the most appropriate place of refuge, minimising adverse consequences.



3.6: Incident Control Centre

The Forth Ports MEC will normally manage Tier 1 & 2 incidents in the first instance. As defined in the National Contingency Plan (NCP) however, a number of control centres could be mobilised to manage an oil spill incident. Those mobilised will depend on the incident and Tier of spill. The incident response centres that could be manned for oil pollution incidents are detailed in the diagram below. These include the additional centres that could be set up if SOSREP becomes involved in the incident.

The in - built flexibility in the NCP means that not all of these response cells will need to be set up in every incident. The response will be dictated by the scale and type of incident and will be mobilised by the Harbour Authority, MCA and SOSREP. As is described in the NCP, the MCA will set up their own MRC whilst the Harbour Authority will set up their own dedicated command and control centre which will liaise with the MCA MRC and with the SCU and via the ELO with the Environment Group.

3.6.1: Marine Emergency Centre

All incidents will be co-ordinated from the Marine Emergency Centre (MEC) at FTNS Building, Grangemouth.

3.6.2: Participant's Emergency Control Centres

The following participants emergency control centres will provide communications with MEC:

- Hawes Pier Forward Incident Support Room
- MRCC Aberdeen
- Braefoot Bay Terminal Emergency Response Centre
- Local Authority Response Centres
- INEOS Grangemouth Incident Management Room (IMR)
- INEOS FPS IMT

3.6.3: East of Scotland Regional Resilience Partnerships

In Scotland, on shore, the relevant Local Resilience Partnership will co-ordinate the multi-agency response to a marine emergency. The roles of local and regional partners, as well as regional and national support arrangements, will follow the guidance contained within 'Readv Scotland-Preparing Scotland' (http://www.gov.scot/Publications/2012/03/2940). Local and Regional Resilience Partnerships, dependent upon the scale of the incident or emergency, will cover the functions previously carried out by the Shoreline Response Centre. These partnerships will establish the required management teams at all relevant levels i.e. Operational,



Tactical and Strategic, and, if required, implement the linkages into Scottish national structures.

3.6.4: Environment Group

The Environment Group (EG) provides a single advisory line on public health and environmental issues at sea to all response cells. Where an incident poses a significant threat to health or the environment on land, the Resilience Partnership may establish a Scientific and Technical Advice Cell (STAC) and this may be integrated within the EG. At the outset of an incident, at sea, the MCA triggers the formation of an EG to provide advice requiring a local, regional or national response. Standing EGs cover the entire UK coastline and the MCA co-ordinates the geographical coverage of individual Standing EGs, their contact details and call out arrangements. The EGs comprise the statutory environmental regulators, fisheries departments, nature conservation bodies and public health bodies plus a range of specialist public sector and non-government organisations.

The EG framework enables a co-ordinated and timely input to any other more localised or specialised incident. The Group may be set up as a precautionary approach when the possibility of incident escalation has potential. In many major incidents the operational EG remains a 'virtual' Group responding with advice when requested. The EGs remit is advisory and it has no powers of direction or enforcement. Regulatory functions of individual members of the Group are exercised outside the Group structure and function.

Core members of EG will comprise as a minimum representatives from SEPA, NatureScot and Marine Scotland.

For further information regarding the EG please follow the hyperlink in Appendix 8. The STOp notice 1/14 explains the composition, structure and establishment.

3.6.5: Liaison between Emergency Control Centres

Certain incident scenarios involve different aspects of the response being managed by more than one agency or organisation from a number of emergency control centres. In these situations there will be a requirement for co-ordination of particular response activities, for example, the issue of press statements. Without a means of co-ordination, inconsistencies may develop in the contents of press releases that would be seen by the media as being a result of confusion and chaos. A means of co-ordination would reduce the possibility of other errors such as the wasteful duplication of response efforts and omissions in the overall response strategy. The most effective method of achieving this level of co-ordination is an exchange of appropriate representatives from the emergency control centres that have been activated. The representative would provide a mechanism for two-way exchange of information between organisations. Should one response organisation require information from another, their representative could handle the request. The representative will be able to direct the request for information to the most appropriate personnel saving time and ensuring that response personnel are not diverted from fulfilling their functions.



3.7: Communication Routes and Mobilisation

3.7.1: Forth Ports Limited Communications and Mobilisation Routes

Forth & Tay Navigation Services (FTNS) at The Entrance Lock, Grangemouth, will act as the initial point of contact for all spill incidents and from all potential sources of pollution. The FTNS Duty Officer will provide communications support including notification of the spill via POLREP to MRCC Aberdeen and initial request to spray dispersants.

3.7.2: Participant Call-out and Alerting Routes

Call-out of participants is carried out using an automated call-out system. The calls are made to mobile, text, telephone and email. See Figure 3.3 below.



Clearwater Forth OSCP Page 42 Version 3

Figure 3.3: Communication Routes for Clearwater Forth





3.8: Communication Systems

3.8.1: Forth & Tay Navigation Services

The incident management team will be activated by FTNS. FTNS is located at the entrance lock Grangemouth, FTNS maintains a continuous 24 hour listening watch of international marine VHF Channel 71.

3.8.2: MEC Grangemouth

The MEC at Grangemouth will maintain contact with the vessels involved in the incident on international marine VHF Channel 10, either directly, or through FTNS and MRCC Aberdeen. Feedback on the effectiveness of strategy and tactics must be provided to the decision makers in the MEC and also the On-Scene Commander and Tier 2 response contractors on the Firth if the response system is to adapt its strategy and tactics and remain goal directed. Communications with the MEC are also by telephone, email and facsimile.

3.8.3: MCA (MRCC Aberdeen)

MRCC Aberdeen maintains a 24 hour continuous watch on international maritime channel 16 and channel 0. MRCC's have the full range of VHF channels and will select working channel as appropriate after the initial call on Channel 16.

If the circumstances are such that the MEC cannot maintain direct communication with the vessel(s) involved in the incident MRCC Aberdeen may act as the VHF link between the vessel(s) and the MEC.

Coastguard stations also have direct telephone lines to the police, other CG stations, the military MRCC'S, Air Traffic Control, foreign RCC's and CG helicopter bases.

Rescue Centres keep a constant radio watch on the international VHF distress frequencies and also handle telex and facsimile messages through specially designed consoles. Each Centre has a fully fitted operations room with emergency planning, press and staff facilities, along with storage for rescue equipment, vehicles and boats. All have local radio antennae as well as control of remote antennae on high points to give increased VHF range.

3.8.4: Response Vessels

All communications between response vessels and the MEC will be made direct with the MEC. Alternatively, communications may be made through FTNS or MRCC Aberdeen if communications with the MEC cannot be maintained. Please refer to Appendix 2 for response vessels available for an oil spill.



3.9: MEC Incident Management Room Process





Section 4: Action Checklists

4.1: Use of Section

This section outlines the actions that may be undertaken by the Forth Ports response teams in the event of water borne hydrocarbon spill in the Harbour area or ports. It must be borne in mind, however, that co-ordinators and response teams must be prepared to adapt their actions as the incident develops and conditions and oil properties change. Action checklists provided are given in Table 4.1. For spills within Grangemouth, separate actions cards can be located in Appendix 11 for INEOS Grangemouth staff.

Section	Responder	Remarks	
4.2	Forth & Tay Navigation Services : Initiation of Tiered Response		
4.3	Initial Responder – Ports of Methil, Burntisland, Kirkcaldy, Grangemouth and Leith.		
4.4	Initial Responder - Firth of Forth Harbour Area		
4.5	Incident Management Team	4.5.1 Incident Manager - Tier 1 Incidents Ports of Methil, Burntisland, Kirkcaldy, Grangemouth and Leith	
		4.5.2 Incident Commander; All Spills Firth of Forth Harbour Area	
		4.5.3 Incident Manager – Ports T2 &3, All spills FoF Harbour Area.	
		4.5.3 Public Relations Unit	
4.6	Marine Operations	4.6.1 Team Leader	
		4.6.2 On-Scene Commander	
4.7	MEC Operations	4.7.1 Team Leader	
		4.7.2 Environment Unit	
		4.7.3 Health and Safety Unit	
		4.7.4 Waste Management Unit	
4.8	Logistics Team	4.8.1 Logistics Team Leader	
		4.8.2 Equipment & Manpower Unit	
		4.8.3 Support Services Unit	
		4.8.4 Communications System Unit	
4.9	Administration and Finance Team	4.9.1 Team Leader	
		4.9.2 Administration Unit	
		4.9.3 Claims and Insurance Unit	
4.10	Legal Unit		

Table 4.1 – Action Plan Summary



4.2: Forth & Tay Navigation Service- Initiation of Tiered Response Actions

To be carried out by Forth & Tay Navigation Service Duty Officer

ALL INCIDENTS

On receipt of an oil pollution report / alert from either personnel in the ports of Methil, Burntisland, Kirkcaldy, Grangemouth, Leith and Rosyth, or from personnel operating in the Harbour Area, proceed with the following:

- 1. Obtain as much information as possible from the caller so that you can complete the POLREP report (see Appendix 5). After taking details from caller, read them back to the caller to ensure accuracy.
- 2. Commence logging all details and times of incident on Log Sheets (see Appendix 5). This will be most important for any post-incident inquiries and can be forwarded to the MEC if required to assist with a seamless handover.
- 3. If required for larger incidents and in consultation with the Marine Management Team complete the *Request to use Dispersant form,* and forward to Marine Scotland. For spills in the ports, mobilise an Initial Responder; for spills in the Harbour area, mobilise an on-scene responder to proceed to the incident site to investigate the pollution report.
- 4. If possible, make an initial classification of the incident according to the following table:

Tier	Scale of Incident	Mobilisation level
Tier 1	Small spills which can be dealt with using local resources.	 Will be dealt with by Forth ports or local responder (Methil, Kirkcaldy, Grangemouth, Leith & Burntisland). Spills from small ports will be dealt with by Clearwater Forth; 3rd party spills or vessels in transit will be dealt with by Forth Ports Limited.
Tier 2	Spills that require mobilisation of additional regional resources.	Will be dealt with by dedicated port/facility plan in conjunction with Clearwater Forth. Requires mobilisation of further resources and may involve local government
Tier 3	Major spill which requires a rapid large scale response; these will usually result from a loss of containment event.	A Tier 3 spill is beyond the resources of both local and regional resources and is an incident that requires the involvement of the Maritime and Coastguard Agency (MCA) and activation of the National Contingency Plan.

Table 4.2 Tiers of Spill



- 5. In the event of large scale pollution that is likely to cause a hazard to shipping, issue a warning to incoming/outgoing vessels both in the river, terminals and the ports of Rosyth, Methil, Kirkcaldy, Burntisland and Inverkeithing or if likely to be affected Port of Leith and Grangemouth. Before doing this confirm action with Marine Management Team.
- 6. Forward POLREP to Maritime & Coastguard Agency (MRCC Aberdeen) and SEPA by email or other available means. Do not delay sending POLREP if all information is not available. Follow-up proformas should be issued. An appropriate timing for follow-ups would be about every 6 hours OR in the event of a major change in the incident response. Computerised blank POLREPS are maintained by FTNS.
- 7. You are fully authorised to activate Clearwater Forth if you consider this to be necessary according to the particular circumstances of the case. It is better to over react rather than to mobilise resources later in the response when it may be too late. There may however be time to consult a member of the Marine Management Team to discuss the situation before taking this action.
- 8. Clearwater Forth activation will be conducted using the Forth Ports automated call-out system. This system will alert the Clearwater Forth community via telephone message, text, and email. All participants will be alerted within 5 minutes. On-scene time will vary depending on the location of the incident.



TIER 1 INCIDENTS

1. Call out / inform personnel as given in the Activation Matrix below.

Table 4.3 Tier 1 Activation Matrix

Duty Role	Duty Person (as applicable)	Contact Route (all numbers are 24 hours unless specified).
Incident Commander or Incident Manager	Chief Harbour Master (CHM) Or Harbour Master Forth & Tay	Numbers held by FTNS
Maritime & Coastguard Agency (MRCC Aberdeen)	Duty Officer	Tel: 01224 592334 (24 hours)

TIER 2/3 INCIDENTS

1. Activate Clearwater Forth by initiating the automated communications system. Notification will be sent to internal and external contacts simultaneously via recorded telephone message, email and text message.

Note: The Clearwater Forth activation matrix and corresponding contact numbers are also held on file by FTNS.

- 2. The Marine Emergency Centre at the MEC, FTNS Building, Entrance Dock, Grangemouth will be brought into operation following activation of Clearwater Forth.
- 3. Assist as directed by the Incident Manager.
- 4. Check the communication systems *Administration* to determine who has received a call. Endeavour to contact those organisations or individuals who have not received calls and pass a print out to the MEC when manned. Table 4.3 Clearwater Forth Participants Activation Matrix.

Table 4.4 Clearwater Forth Participants Activation Matrix



CLEARWATER FORTH OSP ACTIVATION MATRIX

The personnel listed below will be called by the Cascade Callout

FORTH PORTS PERSONNEL	All numbers held by FTNS
Chief Harbour Master	
Harbour Master Forth & Tay	
Marine Manager	
Assistant Marine Manager	
Marine Officer	
Incident Secretary	
Telephonist / Clerk	
Marine Services Manager	
Group Sustainability, Safety & Regulatory Manager	
Conservancy Manager	
Nominated additional Marine Personnel	
Forth Ports Limited Public Relations consultants	
Forth Ports Directors	
Legal Advisor	

External bodies who receive a call by FTNS include:

- ➤ MCA
- INEOS Forties Pipeline System Kinneil Shift Leader (KSL)
- Ineos Grangemouth Site Shift Leader
- ➢ Shell Expro
- Adler and Allan
- Marine Scotland
- NatureScot
- Scottish Environment Protection Agency (SEPA)
- East Lothian Council
- Stirling Council
- West Lothian Council
- Falkirk Council
- Clackmannanshire Council
- Fife Council
- City of Edinburgh Council
- ➤ ITOPF
- Police Scotland
- Longannet Power Station
- > RSPB
- > SSPCA
- Forth Road Bridge
- Forth Rail Bridge



Table 4.5 External Organisations Notification Matrix

Organisation/ Applicable Legislation	Contact Point	All Spills	Organisation / Agency Role
Local authorities	Fife Council The City of Edinburgh Council West Lothian Council East Lothian Falkirk Council Clackmannanshire Council Stirling Council Refer Appendix 10 for contact details.		The relevant local authority should be notified of any spill that could result in shoreline pollution.
Scottish Environment Protection Agency (SEPA) (The Water Environment (Controlled Activities) (Scotland) Regulations 2011) SEPA are responsible for water quality in controlled waters – underground waters, inland waters & coastal waters within 3 miles of the shore and for the spread of oil inland from estuaries)	Emergency Hotline	~	For spills in the water environment of the Forth, SEPA when notified can provide advice to mitigate or prevent further pollution where practicable. SEPA will regulate and licence the storage and transportation or any waste products collected as a result of any clean-up operations In general as a regulatory body SEPA will not be responsible for any clean-up operations leading to the restoration of normality. During an incident SEPA may require to take evidential samples for possible later legal action.
Marine (Scotland) 2010 Act; Marine Licensing (Exempted Activities) (Scottish Inshore Region) Order 2011; Marine Licensing (Exempted Activities) (Scottish Offshore Region) Order 2011). MARINE SCOTLAND are the controlling body for the waters of the marine environment and fisheries; are the licensing body;	Mobile and email	✓	Under the Marine (Scotland) Act 2010 Marine Scotland (MS) administers the devolved powers on behalf of the Scottish Ministers and co- ordinates environmental advice within the Scottish Government to inform decisions on dispersant use. MS-LOT licences the use of dispersants for all uses in shallow waters (< 20 m depth or within 1 nautical mile of any such area).
NatureScot Marine Scotland would consult with NatureScot as required re use of dispersants in waters which may impinge on statutory conservation areas	Telephone and mobile	✓	Telephone if spill exceeds 1 tonne. Would require immediate notification for spills which are likely to impact on designated conservation sites.



4.3: Initial Responder- Ports of Methil, Grangemouth, Leith & Burntisland

FTNS will decide who will be Initial Responder e.g. Pilot Vessel Skipper, Marine Personnel. If necessary consult Marine Management Team. When carrying out the incident assessment, the Proforma in Appendix 5.5 may prove helpful.

ResponsibilitiesSurveillanceOverseeing res	ponse to Tier 1 spills	
	spill occurring every effort must be made to c closing the dock gates)	ontain the spill within the enclosed
Stage	Actions	Additional Advice
Response Initiation	Ensure that an Incident Log is initiated and maintained. This will be important for post incident inquiries.	
	Attempt to determine if any hazardous conditions exist prior to arrival on-scene.	FTNS Emergency Line: 01324 668 595 (24 hrs)
	Proceed to incident site and check communications systems. This is ESSENTIAL to ensure on-pass of information to response personnel.	
	Ensure that incident area is safe. If light products have been spilt there may be a vapour cloud. On no account enter area as there will be a danger of asphyxiation. Do not attempt to contain spills of these products	
	Make assessment report to FTNS	
	Note that spill reporting to MCA and external authorities will be carried out by FTNS. Ensure that this is carried out <i>It</i> is a legal requirement under the Merchant Shipping (Oil Pollution Preparedness and Response Convention) Regulations 1998 to inform the Coastguard of spills into the Dock area. HM Coastguard will notify Maritime and Coastguard Agency of all spills	
Initial Actions	Proceed to assess situation at site and confirm source of pollution if possible.	The type of oil spilt will determine the intervention response required
	Confirm oil type (s) spilt and carry out spill assessment.	
	In consultation with FTNS establish Tier of spill Consider suspension of any hot work	Tier 1 : small spills that can be dealt with using local resources Tier 2 : spills that will require mobilisation of response contractors and equipment



	certificates (grinding, welding etc.) in vicinity of spill	Tier 3 : Major spills requiring a large scale response
	In consultation with FTNS consider requirement to stopping ship movements;	For spills that are breaking up and naturally dispersing an intervention
	Determine if a response is required. If possible arrange for issue of Tier 1 equipment	response other than monitoring may not be required.
	Ensure formal samples of spilt pollutant are taken and retained.	Procedures for sampling of spilt oil are provided in Section 5
Further Actions	Consider additional resources e.g. Oil spill responder, On-scene commander activation to supplement initial response.	
	If requested stay on-scene to assist response contractors and act as On –Scene Commander.	
Final Action / Stand Down	Provide report to Harbourmaster who will pass on to the Chief Harbourmaster, Harbour Master Forth & Tay and Marine Manager , Forth Ports.	



4.4: Initial Responder- Firth of Forth Harbour Area

FTNS will decide who will be Initial Responder e.g. Pilot Vessel Coxswain, Marine Personnel. If necessary consult Marine Management Team. When carrying out the incident assessment, the Proforma in Appendix 5.6 may prove helpful.

ResponsibilitiesSurveillanceAssisting in intervention response as required			
Stage	Actions	Additional Advice	
Response Initiation	Obtain all available information on the spill from FTNS.		
	Ensure initiation of Incident Log. This will be essential for post incident inquiries.		
	Attempt to determine if any hazardous conditions exist prior to arrival on-scene.		
	Proceed to incident site and check communications systems with FTNS / MEC / other vessels. This is ESSENTIAL to ensure on-pass of information to response teams onshore. If communications are proving difficult seek immediate help from FTNS	A Table of oil types and their likely behaviour when spilt is provided in Section 6 of this plan.	
	Ensure that incident area is safe. If light products have been spilt there may be a vapour cloud. On no account enter area as there will be a danger of asphyxiation. Do not attempt to contain spills of these products		
Initial Actions	Proceed to assess situation at site and confirm source of pollution if possible. If applicable receive handover from Initial Responder Ports of Methil, Kirkcaldy, Burntisland and Rosyth	The type of oil spilt will determine the intervention response required	
	Confirm oil type (s) spilt and carry out spill assessment.	Tier 1: small spills that can be dealt	
	In consultation with FTNS attempt to establish Tier of spill	with using local resources Tier 2: spills that will require mobilisation of response contractors and equipment Tier 3: Major spills requiring a large scale response	
	Consider requirement to stopping ship movements; inform FTNS		
Ongoing Activities	Determine if an intervention response is required; relay information to FTNS.	For spills that are breaking up and naturally dispersing an intervention response other than monitoring may	



		not be required.
	 Ensure formal samples of spilt pollutant are taken and retained. 	Procedures for sampling of spilt oil are provided in Section 5.
Final Action / Stand Down	If requested stay on-scene to assist response contractors and act as On–Scene Commander.	
	On arrival of a relief On-Scene Commander carry out formal hand-over of incident response. Ensure handover is formally logged	
	Provide report and incident log to the Chief Harbourmaster, Harbour Master Forth & Tay and Marine Manager, Forth Ports.	



4.5: Command Team

4.5.1: Incident Manager Tier 1 Incidents - Ports of Methil, Kirkcaldy, Burntisland, Grangemouth, Leith and Rosyth

Note that the Initial Responder / On-Scene Commander may be able to deal with a Tier 1 without requiring to activate an Incident Manager.

Responsibilities					
Overall response	Overall responsibility for, and control of all aspects of the response to the incident.				
Stage	Actions	Additional Advice			
Response Initiation	On arrival at MEC. Accept situation report & handover of overall control from FTNS/ On- Scene Commander. Ensure handover formally logged (refer Appendix 5 for log). If considered appropriate attend scene rather than MEC				
	Ascertain from On-Scene Commander Tier of Spill				
	Ascertain from On-Scene Commander Tier of Spill. If there is any doubt as to the category of the spill attend scene.				
	If incident large and associated with potentially toxic vapours and /or requirement for a search and rescue function MRCC Aberdeen will call-out emergency services. Confirm if this has taken place.	Note that the Master of the vessel has a legal obligation to report all spills (or probable discharges) from			
	If incident associated with a vessel, establish communication with vessel(s) / Ensure a VHF Channel has been designated for the Incident (Ch. 10 preferred if available).	his vessel to the Harbour Authority; failure to do so on his part could result in prosecution			
Initial Actions	Obtain results of spill assessment; establish incident response priorities and assess need to close area/affected port to traffic. Notify FTNS.	For spills in one of the ports ensure liaison and regular SITREPs from initial responder			
	□ If an intervention response is required mobilise Tier 1 equipment. Contact Adler and Allan and request they initiate deployment of Tier 1 Response Equipment	For Response Operations refer to Section 6.			
	Ensure Port Manager is kept informed of the situation.	Ensure that all recovered absorbents are correctly disposed of through Adler and Allan			
Ongoing Activities	If equipment is needed to be deployed contact local Adler and Allan.				



	status of the incident to a Tier 2 incident. If deemed necessary, check that formal samples of spilt pollutant have been taken and retained. Consider relieving Initial Responder / On- Scene Commander in a protracted incident.
	If circumstances change or new information comes to light be prepared to raise the status of the incident to a Tier 2 incident.
	Monitor response effectiveness; adapt/review response strategy as
	Ensure FTNS are kept informed on the progress of the clean-up response.
	In the event of small quantities of non- persistent oil when deployment of absorbents would be impractical it will be sufficient to monitor the natural vaporisation and disposal



4.5.2: Incident Commander All Spills Firth of Forth Harbour Area

The Incident Commander (Chief Harbour Master or Deputy) will be alerted as part of the activation of the MEC.

Responsibilities					
Overall respon	Overall responsibility and management of strategic aspects of the response to the incident.				
Stage	Actions	Additional Advice			
Response Initiation	 On arrival at MEC establish incident status from Incident Manager. 	For Tier 2 & 3 incidents there will be immediate activation of the MEC.			
	Ensure that Incident Manager has sufficient resources to deal with incident.				
Initial Actions	Hold initial meeting with PR Unit and Legal Advisors.				
	Chair planning meeting as soon as feasible.				
	Initiate interactions with Forth Ports Limited Head Office as required.				
Ongoing Activities	Liaise with salvors, ship-owners as required.	Ensure that Planning Team has set up appropriate liaison between the			
	Liaise with SOSREP / MCA CPSO if in attendance.	team and local/national authorities (NatureScot, Marine Scotland,			
	 Ensure information is supplied to Public Relations Unit for preparation of regular, updated media releases; 	SEPA, local authorities, Environment Group (if set up).			
	Authorise release of press statements & attend press briefing sessions/news conferences as requested				
	 Agree any proposed plans for moving stricken vessel; SOSREP may require the vessel to be moved to a place of refuge. Refer Section 3.5.6 for details and Appendix 6 	An SCU may be established if deemed necessary by SOSREP.			
Final Action / Stand Down	Confirm waterborne pollution has been cleared up to allow satisfactory operation of Harbour Area.				
	Brief Forth Ports Limited Head Office.				
	Conduct post incident briefing.				



Clearwater Forth

4.5.3: Incident Manager Ports Tier 2&3 and All Spills Firth of Forth Harbour Area

This section applies to Methil, Kirkcaldy, Grangemouth, Leith, Rosyth and Burntisland Tiers 2 & 3 and Tier 1 upwards for all other spills in the Forth Harbour Area.

Usually the Initial Responder or On-Scene Commander will be able to deal with a Tier 1 without the need to activate an Incident Manager.

Responsibilities				
Overall response	Overall responsibility for, and control of all tactical aspects of the response to the incident.			
Stage	Actions	Additional Advice		
Response Initiation	On arrival at MEC establish incident status. Accept situation report & handover of response operations from FTNS Duty Officer. Ensure handover formally logged (refer Appendix 5 for log)	For Tier 2 & 3 incidents there will be immediate activation of the MEC.		
	If incident large and associated with potentially toxic vapours and /or requirement for a search and rescue function MRCC Aberdeen will call-out emergency services. Confirm if this has taken place.	t		
	 Ensure coverage of response team functions. 	Pre-planned allocation of functions is given in Matrix of Roles, Section 3.4. These are intended as guide		
	Appoint Marine Operations and MEC Operations Team Leaders.	only.		
	 Request Teams to maintain Status and Situation Reports. 			
	Brief Incident			
	Establish communication with vessel(s) / port/ facility involved in incident and request their current status and intended actions.	Ensure communications systems are operational; for		
	Ensure a VHF Channel has been designated for the Incident (Ch. 10 preferred if available).	incidents in one of the ports		
	Request details of the incident from the On- Scene Commander			
	□ If necessary, ensure samples are obtained	ESSENTIAL to feedback information to the MEC; ensure the On-Scene Commander does		
	Determine the status of the weather and marine conditions (refer Proformas in Appendix 5.7).	this.		
Initial Actions	Obtain results of spill assessment; establish incident response strategy and priorities.	For spills in one of the ports ensure liaison and regular sitreps from initial responder		



	 Assess need to close area/affected port to traffic other than affected vessel and response tugs. Notify FTNS. If a dispersant spraying response is required <u>this will need a rapid response</u>. Authorise mobilisation of required number of response vessels as soon as possible. 	FTNS will have made the initial request to spray dispersant. Check how this is proceeding and pass to appropriate personnel to complete and pursue.
Ongoing Activities	 Receive situation & status. Hold regular meetings with all team leaders. Ensure that measures have been taken to warn river users (including fishermen and inshore fisheries) about incident. Ensure appropriate time outs to assess the situation. 	Ensure that Planning Team has set up appropriate liaison between the team and local/national authorities (NatureScot, Marine Scotland, SEPA, local authorities, Environment Group (if set up).
	 Determine requirements for relief arrangements. Ensure that all handovers are logged Authorise release of equipment for counter pollution response Liaise with salvors, ship-owners as required. 	Close co-operation between the salvage operations and oil pollution response operations will be essential for minimising the environmental impact of a marine casualty.
	 Determine if cargo can be transferred if a vessel is involved with the spill; determine condition of vessel Liaise with MCA CPSO if in attendance. 	SOSREP has the power to intervene and run the Salvage Control Unit if he feels that the salvage response is unsatisfactory.
	 If salvage is involved in the response, liaise with Salvage Control Unit in MEC. Ensure information is supplied to Public 	(Refer Section 3). Agree any proposed plans for moving stricken vessel; SOSREP may require the vessel to be moved to a place of refuge. Refer Appendix 6 for places of refuge in the Forth
	Relations Unit for preparation of regular, updated media releases.	Note that if an Environment Group is convened liaison with the EG will be via an appointed Environment Liaison Officer
Final Action / Stand Down	 Confirm waterborne pollution has been cleared up to allow satisfactory operation of Harbour Area. Notify involved authorities of debrief meeting. 	



Clearwater Forth

4.5.4: Public Relations/ Information Unit

- Provision of prompt accurate information to the news media at the incident site.
- Obtaining up to date information on the incident and preparing regular Press Releases in association with other involved authorities.

Stage	Actions	Additional Advice
Response Initiation	Start Public Relations/Media Unit Log.	Establish communication routes with Forth Ports media consultants.
Initial Actions	 Prepare to draft initial press statement having first established incident facts including: Nature of incident Location and time occurred or began Facilities, vessels involved Casualties suffered 	Sample Press Statements are provided in Appendix 3. Note that it is important that individuals having a legitimate interest in the incident are provided with relevant facts with maximum speed and minimum confusion.
	 Type of oil spilt and estimate of quantity Cause of incident if known Actions being taken to combat spill Listing of agencies informed of spill 	(Under no circumstances should any personnel data be released before notification of next of kin).
	 Issue draft statement to involved third party for comment and approval. 	Refer to Appendix 3 for sample press statements.
	Issue initial press release. Bear in mind the following:	Determine likely media reaction: Local
	 Provide clear, concise and exact information; 	National
	 Address ONLY information known to be fact at the time; do not speculate or attempt to answer for others. 	International
Ongoing Activities	Attend planning meeting; provide data to Incident Commander on media issues associated with incident.	Constantly monitor news/press coverage. In particular look for gross inaccuracies that should be corrected
	 Arrange news conferences and/or interviews. 	in the next press release/conference. Ensure that an agenda is prepared
	Prepare ongoing press releases.	for all press briefings and be prepared to terminate briefings.
	Brief Command Team Leader/Team Leaders prior to press conferences.	For major incidents the MCA press officer will also be present. Ensure close co-operation between involved parties
Final Action / Stand Down	 Provide final press release and conference Provide Administration Unit with incident log. 	Include copies of all press statements, photographic documentation, etc.



4.6: Marine Operations

4.6.1: Team Leader

- Initial and continued assessment of pollution extent and characteristics.
- Establish source of pollution and determine possible methods of control.
- Determine most appropriate response strategy and implement.
- Liaison, as required with vessel owners, cargo owners, insurers, commercial salvors.

Stage	Actions		Additional Advice
Response Initiation	Start Marine Operations Incident Log. Receive appraisal and sitrep from FTNS and ensure the request to spray dispersant has been made.	pro	efer Appendix 5 for Incident Log oforma. It is most important that DGS ARE MAINTAINED.
	Assess status of incident. Confirm incident classification.		
	If incident appears to be a Tier 3 spill and requires assistance from national resources, immediately contact MCA.		
	Make a formal declaration on VHF 71 and other appropriate VHF channels that the MEC in now controlling the incident.		
Initial Actions	Mobilise appropriate resources to undertake detailed site assessment.		For spill assessment procedure refers to Section 5.
	Nominate a team member to establish and maintain communications link with site.		It is crucial that good comms. links are maintained with incident site
	Assess need for and Implement traffic clearance zones.		Aerial surveillance requires the use of specialist aerial
	For spills that are not retained in the enclosed dock areas determine requirement for aerial surveillance. Note that Tier 2 spills may require and Tier 3 spills will always require aerial surveillance. Request Planning Team to make immediate contact with MCA to discuss surveillance requirements.		surveillance aircraft (for specialist equipment refer Section 5). Specialist aircraft can be mobilised by the MCA. The CPSO will make the final decision to mobilise aircraft.
	Request MEC Team to obtain accurate weather forecasts and undertake Oil Spill Modelling		Ensure that you are initiating a response appropriate to the oil type and the geographical area of the spill.
	Conduct assessment meeting with appropriate personnel: Formulate outline response strategy. Refer Section 6 for Oil Spill Response Map and Preferred Strategy of Response guidance and		



Clearwater Forth

		Response Strategy for the Firth of Forth.	
		Options include:	For the Tiered Equipment
	•	Natural dispersion, monitoring and reporting ; Chemical dispersion; Mechanical Containment and Recovery; Shoreline Protection and Clean-up. Determine immediate and future equipment requirements. Place on stand- by / mobilise resources suitable for responding to outline strategy.	Response System refer to Section 6. This gives detail of response capability and mobilisation procedures.
		If a dispersant spraying option is carried out request Environment Unit to ensure that Marine Scotland are kept informed of all dispersant spraying operations.	
		Attend planning meeting / liaise with co- ordinating team in MEC. Develop detailed plan based on the outline response strategy	
		Implement marine aspects of plan.	
		Mobilise / place on stand-by further resources as required by the response.	
Ongoing		Regular assessment of response	
Activities		Regular liaison with vessel, cargo owners and salvors (as appropriate).	
		Monitor effectiveness of response strategy.	
		Monitor levels of equipment & manpower.	
		Attend regular planning meeting.	
		Stand-down / place on standby / mobilise equipment as agreed at planning meeting.	
		Provide information to PR Team.	
Final Action / Stand Down		Ensure water-borne pollution has been cleared for satisfactory operation of the Harbour/Port Area.	
		Stand-down remaining equipment and manpower.	
		Provide Administration Unit with incident log.	



4.6.2: On-Scene Commander

- Overall responsibility for optimum method for clean-up of the spill for the conditions that exist
- Continued on-site assessment of pollution extent and characteristics.
- Monitoring effectiveness of response strategy and deployed equipment.
- Close liaison with FTNS &/or MEC

Stage	Actions	Additional Advice
Response Initiation	If you have not been acting as Duty On- Scene Commander ensure that you have all details of spill surveillance and actions already undertaken.	Log handover and initiate own log If light products have been spilt there may be a vapour cloud. On no account allow response teams
	Proceed to incident site and determine further response actions required.	to enter as there will be a danger of asphyxiation. Do not attempt to
	Always ensure safety of response team members.	contain spills of these products in the vicinity of a vessel
Initial Actions	Confirm source and oil type (s) spilt and immediately notify FTNS/ MEC.	The type of oil spilt will determine the intervention response
	Ensure formal samples of spilt pollutant have been taken and retained	required. A table of oil types and preferred response actions is given in Section 5.
	Determine if current communication systems are fit for purpose if not notify FTNS/Marine Operations Team Leader	given in occurr d.
	Determine likely method of pollution control bearing in mind location of spill and type of oil. Response strategy guidelines for spills in the Clearwater Forth area are given in Sections 6. Any spill involving heavy fuel oil requires immediate mobilisation to site of Tier 2 response contractors.	Ensure that dispersants are NOT applied to areas where dispersant use is prohibited. Response strategies have been pre-agreed with plan consultees.
Ongoing Activities	Ensure correct deployment of response equipment and vessels. This action may be enhanced BY USE OF AERIAL SURVEILLANCE. If so contact MEC and request appropriate assistance	
	Monitor effectiveness of equipment deployed.	
	Monitor equipment levels; make recommendations to FTNS/Marine Team Leader on requirements for more equipment and associated manpower required at site.	
	Ensure that dispersants are NOT applied in areas where dispersant use is prohibited. Ensure that you are aware of the details in the response Strategy Map in Section 5. Ensure that dispersants are not used in the	



Clearwater Forth

	enclosed dock areas	
	□ If possible attend planning meetings.	
	Determine requirement for specialised personnel at site.	
Final Action /	Provide Administration Unit with incident log.	
Stand Down	Ensure all equipment is recovered and handed over to Logistics for repair, cleaning and return.	
	Provide Administration and Finance with list of damaged/lost equipment.	



4.7: MEC Operations

4.7.1: Team Leader

- Planning and preparation of medium-long term planning objectives.
- Collection and evaluation of information on all aspects of the incident.

	advising the CTL on liaison with various orga	
Stage	Actions	Additional Advice
Response Initiation	Start Team Incident Log. Incident log provided in Appendix 5.	Log keeper should be directed to carry out following activities:
	A Log Keeper will be appointed to support this team function.	 Maintain operation of white boards Produce coherent log of events which cross references all relevant media releases, meeting notes, assessment reports, briefing notes etc.
Initial Actions	Assess current situation from Command Team Leader & Marine Operations Team and develop situation map and resource status boards.	Ensure regular updates of situation map and resource status boards and attend planning meeting. This is most important for forward planning of incidents in both the ports and Firth of Forth
	Identify immediate problems and especially any facilities (e.g. power stations and the fishing community) which need to be informed of the possible approach of a slick or	Power stations are on the Activation List; however, ensure that they have been informed of any oil likely to approach water intakes;
	 dispersed oil Obtain Material Safety Data Sheet from ship owner or oil company. 	The Hound Point OSCP (available in the MEC) has a range of MSDS relating to oil products which are likely to be handled in the Harbour Area.
	If oil is likely to move into dock areas, inform docks in order that they can close dock gates and shut down	Wind direction will be important in determining drift of the slick.
	impounding pumps.Obtain weather reports. Ensure these are updated at regular intervals.	Refer to Strategy and Sea Zones Section 6, Firth of Forth Harbour Area: Site Specific environmental database and
	Carry out Oil Spill Modelling.	Priority Protection Areas Section 9; and Response Strategy Options Section 6 for
	From outline response strategy develop medium term plan with possible alternative strategies.	Ports of Rosyth, Methil, Kirkcaldy and Burntisland
	 As requested by Marine Operations contact MCA for aerial surveillance assistance. Contact details are provided in Section 8. 	Aerial surveillance requires the use of specialist aerial surveillance aircraft (for specialist equipment refer Section 5). Specialist aircraft can be mobilised by the MCA. The CPSO will make the final decision to mobilise aircraft
Ongoing	Arrange ongoing planning meetings, prepare brief agenda. Organise	Ensure incident boards are being kept up



Activities	attendees and ensure all team	to date with essential information
	leaders briefed prior to meeting.	 Weather and trajectory information;
	Obtain regular weather forecasts and obtain up to date Oil Spill Models.	Situation Map;Resource Status Boards
	Update situation map & resource status boards.	
	Present data for the next operational period at planning meetings.	Obtain briefing data from Marine
	In consultation with Incident Manager draw up emergency duty roster, and arrange accommodation and catering supplies.	Operations
Final Action /	Close out resource status boards.	
Stand Down	Provide Administration Unit with incident log.	



4.7.2: Environment Unit

- Liaise with external organisations
- Advise MEC & Marine Operations Team on key areas of environmental sensitivity
- Liaison with external authorities
- If Environmental Group is established determine a point of contact and ensure close working

Stage	Group is established determine a point of contact a	Additional Advice
Response Initiation	 Start Unit Incident Log Determine current status of incident 	Incident log proforma provided in Appendix 5. Log may be required for post incident inquiry. Ensure it is maintained
Initial Actions	 Obtain weather forecasts from Planning Team. Initiate running of slick predictions As soon as available pass results to Marine Operations and MEC Team. Refer to maps and tables in Section 9. and determine key environmentally sensitive sites in the vicinity of the incident site and along the predicted slick trajectory; including the fishing community and fish-farms Determine environmental requirements for aerial surveillance (e.g. bird concentrations); recommend requirement for aerial surveillance dependent on nature of incident and hydrocarbons spilt. If dispersants are to be used in areas other than those which do not require prior approval, obtain approval from Marine Scotland at earliest opportunity. They will provide information to FRS as detailed overleaf with the report form being completed and sent no more than 72 hrs following the initial spill. Liaise with relevant organisations who have an interest in the clean-up or protecting the water quality or coastal sensitivities. Include organisations opposite. When liaising ensure you have most up to date information. Give each organisation call back details (name, position, location, telephone no.) Attend planning meeting; provide advice on environmental implications of response 	To obtain approval for the use of dispersants Marine Scotland will require the information listed in the checklist overleaf. Ensure that Proforma in Appendix 5.8 is completed. An initial form should have been submitted by FTNS, check details and follow up with Marine Scotland. Ensure the following have been informed: NatureScot Scottish Environment Protection Agency Local authorities
Ongoing Activities	Aerial surveillance flights to monitor slick movement and bird movements.	



	Contact SSPCA regarding any oiled birds	
	Contact RSPB regarding any oiled wildlife	
	Provide information to/as requested by Public Relations Unit for inclusion into press statements.	Provide results to Marine Operations and MEC Team.
	Obtain updates on Oil Spill Modelling from MEC team.	
	Maintain liaison with environmental bodies and Environment Group if established	
	Attend regular planning meeting.	
Final Action / Stand Down	Obtain reports from any monitoring programmes submit to Administration Unit. Provide Administration Unit with incident log.	

GUIDELINES TO INFORMATION REQUIRED BY Marine Scotland IN CONSIDERING REQUEST FOR DISPERSANT SPRAYING APPROVAL

As much of the following information as possible should be provided when requesting approval for use of dispersants or when informing Marine Scotland of need to initiate a dispersant spraying strategy

- 1. Name of authority or organisation requiring approval.
- 2. Name of contact and telephone and fax number to be used.
- 3. Locality of spill preferably in degrees.
- 4. Oil type or description of appearance if not known. If crude what type?
- 5. Quantity of oil spilled preferably in tonnes.
- 6. Source of spill.
- 7. Potential for further spill.
- 8. Description of slick including dimensions and colour.
- 9. Volume and name of dispersant for which approval is requested.
- *10.* Other methods of response being applied or considered and assistance being sought (e.g. MCA, SEPA).
- *11.* Local fisheries considerations (such as seasonal fisheries, advice given to fishermen).
- 12. Local wildlife considerations (e.g. whether migrant birds are present).
- 13. Tide type and speed, and time of HW/LW particularly.
- 14. Wind and weather (such as "Moderate breeze NW" "Overcast drizzle").
- 15. Sea state.

For Contact Details for Marine Scotland see Forth Ports Emergency Contact Directory in Appendix 10.



4.7.3: Health & Safety Unit

- Advise the Incident Manager and On-Scene Commander of health & safety issues that could arise associated with the incident.
- Ensure that safe operating practices are implemented at the incident site.

Stage	Actions	Additional Advice
Response Initiation	Set up Health and Safety Unit and initiate incident log. This may be important for post incident meetings/inquiries	Ensure you are aware of the advice provided in the health and Safety Guidelines in
	Establish contact with emergency/medical services	Section 6
Initial Actions	Ensure that there is adequate manpower, equipment and services at site to provide for safe operations.	Determine type of hydrocarbon spilt and obtain data sheets from involved 3 rd party or
	Liaise with HSE / local authority safety inspectors onsite.	vessel
	Determine requirement for implementing Permit to Work system.	The permit should be designed to
	Attend initial planning meeting and advise on safety aspects of the response strategy including use of Personal Protective Equipment	 Special conditions Gas tests special hazards
	Establish safety induction facilities for contract labour	safety observerspecial equipment
Ongoing Activities	Attend planning meetings to provide advice and to raise ongoing or predicted safety issues	
	Monitor wellbeing of response personnel	
	Inspect operations to ensure conditions and practices meet minimum acceptable standards. If required halt any activity that may be considered dangerous or could lead to health problems. Immediately advise Command Team Leader	
	Examine operating and safety instructions for all equipment and products delivered to the inciden site. Ensure that full instructions and precautions are passed onto operators.	t
Final Action / Stand Down	Provide Admin/Finance Team with completed Incident Log	Complete internal incident reports, together with notes or
	□ If required ensure that HSE report(s) have been prepared and sent to the HSE	observations for use at post- incident meeting; submit these to the Admin/Finance Team.



4.7.4: Waste Management Unit

Responsibilities

- Arrangements for the collection, transport and disposal of oil and oiled wastes.
- Characterisation of oiled wastes in order to aid identification of most appropriate waste disposal facilities to handle the waste materials.
- Preparation of all necessary documentation and pre-notifications necessary to satisfy the Duty of Care and, if necessary, Special Waste regulations.

Stage	Actions	Additional Advice
Response Initiation	Start Waste Disposal Unit Log.	Incident log provided in Appendix
	If response is likely to generate waste disposal requirements establish early contact with SEPA.	5.
	Make contact with possible waste disposal facility operators to make arrangements for disposal of wastes arising.	
Initial Actions	Alert local authority equipment available for the transportation of oiled wastes; contact waste hauliers to establish availability of additional transport for oiled wastes.	Close-sided lorries and skip- trucks can be used for non-liquid wastes, and specialist vacuum trucks (flash point dependent) and
	Ensure hauliers' vehicles are carrying valid Registered Carriers Registration Certificates before they arrive on-scene	gully suckers are best for liquid oily wastes. If necessary, flat bed lorries can be used for either type of oily waste by transporting the materials in tanks or drums fitted with temporary covers.
Ongoing Activities	Obtain data on likely quantities of liquid oily wastes which are being collected.	Close-side lorries and skips should always be lined with
	Estimate quantities of non-liquid oiled wastes created primarily on shorelines.	heavy-duty oil resistant plastic sheeting necessary to prevent en- route pollution by oil dripping.
	Initiate appropriate Duty of Care and Special Waste documentation to cover all waste transport used, and ensure that the destination of the oiled wastes is extremely clear to the lorry drivers.	Note that the geographical requirement for the different types of waste transport is likely to change during incident.
	Ensure that transport of oily wastes is of a frequency sufficient to prevent the temporary storage being overwhelmed.	
Final Action / Stand Down	Confirm with all waste disposal facilities used that they have received all documentation required to cover the movement of oiled wastes to their facilities.	

Also refer to waste management guidance.



4.8: Logistics Team

4.8.1: Logistics Team Leader

- Responsible for arranging provision of facilities, services and materials in support of the incident.
- Responsible for arranging provision of additional communications.

Stage	Actions	Additional Advice
Response Initiation	 Start Team Incident Log Make contact with Command Team Leader and ascertain the extent of initial anticipated requirements for: 	Incident Log provided in Appendix 5. Ensure that all documentation is filed and retained for logging.
	Catering;	
	Accommodation;	
	Safety gear	
	Communications;	
	Marine response transportation;	
	Aerial surveillance.	
Initial Actions	Attend planning meeting and determine immediate future requirements.	
	Address the immediate needs at site.	
	Liaise with Finance Unit re Purchase Order and Applications For Expenditure (AFE) system that they are intending to run during the incident.	Ensure Equipment and Manpower Unit and Support Services & Transportation Unit are aware of the systems to be
	Ensure that an effective communication network is operative in MEC.	used.
	Appoint and supervise personnel to serve as telephone and fax operators.	
Ongoing Activities	Attend planning meeting	
	Address needs of field	
	Arrange provision of facilities, services and materials in support of the incident response.	
	Determine ETA's on equipment and personnel to be obtained	
Final Action / Stand Down	Ensure return of all equipment ; determine need for any remedial action re equipment	
	Provide Administration Unit with incident log.	



4.8.2: Equipment and Manpower Unit

Responsibilities

• Responsible for the provision of equipment and manpower requirements to support the incident response.

Stage	Actions	Additional Advice
Response Initiation	Start Unit Incident Log.	Incident log proforma provided in Appendix 5
	Determine requirement for additional manpower	Maintain a manpower allocation register
	In liaison with Marine Operations identify the extent of required radio network.	The MCA have a Sector Office at Port Edgar with limited manpower and recourses, Activation via Aberdeen MRCC
	Apply for equipment and record allocation of all radio equipment - initiate a communications allocation register.	
	Ensure that radio users are aware of channels to be used and call signs.	Lists of approved dispersants and suppliers are available on the MMO website. Details are provided in Appendix 4. Ensure that dispersant sourced is suitable for oil type. Liaise with Environment Unit
Ongoing Activities	Attend planning meetings to ascertain future requirements.	
	For all requests for materials and services that are received from the incident site ensure that an oil spill request form is completed including requisitioner's name; obtain authorisation from Logistics team Leader.	Ensure all requests include full description of items required, delivery point. Determine from Administration Unit order system to put in place.
	Establish a central point for receiving equipment and supplies. Allocate staff member to receive, check and log all incoming material.	
Final Action / Stand Down	Provide Administration Unit with incident log.	Ensure all incident documentation is provided with log.


4.8.3: Support Services/ Transportation Unit

- Provision of support services to back-up response operations.
- Organisation of transportation for pollution response equipment and manpower to designated locations.

Stage	Actions	Additional Advice
Response Initiation	Start Support Services/Transportation Unit Log	Refer to Appendix 5 for Incident Log
Initial Actions	Determine likely size of equipment and manpower requirements.	
	Designate appropriate rendezvous areas for equipment and manpower.	
	Obtain and assign cars, trucks, boats to response teams; ensure all assigned vehicles are logged and that the log is maintained.	
	Attend Team planning meeting.	
Ongoing Activities	Liaise with Logistics over catering/accommodation requirements.	
	Arrange for refuelling / maintenance requirements for water craft and road transport	
	Organise as required transport to site of equipment and manpower.	
	Arrange transportation for visitors (e.g. Head office personnel, government representatives) to view and inspect field operations.	
	Designate preferred access routes.	
	Ensure that Team Leader is informed immediately of any problems associated with transportation of resources to site.	
Final Action / Stand Down	Organise return of equipment / vehicles to appropriate location.	
	Inform Logistics of any damaged or lost equipment	
	Provide Administration Unit with copy of incident log.	



4.8.4: Communications System Unit

<i>Responsibilities</i>Provision of communications systems to back-up response operations.				
Stage		Actions	Additional Advice	
Response Initiation		Set up Communications Unit in MEC and initiate team incident log	Refer to Appendix 5 for incident log	
Initial Actions		Determine likely size of communications requirements.		
		Ensure that Communications specialists are available.		
		Ensure that marine weather forecasts are accessible	Ensure that explosion proof radios that will not interfere with radio control signals are used in	
		Ensure that all vessels, helicopters, supervisors involved in the response operation are able to communicate with each other	hazardous atmospheres	
		Ensure individual work crews use separate frequencies	With each radio supply list of	
		Ensure you record the issue of all radio equipment in a communications equipment allocation register	personnel using the same channel	
		Attend Team planning meeting.		
Ongoing Activities		Determine requirement for UHF or VHF repeater stations for the response	Note that for a major spill a large number of communication channels	
		Request support unit to organise as required transport to site of equipment	will be required for: VHF marine and Aircraft channels	
		Monitor communications systems carefully.	Additional marine and UHF	
		Arrange for battery charges/recharging as required.		
Final Action / Stand Down		Organise return of equipment to appropriate location.		
		Inform Logistics of any damaged or lost equipment.		
		Provide Administration Unit with copy of incident log.		



4.9: Administration & Finance Team

4.9.1: Team Leader

- Keeping accurate financial records for subsequent preparation and support of claims for the recovery of money spent.
- Financially securing the requirements of Logistics Team.
- Establishing appropriate filing systems to ensure that accurate records of what was done and why are available in support of financial claims for recovery of money spent.
- Provision of secretarial services.
- Implementing Security Arrangements as required.

Stage	Actions	Additional Advice
Response	General Start Team Incident Log.	Refer to Appendix 5 for Incident Log
Initiation	Set up Administration, Insurance & Claims and Legal Units	
Initial Actions	Hold team meeting in time for planning meeting.	
	Attend planning meeting and inform other teams of financial and administration systems in place and legal advice available.	
	Determine requirement for additional communications systems, e.g. more lines, more phones, etc.	
Ongoing Activities	Attend planning meeting and notify teams of any necessary changes to operating systems.	
	 Financially secure the requirements of Logistics Team. 	
	Keep accurate financial records for subsequent preparation and support of claims for the recovery of money spent	
Final Action / Stand Down	Provide Administration Unit with incident log.	



4.9.2: Administration Unit

- Responsible for setting up filing system to keep records of all aspects of the incident response.
- Responsible for tracking ALL movements of response personnel.
- Administration of Security Arrangements.

Stage	Actions	Additional Advice
Response Initiation	Start Unit Incident Log.	Incident log proforma provided in Appendix 5.
Initial Actions	Determine extent of initial administration services required and likely requirements.	
	Ensure telephone switchboard is suitably manned. Request operators to maintain a full record of all incoming calls	Record the following: Time/date;
	Determine requirements for the record filing system and best method of fulfilling those requirements. The records will have a wide range of uses including:	 Caller's name, company; Recipient of the call; Any messages (ensure these are passed on
	 Serving as a basis from which reports of the operation can be prepared; Explaining and justifying the expenditure; 	quickly to appropriate team).
	Supporting claims for the recovery of the money spent;Dealing with criticism of the response	Ensure that Status Boards are either photographed or printed off before they are wiped clean
	Record keeping should err on the side of too much rather than too little detail.	for re-use
	Determine immediate requirements for security, consider the following:	
	 Initial requirement for Police assistance to establish access control to MEC, Establish pass system. 	Provide Team Leader with all necessary information on Administration systems.
Ongoing Activities	Determine requirement to contract in security services & secretarial and other services from local agencies.	
	 Obtain and file the following on a daily basis Team and Unit Logs; 	
	 Information received; Orders given; Actions taken; 	
Final Action / Stand Down	 Brief Team Leader prior to planning meetings. Finalise Unit Incident Log. Complete all aspects of the incident filing system ready for post incident enquiry. 	



4.9.3: Claims & Insurance Unit

- Maintain and keep full records of all financial transactions associated with the incident.
- Prepare daily financial reports on expenditure.

Stage	Actions	Additional Advice
Response Initiation	Start Unit Log	Incident log proforma provided in Appendix 5
Initial Actions	Determine extent of financial services required and anticipated levels of expenditure short term.	
	Establish bank/cash arrangements. Set-up petty cash system if required.	
	Set-up dedicated financial system for the incident. If required request Equipment and Manpower Unit to obtain computers and accountancy staff.	
	Establish filing system, in conjunction with Administration Unit, for:	
	Suppliers/contractors records;	
	Financial correspondence;	
	Purchase orders;	
	Contracts.	
Ongoing Activities	Provide daily report to Command Team Leader including the following information:	
	Estimated costs committed that day;	
	 Estimated costs committed to date, broken down by: Manpower Material Equipment hire/transportation Food/accommodation Major items of expense 	
	Provide forecast costs.	
Final Action /	Provide Administration Unit with incident log.	
Stand Down	Provide input for compensation claims.	



4.10: Legal Unit

- Provide guidance on all legal matters related to an incident.
- Determine the responsibility and liability for the incident and resulting clean-up.
- Advise the Command Team Leader on all steps necessary to minimise any liabilities arising from law.
- Undertake main liaison with Insurance Companies & Brokers.

Stage	Actions	Additional Advice
Response Initiation	Start Legal Unit Log	Refer Appendix 5 for Incident Log
Initial Actions	Attend planning meeting.	Refer Appendix 1 for legal situation
	Evaluate the legal implications of proposed response strategy and advise the Command Team Leader of any legal matters arising.	Siddion
	Contact Forth Ports Insurance Brokers.	
Ongoing	Attend planning meetings.	
Activities	Monitor situation and proposed plans of action and advise Command Team Leader of possible changes in legal issues.	
	Maintain liaison with Insurance Companies/Brokers.	
Final Action / Stand Down	Assist in the preparation of any insurance claims. Provide input for compensation claims.	Refer Appendix 1 for legal situation
	Provide Administration Unit with incident log.	



Section 5: Spill Assessment & Health and Safety Guidelines

5.1: Spill Assessment Guidelines and Incident Evaluation Guidelines

5.1.1: Introduction

Once an oil spill has occurred it is extremely important to obtain the most accurate information on spill size and type, location and environmental factors. Without this information the rest of the oil spill response cannot be undertaken.

5.1.2: Initial Evaluation Checkpoints

A spill assessment and incident evaluation checklist is given overleaf. The following should be borne in mind:

- 1. The spill assessment and initial incident evaluation should be initiated by the On-Scene Responder.
- 2. Information should be relayed to FTNS/MEC as quickly as possible.
- 3. The spill tracking and evaluation should initially be carried out using the duty vessels.
- 4. For large spills this tracking should be backed up by aircraft overflights once an appropriate aircraft has been mobilised.

Bear in mind the following when undertaking surveillance/responding to pollution reports:

- 1. It is difficult to distinguish the oil from a variety of other unrelated phenomena. These include cloud shadows, ripples on the sea surface and differences in colour of two adjacent water masses.
- 2. The appearance of tank washings and bilge discharges as a single elongate slick usually distinguishes them from accidental spills.
- 3. Crude oil will change in appearance soon after spill; in initial stages, the thicker parts will appear as dense, black areas, but as emulsification takes place, the colour will change to brown, orange or yellow.
- 4. When tracking a slick bear in mind that the thickness will vary, with the thickest portions at the leading edge

For spill assessment use proforma in Appendix 5.5 or bear in mind the following:



Table 5.1 Spill Assessment Checklist

STEP	CHECKPOINTS	
Determine Source of Spill	• If unknown attempt to trace the source of pollution using colour as a guide (increased thickness towards source)	
Assess Safety Hazard	 Determine safety hazard to personnel and potential hazards to response personnel. Is there potential for fire or explosion? 	
Establish Tier of Spill	Tier 1/2/3?Is spill on-going or a one off event?	
Estimate Approx. Spill Size and Thickness	If the quantity of oil is not known, determine the dimensions of the slick on the water surface and the volume of spilt oil. Conduct by direct observation from duty vessel. A guide to the relationship between appearance, thickness and volume is	
Assess Prevailing Weather & Sea state Conditions	 provided below. Wind speed and direction (Note a Beaufort Wind Chart is provided in Section 4) State of tide and current speed Wave height 	
Determine Direction & Speed of Oil Movement	 Predict movement using Oil Spill Modelling Software or manual method of slick prediction (next page) Verify with spill surveillance using tug / aircraft for large spills of crude oil Estimate impact time to beaching. 	
Obtain Sample of the Oil	 A sample of the spilt oil may help to determine the spill source & may be important for post-incident inquiry. Procedures for sampling spilt oil are provided below. 	
Identify Potential Affected Shorelines	 Identify threat posed to vulnerable resources e.g. saltmarsh, mudflats, wintering bird populations, tourist beaches in summer – refer to environmental database in Section 9. Observe and chart the current position of the slick; likely future movement and spread to next tidal cycle. 	



5.1.3: Slick Predictions

Oil spill modelling is carried out to predict likely distance and direction of movement of the slick predict any threatened coastlines, the scale of likely pollution and may also be used to simulate the likely fate and behaviour of the spilt oil.

Modelling may be carried out using the following methods:

- Using Oil Spill Modelling Software, a computer based slick trajectory model which will be conducted by the MEC.
- Manual method of slick prediction to check the output of the oil spill modelling software.

Both methods are based on fact that the oil slick will move at approximately 100% of the tidal current speed and 3% of the wind speed.

5.1.3.1: Oil Spill Modelling Software

The software has an in-built data base of various oils and their properties and a built in module for generating weather, tidal and current data. Required input data by the modeller for modelling includes:

- Location of spill
- Oil type and size of release
- Sea and air temperature

The MCA will also be able to provide a digital model on request, to cross check accuracy

5.1.3.2: Manual Method of Slick Prediction

Slick movement may also be predicted by manual vector addition on the surveillance vessel, or in an emergency when access to a computer programme is not feasible. The manual method of prediction of slick movement is based on a simple vector calculation where the vectors of wind speed and tidal current are added together utilising 3% of the wind speed value and 100% of the tidal current speed. It is important to remember that this method can only provide an approximation of slick movement, and in no way should be regarded as a substitute for continuing monitoring actual slick movement throughout the oil spill response or for the more sophisticated slick predictions generated by computer models. However, the method is rapid and can provide a valuable rough guide to possible slick movement, which may assist in the formulation of an appropriate response strategy.

1. Establish the position of the slick.

2. Establish the tidal rate or strength (in knots) and direction (in degrees) for as many hours as is required. This information is available from the port's hydrographic data as well as from tidal stream atlases, charts and nautical almanacs.

3. Plot the position of the slick on the most appropriate chart.

4. From that position, draw a vector in the direction that the tide is moving. The tidal rate for the first hour in this example has been established as being 1.5 knots (1.5 nautical miles per hour) and the direction is 0200. From the initial slick position, measure



1.5 nautical miles along the tidal vector. This position is where the slick would have travelled to in that first hour if it had been driven by the tide alone.

5. Obtain as accurate an assessment of the wind speed and direction as possible (the vessel on scene may be able to supply this information). If necessary, convert the wind speed into knots. Multiply the wind speed by 0.03 (the slick is affected by 3% of the wind speed). In this example the wind speed was 11.5 knots which when multiplied by 0.03 is 0.35 knots and the direction is 0900 (a westerly wind). Therefore, in one hour the slick would have moved 0.35 nautical miles in the direction of the wind. The above information will allow a wind vector to be drawn.

6. The slick will be driven by both the wind (3%) and the tide (100%) so it is necessary to combine the two vectors. The wind vector (calculated in step 5) should be drawn from the end of the tidal vector (refer to the diagram overleaf).

7. A line drawn from the initial position of the slick to the end of the wind vector is the resultant vector and indicates the direction and the distance of slick travel in that hour.

8. To predict the likely movement of the oil for another hour, the process should be repeated using the resultant position as the start point for drawing subsequent vectors.



Figure 5.1: Manual Method of Oil Slick Prediction



5.1.4: Oil Quantity Estimation Guide

The quantity of spilt oil may be estimated using the following oil quantity table taken from the Bonn Agreement Pollution Observation Log. This should be used to estimate the quantity of oil spilt if direct information is not available. *Visual inspection can be carried out from the vessel, but best estimates are made during aerial surveillance flights. When using this colour method to estimate spill size, bear in mind that the slick is likely to be patchy and that the entire area of the slick may not be visible. Examples of slick colour are provided in Figure 5.3

It is important to determine the size of the spill and to classify it. The best estimate of spill size will come from plant information, for example, the volume of oil in vessel tanks, pumping rate and duration, diesel in transfer hose. If spill size cannot be determined from plant information, an estimate the following procedure has been taken from the Bonn Agreement Oil Appearance Code (BAOAC).

Table 5.2 details the current Bonn Agreement colours that should be used to quantify the approximate size of any spill and Table 5.3 provides a conversion chart. Calculation of the volume of oil spilled from the appearance of oil film on water is as follows:

- * Estimate total size of the area as a square or rectangle (in km) i.e. maximum extremities of the slick.
- * Assess the area affected by the slick in km² calculated as a % of the total area in (refer Figure 5.2 below).
- * Estimate the area covered by each colour of oil, calculated as a % of the total area affected.
- * Multiply the area covered by each colour by the appropriate figure in the oil quantity Table 5.2.
- * Adding all of the colour figures will give the total quantity of oil in m³ within the slick.

Estimating Oil Quantities 2002)				
Code	Description - Appearance	Layer Thickness Interval (µm)	Litres per km ²	
1	Sheen (silvery/grey)	0.04 to 0.30	40 – 300	
2	Rainbow	0.30 to 5.0	300 – 5000	
3	Metallic	5.0 to 50	5000 – 50,000	
4	Discontinuous true oil colour	50 to 200	50,000 – 200,000	
5	Continuous true oil colour	200 to More than 200	>200,000	

 Table 5.2 Oil Quantity estimation by Colour (current Bonn Agreement Code of Practice for Estimating Oil Quantities 2002)

 Table 5.3: Containment Factors

1 tonne*	7.45 bbls		
1 bbl	42 gallons		
1 mile	1,760 yards		
1 sq mile	3,097,600 sq yards		
1 mile	1.61 km		
1 sq mile	2.59 km ²		
* 1 toppo calculated at 844 kg/m ³			

* 1 tonne calculated at 844 kg/m³



SPORADIC 1* - 10%	PATCHY 11 - 50%		BROK 51 - 9		CONTINUOUS 91 - 100%
1% 10%	20% 30%	40%	60% 70%	80%	91%

OIL COVERAGE ESTIMATION CHART

Figure 5.2: Oil Coverage Chart







5.1.5: Spilt Oil Sampling

Where an oil pollution incident is thought to be a result of an illegal operational discharge, a sample of the spilt oil should be taken. If samples may be used in connection with legal proceedings then the following procedures should be implemented, as summarised from the MCA STOp Notice 4/2001. For the MCA link to the Stop Notices refer to Appendix 8.

MCA recommend that 3 samples be collected, the first for analysis to MCA, the second to be provided to the owner or master of the suspect pollution source, and the third for production in court.

Samples should be submitted to the MCA's contractor laboratory. Once a sample has been taken, agreement must be obtained from the MCA Counter Pollution Branch before it is analysed. Once agreement has been obtained, the Counter Pollution Branch will contact their analysis contractor to arrange for the sample to be collected by courier and analysed.

Samples should be labelled correctly and packed in a suitable container to avoid breakage.

NO.	ACTION	NOTES
1	The sample should be taken in a clean glass container as provided in the spill sampling kit.	Metal or plastic containers should be avoided since they may interfere with subsequent fingerprinting
2	Care should be taken to sample the oil only	The field vessel is provided with dedicated oil sampling kits which include all the equipment necessary for the sampling of spilt oil on the sea surface
3	Minimum of two samples should be taken. Preferably take three. The following sample sizes provide guidance to what is required for laboratory analyses.	For freshly spilled, relatively non-emulsified oils take at least 30ml to divide between the 3 10ml sample sizes required for lab. analysis; For emulsions take at least 500ml, to be divided between the three samples required for lab. analysis If these quantities cannot be obtained a sample should still be taken.
4	Carefully store samples; these should be sealed to avoid tampering. All samples, once bottled, should be placed in plastic bags and sealed.	Ensure jars are stored in safe place and in a cool dark area away from heat (preferably (<5°C)
5	Label or accompanying documentation should contain the	Sample Identification No. and initials of person in charge of sampling

Table 5.4 Sampling of Spilt Oil



following information.	Description of samples (eg crude oil, fresh, weathered, water-in-oil emulsion)
	Date, time and place of sampling;
	Name of Company;
	Method of sampling;
	Purpose for which sample was taken;
	Source if known or suspected;
	Metocean conditions at time of sampling
	Particulars of any photos or supporting evidence

5.1.6: Assessing Oil Dispersability

5.1.6.1: Identifying Dispersed Oil

Note the following:

1. Some things in and on the water, such as suspended solids or algal blooms, can resemble dispersed oil.

2. The appearance of oil slicks and subsurface plumes is affected by factors such as oil characteristics, time of day (different sun angles), weather, sea state, and the rate at which oil disperses.

3. Once dispersant has been applied to a slick, you may observe colour changes in emulsions (mousse), produced as the demulsifying action of the dispersant reduces the water content and viscosity of the emulsion. Demulsification also can produce changes in the shape and size of a slick: as demulsification pushes water out, the slick may appear to shrink in area.

5.1.6.2: Observing when Dispersion has Occurred

Note the following:

1. A visible subsurface plume of dispersed oil indicates that an application of dispersant is working. When no plume is visible in the water column, it is difficult to determine whether the dispersant is working, but does not definitively mean that the dispersant is not having an effect.

2. Subsurface plumes of dispersed oil typically have a cloudy appearance, and can range in colour from brown to white. Some are not visible. When dispersant is working, oil remaining on the water surface also may change colour.

3. In some cases, you may not be able to see a subsurface plume even when one is present. When the water is turbid, you may not be able to see a plume. Sometimes,



remaining surface oil and sheen can mask oil dispersing under the slick, making it hard for you to see the plume.

4. A subsurface plume may not form instantaneously once dispersant has been applied to a slick. In some cases, such as when oil is emulsified, it can take several hours for a plume to form. In other cases, a visible plume may not form (you then may wish to use sampling to learn whether dispersion has occurred).

5. A change in the appearance of a treated slick, compared with an untreated slick, might indicate that the dispersant is working. However, a difference in appearance alone is not enough of an indication to be sure that the dispersant is having an effect

6. A clear stretch of water left in the wake of a dispersant application vessel can appear to represent successful dispersion of oil. However, areas of clear water can be created as the vessel wave breaks a path through the oil, either physically parting the oil or mechanically dispersing it. Mechanically dispersed oil will recoalesce and float to the surface.

7. When initially applied, dispersants sometimes have a herding effect on oil, making a slick appear to be shrinking when, in fact, the dispersant is "pushing" the oil together. This effect results from the surfactant action of dispersants, which exerts a horizontal spreading force on thin oil films. This effect can cause parts of an oil slick to seem to disappear from the sea surface for a short time.

5.1.6.3: Field Testing for Dispersability of Spilt Oil

If the dispersability of the spilt oil is in doubt, or the ability of the dispersant to treat the oil type spilt, run a field dispersability test using dispersants and equipment available on the vessel. Do this as quickly as possible after taking the sample.

	WATER BORNE VESSEL MOUNTED DISPERSANT SPRAYING TESTING
1	Test the amenability of the spilt oil to dispersants following the sampling of the slick. Do this as quickly as possible after taking the sample. Test carried out as follows: fill a clean screw top jar with seawater; carefully place about 25ml of spilt oil on the surface; add about 1 ml of dispersant (ca. 2 drops) onto the surface. Shake the jar; if the oil does not rise again to the surface but breaks up in the seawater, the slick should be amenable to dispersant spraying.
2	Undertake calculations to select correct pumping rate and boat speed in relation to nozzle size of equipment.
3	Initially spray boat should enter the oil on surface at recommended speed to spray at a constant rate and agitate the area.
4	Watch oil for evidence of dispersion.
5	As dispersion is achieved it will produce a "smoke plume" in the water. The dispersion will vary in colour between dark and light brown.
6	If dispersion is not taking place large oil droplets will be evident. If this is the case STOP spraying.

Table 5.5 Field Testing for Dispersability of Spilt Oil



5.1.7: Aerial Surveillance

Aerial surveillance is an extremely important part of the marine response to large spills. It should be used for assessing the location and extent of the oil slick, and verifying the predictions of slick movement made as well as progress of natural dispersion and emulsification. It should also be used to direct response operations, be they dispersant spraying, mechanical containment and recovery or, indeed, both.

Aerial surveillance requires specialist aircraft fitted with the following equipment:

- Sideways Looking Airborne Radar (SLAR) for large area, long range detection (20 miles for sea surface and 40 miles for detection on shipping patrol),
- Ultra Violet (UV) sensor for accurate area measurement
- Thermal Infra-Red (IR) sensor for relative oil thickness measurement.
- Night Identification System, which enables the name and port of registration of any vessel to be taken in darkness.
- Digital video and still cameras to provide photographic evidence Frequency of Flights

MCA aerial surveillance capability is fitted with these requirements. Mobilisation of this capability will take place at the discretion of MCA in consultation with Forth Ports.

Aerial surveillance should be carried out for Tier 2 and 3 spills and should be initiated as quickly as possible.

Following the initial flight, subsequent flights should be made regularly, commonly at the beginning and end of the day so that the results can be used to plan the response operations.

5.1.7.1: Flight Plan

A "ladder search" is the most economical method of surveying a large area of water. Since floating oil has a tendency to become aligned in long and narrow windrows parallel to the direction of the wind, it is advisable to arrange a ladder search across the direction of the prevailing wind to increase the chances of oil detection.







5.2: Health & Safety Guidance

Safety must always be the prime consideration during an oil spill response. <u>Remember</u>, <u>every spill situation has potential safety and health hazards</u>.

5.2.1: Safety Guidelines for Initial On-Site Assessment

Before commencing operations ensure safety and health risk evaluations are carried out The safety of the general public as well as port employees, visitors and contractors must be taken into account. Until it is established otherwise, assume that the spill is giving off lighter fractions that are flammable and explosive. Always approach the spill from upwind as there may be a vapour cloud. Close approach to the spill point should not be made unless the area is considered SAFE. Eliminate all possible sources of ignition. Any spill involving confined airspace in which vapours may accumulate should be treated in the initial stages as a potentially explosive situation. Until it is established otherwise, assume that the spill is giving off hydrogen sulphide, a highly toxic, colourless gas with an odour of rotten eggs; as even small concentrations cause olfactory fatigue, the sense of smell should not be relied upon to detect this gas. 4 If hydrogen sulphide is detected at hazardous levels the area should be evacuated immediately and the on-site response suspended until personnel can be equipped with suitable PPE, or until levels drop to safe and tolerable levels.



5.2.2: Safety Measures for On-Site Response Personnel

- Individuals should not work alone
- If possible a safety boat should be on station for the duration of any boom deployment.
- ↓ Personnel should not enter tidal mud flats areas on foot
- No personnel should go below high water unless a "Safety Officer" is in a secure position to monitor their safety throughout deployment.
- An adequate supply of clean fresh water should be situated at or near the response location(s) for immediate First Aid use.
- Levels of flammable vapours and hydrogen sulphide should be regularly monitored in the early stages of the spill response.
- Access to the site should be controlled.

5.2.3: Personal Protective Equipment

All on-site response personnel should be equipped with appropriate PPE.

For personnel who are likely to handle or come into contact with oil or dispersants the following PPE should be supplied:

- Overalls (preferably disposable)
- Safety helmet
- Safety boots
- \rm Safety glasses
- Gloves (preferably PVC)

Personnel involved in spraying operations should be equipped with:

- Full cover plastic overalls
- Safety helmet
- ↓ Face visor (or safety goggles and mouth and nose mask)
- PVC gloves
- Chemical resistant safety boots
- Safety boots
- Lifejacket (if working from a boat or adjacent to water)



5.2.4: Open Water Safety Response Tips





5.2.5: Dispersant Response Option Safety Tips

Dispersant Response Operation Safety Tips
Assess the routes of possible exposure to dispersant chemical
Provide PPE (see above) to guard against each and every route, ensure all PPI is compatible and fits wearer
Keep decks clears and dispersant free by regular washing
4 Head spray vessels into wind where possible
Make sure PPE is resistant to dispersant in use
4 Avoid uncontrolled release of dispersant
 Avoid unnecessary and prolonged contact with BOTH spilt oils and chemical dispersants
 Always refer to the Material Safety Data Sheets prior to commencing operations (available in FTNS MEC)
Ensure that small craft not involved in the response are directed to keep clear of dispersant operations.

5.2.6: Health Effects of Exposure to Spilt Hydrocarbons

Crude oil contains substances that can cause acute as well as chronic health effects. Primary health risks with fresh crude are related to the inhalation of:

Substance	Health Risk
Hydrogen Sulphide	Toxic
Benzene	Carcinogen
Total hydrocarbons	Irritant, toxic, carcinogenic dependant on crude type
Oxygen displacement	Asphyxia

In addition prolonged or repeated skin contact may result in dermatitis as well as increased body uptake of some crude oil compounds.



5.2.7: First Aid for Contact with or Ingestion of Oils and Dispersants

5.2.7.1: Eyes

For oil or dispersants the eyes should be rinsed thoroughly with copious quantities of fresh clean water for at least for at least 1-2 minutes. A medical professional should be consulted as soon as possible for advice on further treatment that may be required.

5.2.7.2: Ingestion

Ingestion of oil or dispersant should be initially treated by drinking at least half a pint of milk. Vomiting should <u>not</u> be induced. Professional medical advice should be obtained as soon as possible.

Although dispersants are generally of low toxicity, a copy of the Material Safety Data sheet should if possible be made available to the medics treating the casualty, as this will provide details of any hazardous components and possible harmful effects.

5.2.7.3: Skin Contact

Oil on the skin should be cleaned off with an approved cleanser for this purpose (such as Swarfega), followed by thorough washing with soap and hot water. Solvents or degreasers such as paraffin or white spirit (turpentine substitute) should <u>not</u> be used to remove oil as these may cause industrial dermatitis; on no account should coarse abrasives be used on the skin.

5.2.8: General Hygiene

Hands and any exposed skin should be washed thoroughly before eating after any contact with oils or dispersants Even if otherwise permitted, smoking should be discouraged when handling dispersants or oil to help avoid any mouth contact. Barrier creams should be used.

Response personnel should <u>not</u> carry oily rags, handkerchiefs or other items that have been heavily oiled in clothing pockets so as to avoid prolonged contact with oil permeating the clothing

Response personnel must not wear clothing which has become heavily soaked with oil or dispersant for extended periods. Such clothing must be exchanged for clean as soon as possible and disposed of as oily waste.



Section 6: Firth of Forth Response Options and Guidelines

6.1: Purpose of these Guidelines

The purpose of this section is to provide teams who are undertaking a response to spills of waterborne hydrocarbons in the Ports, enclosed docks and Firth of Forth Harbour Area with guidelines to implementing the appropriate response option(s) to a spill incident. When using this section as a guide to formulating a response to a spillage it must be borne in mind that:

- A precise response strategy can only be decided at the time of the spill; where
 response techniques such as containment and recovery, exclusion and diversionary
 booming are recommended as possible first alternatives it is important to remember
 that their feasibility is dependent on weather conditions, sea states, type of oil spilt
 and other circumstances that cannot be pre-determined.
- Co-ordinators and response teams must be prepared to adapt their actions as the spill develops and as conditions dictate.
- Flexibility is an absolute requirement of the response teams.

It is important to note that all these control and clean-up procedures and written assuming that the area has been declared safe to work in and that all response personnel are wearing protective clothing and have been acquainted with the health and safety guidelines in Section 5.

6.2: Oil Types, Characteristics and Fate & Behaviour when Spilt on the Surface of the Water

Utilising a large database of oil properties, a model of oil types and their behaviour when spilt has been developed by ITOPF, 1987 with oils being allocated to one of four groups or types. The model is illustrated in Figure 6-1 and examples of the different oil types and groupings given in Table 6-1. The table also provides a summary of potential response options for the different groupings with procedures for these response options given in the following sections.



Figure 6.1: ITOPF model of oil types and behaviour



Clearwater Forth

6.3: Oil Types and Counter Pollution Strategies

Once the type of oil that has been spilt in the harbour has been confirmed, ensure that the type of response that is initiated is suitable for the oil type. Refer to Tables 6.1 and 6.2.

Table 6.1 Oil Types Behaviour When Spilt on the Water Surface and Counter Pollution Response Options

GROUP	BEHAVIOURAL CHARACTERISTICS	POSSIBLE RESPONSE TECHNIQUES	NOT ADVISABLE	HYDROCARBON TYPES FIRTH OF FORTH HARBOUR
Group 1	Very low viscosity, flammable liquids. The liquids in this group are highly flammable, give off potentially toxic vapours when evaporating and could form a vapour plume. As shown in Figure 6.1, these substances will evaporate rapidly, within hours of the spill and are non-persistent. They do not increase in bulk as a result of emulsification and will be removed from the water surface rapidly by the processes of evaporation.	Natural dispersion and monitor Naked lights or other possible sources of ignition must be avoided. Radio and radar equipment may constitute a hazard. The oil and atmosphere should be sampled at regular intervals to check flashpoint and flammable gas concentration until the light compounds have evaporated and the flashpoint of the oil is well above 60°C (IMO, 1988). The safety of any passing vessels should be taken into consideration.	Any intervention response. These oils are potentially hazardous and should not be subject to an intervention response until it is determined that the area is safe and the vapour cloud dispersed.	Unleaded motor spirit Leaded Motor spirit; Range of hydrocarbon distillates shipped out of Grangemouth jetties
Group 2	Low viscosity, light fuel oils and refined products. These hydrocarbons will evaporate, are extremely rapid spreading and form a slick with little interaction with the water. As shown in Figure 6.1, under certain circumstances they may increase in volume. These hydrocarbons are non-persistent and the major part of the spill will be removed from the water surface rapidly through the processes of evaporation and natural dispersion.	Natural dispersion and monitor - i.e. leaving the oil alone to disperse naturally - may be the best option especially in cases where the slick will not threaten sensitive areas or where the spill is small and rapidly naturally dispersing. Vessels may be moved through the slick to assist in break-up of the oil.	Although corralling of these oils may be possible by use of booms in the enclosed areas in the ports and docks, the very rapid spreading which is characteristic of these oils coupled with the difficulty of deploying booms may inhibit corralling in the open water of the Firth	derv, gas oil, jet A-1, kerosene (ATK, RSK, Jet A-1)



FORTH PORTS LIMITED

Clearwater Forth

Clearwater Forth OSCP Page 96 Version 3

GROUP	BEHAVIOURAL CHARACTERISTICS	POSSIBLE RESPONSE TECHNIQUES	NOT ADVISABLE	HYDROCARBON TYPES FIRTH OF FORTH HARBOUR
Group 3	Medium viscosity crude oils. Substances that float on water. Will evaporate, but rate will be dependent on the volatility of the crude oil; will also form water in oil emulsions which are then more difficult to treat. Most crude oils are persistent, especially when they have started to emulsify. They may increase in volume by up to three times as a result of emulsification. The bulk of the slick will be removed from the water surface by natural break-up processes within a week of the spill. Residual oil will remain. Will increase in viscosity over time with the action of wind and waves.	Containment and recovery of the spilt oil as close as possible to the source of the spill. Dispersant spraying; may in some cases offer a net environmental benefit in order to prevent oil beaching in key priority sensitive areas, particularly in the deep and open waters of the outer Firth. For optimum results utilise a dispersant that is known to disperse the particular oil type.	The oil should not be left to disperse naturally unless adverse weather leaves no option	Crude oil; light- medium fuel oils
Group 4	 High viscosity fuel oils. These are used to fuel product and crude oil carriers. Heavy crude oils These are substances which float but which may become solid or semi solid when interacting with water surface. If mixed with sediment could have the potential to sink. There will be little evaporation from these oils and these oils are highly persistent when spilt. Will greatly increase in viscosity over time by the action of wind and waves. As shown in Figure 6.1 may increase in volume by 2 times and are highly persistent – if not treated may persist for months or even years. 	Vacuum pumping may be used on both surface and subsurface fuel oil in port areas Dispersant spraying using an appropriate dispersant <i>may</i> be an option for heavy crude oils in open water areas. Booming of heavy fuel oil around vessels and mechanical containment and recovery using specialised equipment	Sinking agents	Heavy crude oil; heavy fuel oil



6.4: Oil Groups, Spill Sizes and Counter Pollution

For each oil type group spill response methods considered most appropriate are recommended in Table 6.2. Note that responses are given by oil grouping and Tier of spill for both open water situations and nearshore/port situations.

	Open	water re	sponse	options		shore / respon			ocks	
Oil Type Group	Natural dispersion & monitor	Containment and recovery	Diversionary booming	Dispersant use (following consultation)	Shoreline booming & oil recovery	Containment around vessel	Dispersant use	consultation	Natural dispersion & monitor	
	•	×	×	×	×	×	×		•	Tier 1
Group 1	•	O Residual	×	×	O Residual	×	×		•	Tier 2
	•	O Residual	×	×	O Residual	×	×		•	Tier 3
	•	0	×	×	×	×	×		•	Tier 1
Group 2	0	0	ο	×	ο	0	×		0	Tier 2
	×	0	0	×	0	ο	×		×	Tier 3
	0	0	0	×	•	•	×		×	Tier 1
Group 3	×	•	ο	ο	•	•	×		×	Tier 2
	*	•	0	ο	•	•	0		×	Tier 3
	×	•	0	×O ¹	•	•	×		×	Tier 1
Group 4	×	•	0	× O 1	•	•	×		×	Tier 2
	*	•	0	×O ¹	•	•	×		×	Tier 3
KEY	•	APPLICA	BLE	0	CONSIDE	R	×	AVC	DID	



6.5: Response Strategy and Firth of Forth Sea Zones

For response to water borne spills within the Firth of Forth, the Harbour Area has been divided into six zones. These zones have been specified taking into consideration the following factors:

- 1. The key environmental sensitivities of the Firth of Forth.
- 2. The fisheries interests of the Firth of Forth.
- 3. The priority protection areas defined in *Priority Protection Areas Map*.
- 4. Water depths in the Firth of Forth
- 5. Degree of exposure of the nearshore areas and their adjacent coasts.

 Table 6.3 Definition of Response Strategy Zones for the Forth of Forth harbour Area

Zone 1:	The mudflat areas of the Firth of Forth which include significant nursery areas for flatfish (as defined by Marine Scotland).
Zone 2:	A1 priority protection areas lying in the more exposed outer Firth of Forth.
Żone'3:	A1 priority protection areas lying within the relatively more sheltered inner Firth of Forth Estuary.
Zone 4:	The area within the vicinity of Hound Point Marine Terminal.
Zone 5:	The outer Firth area between the nearshore zone and deep water channel.
Zone 6:	The open deep-water channel out with 1 nautical mile from the 20m bathymetric contour.



Clearwater Forth

for oil type*.

Marine Scotland.

Zone 6

□ Marine containment and recovery of spilt oil.

If impractical application of dispersants to assist dispersion of slick after consultation with

Table 6.4 Prefer	red St	rategies for Response to Persistent Oils Spilt in Firth of Forth Harbour Area
PREFER	RED S	TRATEGIES OF RESPONSE FIRTH OF FORTH HARBOUR AREA~ (Use with Firth of Forth Oil Spill Response Map)
Zone on Oil Spill Response Map		Preferred Strategy of Response
		Prevent oil from reaching these sensitive areas if possible.
Zone 1		Do not use dispersants.
		Shoreline protection; water borne containment and recovery; avoid trampling sensitive mudflat areas.
		Avoid dispersant use. If dispersant use is required to protect A1 Sites (Refer to Priority Protection Areas Map) only use on approval of Marine Scotland.
Zone 2		Booms should be deployed around Deep Sea World water abstraction points (A2 on Priority Protection Areas Map) if there is a possibility of hydrocarbons entering the vicinity.
		Shoreline protection containment and recovery techniques may be used.
		Nater-borne containment and recovery techniques suitable to estuarine waters.
		Diversionary booming techniques using beaches of opportunity [locate at areas with good access].
Zone 3		Diversionary booming to deflect oil away from key sites.
		Shoreline protection containment and recovery techniques.
		f the above is impractical due to weather conditions, current speeds etc. limited application of dispersants may be required, following consultation with Marine Scotland.
Zone 4	s i	Rapid application of dispersants for small spills as quickly as possible to prevent spill from spreading in area around Hound Point Marine Terminal. A standing approval has been ssued for this specified area for a limited use of dispersants. Dispersant use above the approved limit requires formal approval by Marine Scotland.
		Nater-borne containment and recovery of large spills.
		Diversionary booming to deflect oil away from key sites.
		Shoreline protection and containment and recovery techniques.
		Marine containment and recovery of spilt hydrocarbons.
Zone 5		imited application of dispersants to assist dispersion of slick after consultation with Marine Scotland.
	C	Application of dispersant in deeper, open waters and anchorages if ambient weather conditions indicate possible impact of A1 priority protection sites; use dispersant suitable for all type*



Figure 6.2: Oil Spill Response Map





6.6: Response Procedures

Response procedures and checklists are provided in the following sections for the following:

- 1. Natural dispersion and monitoring checklist and response procedures;
- 2. Chemical dispersion checklist and response procedures;
- 3. Mechanical containment and recovery checklist and procedures;
- 4. Containing spill in the vicinity of a vessel;
- 5. Response options for heavy fuel oil spills;
- 6. Waste Disposal Plan.



6.6.1: Natural Dispersion & Response Checklist

Step	Resources & Actions	Guidance Notes
Initiate surveillance of spill	 Available vessel Support Services Unit to mobilise aerial surveillance craft from most appropriate location For Tier 2/3 request MCA to mobilise aerial surveillance aircraft Ensure MRCC Aberdeen are aware of intention to track the slick. 	 Carry out surveillance from available vessel; follow-up using aircraft surveillance for larger spills (helicopter fights commercially available – refer Section 7 for details) Floating oil has a tendency to align in long and narrow windrows parallel to the direction of the wind refer Figure 6.3 overleaf). It is advisable to arrange a ladder search across the direction of the prevailing wind to increase chances of oil detection. (see Section 5 Spill Assessment)
For larger spills place on standby back- up resources	 Forth Ports Limited dispersant facility. Tier 2 response provider, INEOS FPS Response Resources. 	For any large spill of Group 2 oils or smaller spills of crude oils anti-pollution resources should be placed on standby / mobilised. Refer Section 7 for Equipment Resources
Obtain spilt oil sample	Available vessel should obtain sample.	Sample may be required for post incident inquiry. Ensure personnel follow procedures given in Section 5.
Obtain weather forecasts	Obtain data from weather forecasting contractor.	Greater wind speeds and wave conditions will increase speed of natural dispersion. These data will also be important for slick predictions and assessing suitable weather windows for equipment deployment should strategy need to be changed.
Slick predictions	Environmental Unit initiate slick predictions.	Monitor movement of spill; ensure computer runs are regularly updated.
Carry out monitoring	Resources as mobilised. Ensure that the monitoring covers the points opposite. Table 6.5 provides specifications for aerial surveillance aircraft. Air Reconnaissance contracted to MCA meets these specifications	 Chart slick size, growth patterns; affected area; feedback data to FTNS/MEC Estimate quantities remaining if possible; refer Identify heaviest concentration of hydrocarbons (these are likely to be at the downwind leading edge of the spill); Determine proximity of slick to most sensitive areas (refer to Environmental maps & charts in Sections 10 & 11); Watch for any flocks of birds; Watch for breakup of slick and determine direction of movement of any oil patches; Report on progress of natural dispersion.



Thick oil and water-in-oil emulsion (imm) Wind Sheen (< 1 mm) Windrows	121.

Figure 6.3: Distribution of oil in a slick

Ideally for large spills aerial surveillance craft should meet the following specifications:

Equipment	Purpose
Infrared Line Scanner imaging equipment	Aids in the assessment of the volume of the spilt oil
Suitable navigation equipment including Global Positioning Equipment (GPS)	Ensures the accurate display of search areas and spray patterns and control activities of other resources during counter pollution operations
A comprehensive communications suite including multi-channel VHF FM radio, Marine Band (156-174 MHz)	Ensures accurate flow of information to the incident control base
Ultra-violet (UV) Liner Scanner imaging equipment	Assesses oil thickness
Low light camera equipment with image intensifier and infrared illuminator	Night identification
Suitably trained and experienced air crew and other trained staff	To ensure an adequate response capability



6.6.2: Chemical Dispersion Response Option Checklist

Remember that Marine Scotland must be consulted and their approval obtained prior to dispersant use in any area that does not have a prior derogation to spray.

Operation	Resources & Actions	Guidance Notes
Initiate surveillance of spill	 Available vessel For Tier 2 spills Support Services Unit to mobilise aerial surveillance craft from most appropriate location (refer Section 7 for details of available resources) MCA will mobilise aerial surveillance aircraft for Tier 3 spills and on request for Tier 2 spills. 	 Carry out initial surveillance from available vessel; follow-up using aircraft surveillance. For aerial surveillance arrange a ladder search across the direction of the prevailing wind to increase the chances of oil detection (refer Section 5) Ensure MRCC Aberdeen are aware of intention to track the slick.
Mobilise dispersant spraying and resources	INEOS Oil Spill Response equipment, Adler and Allan, Forth Estuary and Hound Point tugs/ work boats. Note that dispersant should be used that is amenable to oil type.	Obtain data on oil type spilt. Request Environment Unit to source dispersant likely to disperse oil type spilt. Note that Dasic Slickgone NS is a wide spectrum dispersant that may disperse a range of oil types. Dasic LTSW also wide spectrum. For spills of heavy fuel oil refer Section 6.6. Mobilise resources as rapidly as possible in order to maximise effectiveness of response and to prevent beaching. Mobilisation routes provided in Section 6.
Obtain spilt oil sample	Available vessel should obtain sample prior to spraying.	Sample may be required for post incident inquiry. Ensure personnel follow procedures provided in Section 5.
Obtain weather forecasts	Obtain data from current weather forecasting contractor.	Important for slick predictions and assessing suitable weather windows for response options and equipment deployment
Run slick predictions model	MEC Operations / Environmental Unit to initiate running of slick predictions. Selected slick predications have been run and recorded for a range of oil spill scenarios in the Firth refer to Section 2	Monitor movement of spill; ensure computer runs are regularly updated.
Deployment of resources	Utilise surveillance aircraft to achieve best deployment of resources	The thickest, downwind sections of the slick should be sprayed first. Use colour guide to identify these or obtain data from surveillance aircraft (refer Section 5).
Carry out monitoring	Utilise resources mobilised for aerial surveillance.	Utilise aerial surveillance and monitor progress of dispersion. A minimum of 2 flights a day is recommended. Refer to Monitoring & Reporting Response Checklist for monitoring. If dispersant spraying is not proving effective : STOP



6.6.2.1: Vessel Mounted Chemical Dispersion

Application Guidelines to Follow After Start Up

- If at all possible use a spotter plane to control larger spraying operations, ones where the slick has become fragmented
- Commence treatment from edge of the slick posing the greatest threat to the shoreline; spray thicker patches of oil rather than intervening thin films or sheens, which will more easily disperse through natural processes.
- Try and avoid cutting across slick (see diagram below)
- Treat slick with parallel and continuous runs to cover the whole area; treat slick into the wind
- Begin treatment at the outer edges of the thicker parts of the slick
- If the slick is near shore, the preferred pattern is in swaths back and forth parallel to the shoreline
- If dispersion is taking place there may be a smoke plume (light brown cloud) evident in upper water layers
- DO NOT spray sheens. These will rapidly disperse naturally. Do not attempt to spray very viscous or semi-solid oils.



Figure 6.4 Vessel mounted dispersant application

When using dispersants, deployed from either a vessel or aircraft, note the following:

Once dispersant been applied to a slick, you may observe colour changes in emulsions (mousse), produced as the demulsifying action of the dispersant reduces the water content and viscosity of the emulsion. Demulsification also can produce changes in the shape and size of a slick: as demulsification pushes water out, the slick may appear to shrink in area.



A visible subsurface plume of dispersed oil indicates that an application of dispersant is working. When no plume is visible in the water column, it is difficult to determine whether the dispersant is working, but does not definitively mean that the dispersant is not having an effect.

Subsurface plumes of dispersed oil typically have a cloudy appearance, and can range in colour from brown to white. Some are not visible. When dispersant is working, oil remaining on the water surface also may change colour.

In some cases, you may not be able to see a subsurface plume even when one is present. When the water is turbid, you may not be able to see a plume. Sometimes, remaining surface oil and sheen can mask oil dispersing under the slick, making it hard for you to see the plume.

A subsurface plume may not form instantaneously once dispersant has been applied to a slick. In some cases, such as when oil is emulsified, it can take several hours for a plume to form. In other cases, a visible plume may not form (you then may wish to use sampling to learn whether dispersion has occurred).

A change in the appearance of a treated slick, compared with an untreated slick, might indicate that the dispersant is working. However, a difference in appearance alone is not enough of an indication to be sure that the dispersant is having an effect

A clear stretch of water left in the wake of a dispersant application vessel can appear to represent successful dispersion of oil. However, areas of clear water can be created as the vessel wave breaks a path through the oil, either physically parting the oil or mechanically dispersing it. Mechanically dispersed oil will recoalesce and float to the surface.

When initially applied, dispersants sometimes have a herding effect on oil, making a slick appear to be shrinking when, in fact, the dispersant is "pushing" the oil together. This effect results from the surfactant action of dispersants, which exerts a horizontal spreading force on thin oil films. This effect can cause parts of an oil slick to seem to disappear from the sea surface for a short time.



6.6.3: Mechanical Containment & Recovery and Coastal Protection Response Checklist

Step	Resources and Actions	Guidance Notes
Initiate surveillance of spill	 Available vessel Mobilise aerial surveillance craft from most appropriate location MCA may mobilise aerial surveillance aircraft Prior to commencing ensure MCA has been made aware of intention to track slick 	 Carry out initial surveillance from vessel; follow-up using aircraft surveillance Guidelines for vessel surveillance provided in Section 5 For aerial surveillance arrange a ladder search across the direction of the prevailing wind to increase the chances of oil detection (refer Section 5)
Mobilise pollution control resources	Adler and Allan, INEOS FPS Resources (Burntisland Response Base and Hound Point Tugs).	Refer to Section 7 for mobilisation and equipment resources details
Carry out consultations	whose coast is threatened and ap	a coastal strategy for protecting ult with the appropriate local authority opropriate environmental bodies including SEPA. Note priority protection areas are
Determine location of sensitive areas	 Refer to Priority Protection Areas map and environmental sensitivity database Agree on order of priorities for protection 	 Note that the data and map provided in Section 9 has been based on data supplied from environmental agencies. Additional information in Appendix 11 and Appendix 12.
Obtain weather forecasts	Support Services to obtain data	Important for assessing suitable weather windows for equipment deployment. Ensure that a record is kept of weather and sea state conditions
Run Oil Spill Modelling Software predictions	Environmental Unit to run oil Spill Modelling Software	Monitor movement of spill; ensure computer runs are regularly updated; for reference selected slick predications have been run and recorded for a range of oil spill scenarios in the Firth of Forth harbour area; refer to Section 2 for results.
Deployment of resources	 Oil spill responder to deploy resources A common difficulty when deploying booms and skimmers to recover oil is controlling the movements and activities of vessels and directing them to the thickest areas of oil. This can be overcome by using aircraft equipped with air to sea communications. 	Using results from surveillance to assist in deployment of resources; note that the anti-pollution tug has a side sweep system and can be used on its own or can also deploy additional boom utilising a workboat or other vessel to assist. Examples of typical booming configurations are provided below. These are examples of how booms can be placed as many booming configurations can be deployed. These configurations will be dependent on metocean



		conditions, the size and location of the spill at the time of the spill.
Carry out	Utilise resources as mobilised	 Utilise aerial surveillance and monitor
monitoring	for aerial surveillance	progress of response. Identify heaviest oil concentrations 2 flights a day should be made.



Single ship system extended with additional vessel towing boom to increase the encounter rate.





U configuration towed by two vessels at 1-2 knots. Oil escaping behind boom is intercepted by a single ship system.



Figure 6.5: Water bourne containment and recovery configurations utilising a single vessel system

A range of typical configurations is shown in Figure 6.6 below. Bear in mind that the appropriate configuration will depend on a range of factors that include:


- The area (size) of the approaching slick
- The amount of redirection necessary
- Wind direction



Figure 6.6: Potential boom configurations for diversionary booming

For selected nearshore booming points, INEOS FPS Onshore Oil Spill Contingency Plan have identified and exercised a number of sites that are designed to prevent the spread of oil up major river courses.



6.6.4: Containing a Spill in the Vicinity of a Vessel

6.6.4.1: First Actions

- □ Assess:
 - Extent of pollution
 - Navigational dangers
 - Other restrictions to an open operation
 - Tidal stream direction/strength
 - Weather conditions
 - Condition of stricken vessel
 - Whether vessel can be safely boarded
 - Best location for marine operations field control point
 - Need for smoking restrictions
 - Personnel boarding and loading facilities at harbours
- D Photograph site if safe to do so; use intrinsically safe camera or site CCTV

6.6.4.2: Secondary Actions

- □ In consultation with contractor on site determine the requirement (types and amount) for:
 - Booms
 - Recovery equipment
 - Dispersants
 - Spraying equipment
 - Storage vessels
 - Support craft, tugs, rig tenders
 - Helicopters
 - Anchors, chains, ropes
 - Submersible pumps
- Hoses
- Fenders
- Manpower to assist boat crews
- **Refer to Section 7 for equipment availability.**
- **D** Arrange with Marine Operations to acquire additional approved resources

6.6.4.3: Executing Counter Pollution Plan

- □ Arrange radio network link-up (with Communications Unit) and establish Call-Signs
- **Contact stricken vessel and ask:**
 - If any unseen dangers around vessel
 - For vessel condition report



FORTH PORTS LIMITED

- If oil leakage stopped
- **D** Advise stricken vessel of containment plan and of possible intention to board
- **D** Take station in marine operations field control point
- **D** Test communications
- □ Monitor weather reports/forecasts
- □ Start deploying booms keep close control of this operation:
 - Do not let tugs pull-out boom too quickly
 - Watch closely for tidal variations
 - Watch tugs keep propellers clear of towlines
- **Gold Site boom as required, anchor by ground tackle or by boats holding**
- □ Site recovery vessel alongside booms, and anchor
- **Commence transfer**
- **D** Monitor recovery rate (for recovery vessel replacement)
- **Arrange for samples to be collected from recovery vessel**
- **D** Monitor equipment performance
- **D** Board stricken vessel if possible and determine:
 - Has leakage stopped
 - Can leakage be stopped
 - Quantity of oil loss before leakage is stopped
 - Quantity of oil loss so far
 - Vessel pumps availability
 - Can cargo be transferred
 - Condition of vessel (shear stress/bending moments)
- □ Maintain log which should be used as a record of the event; include the following, all of which should have a time entered alongside:
 - Key events
 - Incidents (names)
 - Equipment receipts
 - Boat operations (start/stop time)
 - Positioning booms/boats/tugs
 - Start/stop of recovery
 - Meetings (internal/external)
 - Volumes recovered
 - Equipment defects/shortages
 - Weather/tide/wind changes



6.6.5: Response Options for Heavy Fuel Oil Spills

6.6.5.1: Fate and Behaviour of Heavy Oil

Various factors determine the severity and environmental consequences of an oil spill. Of the range of factors, type of oil; amount spilt; environmental sensitivity of the spill location and shoreline that can affect severity of the spill, one of the most significant is the type of oil.

Heavy fuel oils have a high specific gravity and high viscosity which means they do not degrade naturally easily and, as shown in Figure 6.1 and Table 6.1 are highly persistent.

6.6.5.2: Response Options

Sorbent Booms

Absorbent booms may be used to corral and contain small spills of heavy fuel, for example small patches in the open water or around a vessel. They may also be used deflect or divert small spills away from sensitive shoreline areas.

Sorbent booms can be deployed rapidly utilising workboats and secured by ropes and clips. They may also be used to contain residual oil upstream of traditional containment booms.

<u>Availability</u>

Extensive stocks of sorbent booms, pillows and pads are held by INEOS FPS Dalmeny & Forthwright storage. One of the four tugs stationed at Hound Point Marine Terminal will be available at all times for a response. Two of the vessels have recovered oil capacity, one is 100m³, and the other is 200m³.

Traditional Booms and Skimmers

Larger spills of heavy fuel oil in the open water, as with crude oil, will require use of specialist vessels for ready deployment of booms and skimmers and for storage of recovered oil. The recent evaluation of the response to the Prestige heavy fuel oil spill by ITOPF (ITOPF, 2005) provides a review of the most appropriate equipment for dealing with heavy fuel oil spills. The following conclusions were reached with regard to recovery equipment:

- 1. Disc skimmers are least effective of the skimmers available;
- 2. Weir skimmers experienced good recovery rates before the oil increased in viscosity and fragmented;
- 3. In the early stages of the spill the weir skimmers were able to operate without the use of booms; however once the oil fragmented deployment of suitable sea-going booms was required to corral the oil;
- 4. Sweeping arm skimmers achieved high recovery rates and volumes of spilt oil.
- 5. Rapid mobilisation of vessels and specialised booms and skimmers will allow recovery of heavy fuel oil, especially in the early stages of response



before the oil has increased in viscosity through the action of wind and waves.

6. For very large spills the encounter rate is unlikely to prevent oil from beaching.

<u>Availability</u>

- Side sweep systems are available on the tugs stationed at Hound Point Marine Terminal.
- Open water boom stocks at INEOS FPS Burntisland Response Base.
- Hound Point Marine Terminal tug & work boat for boom deployment and 'Hopetoun' oil recovery vessel with 200m² storage capacity.

Chemical Dispersants

Under certain circumstances dispersant *may* disperse heavy fuel oils. In 1997 sea trials were carried out by the National Environmental Technology Centre on behalf of the MCA to determine whether chemical dispersion of HFO was a feasible response option. These sea trials were followed up by laboratory trials. The results demonstrated that dispersants may be a feasible option for spills of HFO at water temperatures of 15°C.

COREXIT 9500 is not currently on the DEFRA approved list, BUT, existing stockpiles may be used away from rocky shorelines in appropriate conditions.

<u>Availability</u>

Stockpiles are held by OSRL in Southampton and could be mobilised in the event of Tier 3 spill for trial runs. This consists of 500m³ of 'Dasic Slickgone NS' in addition to 500m³ of 'Finasol OSR 52'.

Manufacturers and suppliers of Dasic LTSW and Superdispersant are provided in the DEFRA approved listing and stockpiles are maintained by the MCA (Barnsley, Bristol and Dundee).

This response option would only be considered as a part of an overall mechanical containment and recovery option.



6.6.5.3: Response Times

The ITOPF evaluation of the Prestige spill demonstrated that vessels that were mobilised promptly were able to recover significant volumes of oil. Two key factors affect response times for heavy fuel oil spills:

1. Behaviour of the fuel oil; the ITOPF evaluation of the Prestige spill demonstrated that, for the first week of the spill the oil remained in a homogenous state with slicks of hundreds of metres and several centimetres thick. For containment and recovery operations using the specialised equipment referenced above, these conditions would have allowed recovery of spilt oil.

Metocean conditions worsened in the second week with the result that there was a dramatic increase in viscosity and decrease in the rate of oil recovery.

2. In an open sea situation, such as the original spill location of the Prestige there is sufficient time to deploy oil spill response equipment. In situations such as the Firth of Forth travel distances are more restricted. Slick trajectories in Section 2 demonstrate that for spills of heavy fuel oil from the Fairway Buoy oil would beach under neap ebb tidal conditions and a 9 knot wind at Largo Bay in about 47 hours. Under springs flood conditions, with a 19 knot wind, oil could beach at Inchcolm Island in approximately 13 hours. In the open water 4 nautical miles off North Berwick under neap ebb conditions and a wind speed of 15 knots, oil could beach at North Berwick in about 5 hours and in Largo Bay in about 6 hours under spring flood conditions.

This data clearly demonstrates that under a range of tidal conditions and wind speeds, oil spilt from the above point sources will beach rapidly.

The availability of Ro-Boom side sweep systems on the tug stationed at Hound Point Marine Terminal will allow a ready and rapid response to smaller spills and an initial response to larger spills. As previously mentioned, there is also a work boat and recovery vessel available.

Heavy Fuel Oil and Tiers of Spill

Considering the potential difficulties of mounting an intervention response to heavy fuel oils in terms of speed and response, type of equipment required and difficulties of recovery, especially for spills in the open water, spills of heavy fuel oil may escalate more rapidly in terms of volumes of oil spilt from a Tier 1 to a Tier 2 incident than would be considered for spills of crude oil.

In addition, because of the equipment requirements spills of heavy fuel oil and heavier types and blends of crude oil may escalate more rapidly and at much smaller volumes of spilt oil to a Tier 3 than the equivalent volumes of light crude oil.



6.7: Waste Disposal Procedures

A natural dispersion or chemical dispersion response strategy or chemical dispersion may remove oil from the sea surface and prevent oil beaching. In the event of a containment and recovery strategy either water borne offshore or nearshore will result in generation of oily waste.

Recovery operations potentially give rise to a large quantity of waste oil and water for treatment. The type of spilled oil will have an effect on the resultant waste. Viscous and waxy oils will entrain debris and create large waste volumes.

Wastes generated may include:

- Recovered oil
- Oily water
- Oiled equipment
- Oiled PPE
- Oiled vegetation
- Oiled sorbents
- Oiled flotsam

In the event that waste generation occurs the following will be required:

- Arrangements for the storage of recovered oil offshore;
- Arrangements for the collection, transport and disposal of oil and oiled wastes.
- Characterisation of oiled wastes in order to aid identification of most appropriate waste disposal facilities to handle the waste materials.
- Preparation of all necessary documentation and pre-notifications necessary to satisfy the Duty of Care and, if necessary, Special Waste regulations.

6.7.1: Consultations

This will be an integral part of the waste management plan in order to determine:

- Where waste may be landed in what form
- Decisions on on-site storage and method
- Availability of suitable waste carriers
- Consideration of potential final resting place
- Proximity, capacity and license of range of treatment and disposal facilities



6.7.2: Checklist for Waste Management

- Make initial contact with possible waste disposal facility operators to make arrangements for the ultimate disposal of waste materials. Note that Close-sided lorries and skip-trucks can be used for non-liquid wastes, and specialist vacuum trucks (flash point dependent) and gully suckers are best for liquid oily wastes. If necessary, flat bed lorries can be used for either type of oily waste by transporting the materials in tanks or drums fitted with temporary covers.
- Ensure that all hauliers' vehicles are carrying valid Registered Carriers Registration Certificates before they arrive on-scene.
- Obtain data on likely quantities of liquid oily wastes that are being collected by any recovery operations.
- Estimate quantities of non-liquid oiled wastes created primarily on shorelines. Initiate appropriate Duty of Care and Special Waste documentation to cover all waste transport used, and ensure that the destination of the oiled wastes is extremely clear to the lorry drivers. Shoreline waste is the responsibility of the Local Authority this is an issue the Environment Group will be looking at on a case by case basis.
- Ensure that transport of oily wastes is of a frequency sufficient to prevent the temporary storage being overwhelmed.
- Confirm with all waste disposal facilities used that they have received all documentation required to cover the movement of oiled wastes to their facilities.
- Oil spill wastes are considered to be hazardous wastes and are subject to the Waste Management Licensing Regulations 2011. However, oil collected during response activities can be stored temporarily at the site in accordance with Waste Management Licensing Exemption 41 (which allows storage of waste at the place of production).
- Plans for handling and temporary storage of wastes during the oil spill response must be discussed with the Scottish Environment Protection Agency (SEPA) at the earliest opportunity.
- Any recovered oil should be reported to HM Customs as advised in the oil spill reporting table provided in Section 5.
- The disposal site for the waste MUST hold a licence to receive the type of oily waste that you are sending to it.
- It is the responsibility of all parties involved to ensure the site is licensed to receive waste.
- The responsibility for complying with regulations is divided between the Harbour Authority / Port for waste generated on the water surface in whose jurisdiction the spill has occurred and the local authority if there is



shoreline clean-up and those involved in its movement and reprocessing, storage and disposal.

- In the event of containment and recovery at sea and shipping of oil onshore for disposal, the responsibility for complying with the waste legislation lies with the port who is recognised as the waste producer.
- Where the oil has beached and the local authority is conducting a beach clean-up operation and are sending the waste for disposal, the local authority become the waste producer and are the body responsibility for the waste paperwork, registered carrier checking.

Marine oil waste disposal regulatory controls by SEPA are summarised in the diagram and the Key on the following pages:

Key	REGULATORY CONTROLS			* Not specifically SEPA
		N	ML	- Waste Management Licence
1.	Duty of Care*			
	S.34 EPA 1990 (NB Applies from 1. to 8. irres	spect	ive o	f other controls;
2i.	Temporary Storage			
	"Emergency" provisions apply,)	1	
	No WML required;)		
2ii.	Longer Term Storage			
	WML required;			
3.	Existing Local Holding Facilities (Tankage)			
	WML required;			
4.	Waste Movement By Road			
	Registered Waste Carriers,			
	Waste consigned under Special Waste Regs.	1996	;	
5.	Intermediate Storage (e.g. old airfields)			
	Planning approval,)	"Phantom" applications could be
	WML required;)	processed as forward planning provision
6.	Land Farming			
	Site specific risk assessment,			
	WML required,			
7.	Treatment/Recovery			
	WML or authorisation under Part I EPA requi	red;		
8.	Landfill Disposal			
	Suitably licensed sites only			
	Must be engineering containment,			
	Loading limits on oil input will apply.			



Clearwater Forth





6.7.3: Waste Minimisation

Minimisation is a method of reducing the amount of waste entering the waste stream. This can reduce the amount of waste for final disposal and also limit environmental and economic impacts. Efficient methods should be developed for oil spill clean up to ensure that the minimum material is used and/or contaminated during the process.

There are a number of methods that can be used for this:

- Recovery equipment should be cleaned and reused rather than discarded.
- Reusable personal protective equipment (PPE) should be utilized where appropriate, for example products such as rubber boots that can be cleaned and reused.
- Sorbents should be used sparingly and effectively.
- Production of a marketable product from waste, e.g. taking waste oil to a refinery (Grangemouth Refinery) for conversion into other usable products.

Refuse is the final and least desirable option. If none of the above methods can be carried out for whatever reason the waste must be disposed of effectively following guidance from SEPA. For disposal of oiled waste a Special Waste Consignment Note will be required. There is a minimum of 3 days pre-notification to SEPA for this although in the event of an emergency the regulator may waive the requirement for pre-notification.

6.7.4: Temporary Storage and Disposal of Recovered Oil & Oiled Absorbents Procedure

A mechanical and containment response in the dock area will lead to the generation of oily waste. Temporary oil storage on the quayside and waste disposal of this material is very much a part of dealing with an oil spill incident.

Plans for handling and temporary storage of wastes during the oil spill response must be discussed with the Scottish Environment Protection Agency (SEPA) at the earliest opportunity.

In the event of water borne containment and recovery and storage of oil on the quayside for disposal, the responsibility for complying with the waste legislation lies with the harbour authority who is regarded as the waste producer.

6.7.4.1: Permits and Exemptions for Temporary Storage of Recovered Oil and Oily Waste

Scottish Environment Protection Agency guidance is that recovered oil and oiled waste is classed as Special waste and is therefore

• Subject to all waste regulations when landed including Special Waste Regulations (as amended) 1996



• Waste regulations require licensing of sites where recovered oil and oiled waste is temporarily kept.

Note that:

• Oil spill emergencies do not generally preclude requirement to obtain permits and approvals and to comply with waste licensing conditions.

Oil collected during response activities however, can be stored temporarily at the site in accordance with Waste Management Licensing Exemption 41. Exempt options for recovered oily waste landed in harbour areas include storage on the site where it is produced for 12 months of:

- Liquid waste up to 23,000 litres (5000 gals) and in secure container (for example lined and covered skip)
- Non-liquid waste up to 80 cubic metres in secure container

6.8: Tiers of Spill and Ports Response Capability: Methil, Kirkcaldy, Burntisland, Rosyth, Leith and Grangemouth

6.8.1: Tiers of Spill

Table 6.6 Categorisation of Oil Spill Incidents

Tier	Scale of Incident	Mobilisation Level	
Tier 1	Small spills which can be dealt with using local resources. These spills will usually be less than 0.5 tonnes deployed Adler and Allan t contacted		
Tier 2	Larger spills that require mobilisation of additional resources. These spills will be larger than 0.5 tonnes. If contained within the dock it would be unlikely that a general `Clearwater Forth` would be declared.	Tier 2 oil spill response resources and Tier 2 oil spill response contractors (Adler and Allan)	
Spills that leave the enclosed dock	Will be beyond the resources of the Dock	Clearwater Forth will mobilise appropriate mobilisation level.	

6.8.2: Ports Response Capability

Tier 1 equipment can be located in Appendix 2.



6.9: Mechanical Containment & Recovery of Split Oil

In the event of a spill o	ccurring every effort must be made to contain the spill within the dock or port	
LIKELY AFFECTED AREAS	There is no import or export of hydrocarbons within these ports. Vessel damage or release of fuel oils or from land-based sources may occur therefore there is the potential for a spill to occur anywhere within the docks areas	
PROTECTIVE GEAR	Appropriate PPE dependent on incident e.g. Lifejacket, hardhat, overalls, gloves, safety boots, and safety goggles.	
FIRST ACTIONS	Call-out available small craft to assist in boom deployment. Rigid inflatable boats will be particularly effective for maneuvering in more confined areas.	
	Take 2-way communications and relevant equipment to the incident site. A means of maintaining communications with the small craft is essential.	
	Ensure response personnel are wearing required PPE (see above).	
BOOM DEPLOYMENT	1. Deploy two personnel to opposite side of response site.	
	2. Deploy rope (15mm) across to other side using workboat.	
	 Connect appropriate number of lengths of sorbent boom together by attachment clips; allow an overlap for each section. Lay out along dockside ready for deployment. 	
	4. Once sufficient boom has been connected together attach to the rope and request far bank to commence pulling the boom across. N.B. Additional lengths of boom can be attached as the boom is being hauled across if required.	
	Secure both ends to bollards. Allow sufficient length to achieve a seal against the dock wall on both sides of the deployment site.	
	Note that, for heavier levels of contamination two or more strings may be required to contain the oil.	
SECOND ACTIONS (Tier 1 Spills)	The next stage of the response is to attempt to corral and recover any spilt hydrocarbons.	
	Using sorbent booms attempt to corral pollutants into the most appropriate corner of the dock as dictated by the prevailing wind direction. With absorbent booms this may be achieved by 'walking' the ends of the sorbent boom slowly along the edges of the dock.	
	If there is no wind direct pollutants into the most appropriate corner for accessibility for men and equipment.	
	Once the oil is corralled, use either absorbent pads or oil skimmer (if available) to recover the pollutants. Alternatively a vacuum taker may be used to recover thick layers of oil.	
	Absorbent pads laid onto the oil must be allowed sufficient time for the oil to be absorbed. Once saturated lift pads carefully and place into the heavy duty	



	plastic bags. Continue placing absorbent pads onto the oil and recovering until all oil has been removed.
SECOND ACTIONS – Tier 2 (Traditional Boom)	Once the traditional boom has been deployed in the event of a Tier 2 spill to prevent a spill spreading throughout the docks, a skimmer can be deployed within the thickest areas of spill to attempt recovery from the water surface. The skimmer and requisite ancillary equipment should be moved as necessary to other areas of the spill until recovery is no longer being achieved at a satisfactory rate. When the skimmer is no longer effective, sorbent boom can be used in the manner described above to sweep the water surface, corralling the remaining oil into a convenient corner of the dock. If there is no wind direct pollutants into the most appropriate corner for accessibility for men and equipment. If sufficient oil is corralled in this manner, the skimmer can be re-deployed to recommence oil recovery. If the skimmer is not effective, sorbent pads should be laid as described above onto the surface of the water to absorb the remaining oil.
ADDITIONAL INFORMATION	In the event of large Tier Two spills additional supplies of materials and manpower will be brought to site by the Tier Two response contractor.
WASTE DISPOSAL	Contaminated materials and recovered oil associated with the clean-up of the spill will be disposed of by a certified waste disposal company. Recovered oil may also be consigned to waste oil recycling companies. All contaminated materials must be placed in the appropriate skips once on-site. They MUST NOT be placed in the Docks normal waste bins.

The following diagrams are illustrative of potential spill events in ports, but are not representative of every spill situation:

Figure 6.6 Corralling of spilt oil using absorbent boom





6.10: Clean-up of Dock Walls and Support Structures

The following procedure assumes that all free-floating oil within the dock area has bee	n cleaned up.
The following procedure declines that an new neutring on mann the deck area has bee	n oloanoa api

Use of dispersants (detergents) within the dock areas must only be undertaken after FULL consultation with the SEPA and Marine Scotland. Marine Scotland must give their approval to any intended use of dispersants.

PREFERRED METHOD	Hosing / Flushing. Use medium pressure cold water to wash the dock walls and other structures to remove surface residue oils.
ALTERNATIVE	High Pressure / Hot water System to remove oil from complex structures and / or particularly heavy contamination.
EQUIPMENT REQUIRED	Skirted Sorbent Booms or Traditional Booms; absorbent pads and or mechanical recovery system; pressure washing unit [located on the adjacent dock side]; work boat or pontoon(s).
PROTECTIVE GEAR	Appropriate PPE e.g. Lifejacket, hardhat, overalls, gloves, safety boots, safety full-face visor.
FIRST ACTIONS	Deploy boom around the area of the dock walls to be cleaned and pontoons / work boat. This is done to ensure that any oil released from the operation is contained and recovered and is not allowed to contaminate other areas of the docks.
SECOND ACTIONS	 Wash down contaminated surfaces ensuring that any oil released is being contained within the boomed work area. Use absorbent pads to recover the pollutant from the collection area. This may be achieved by laying them onto the oil and allowing sufficient time for the oil to be absorbed. In the event that the oil is no longer being absorbed by the pads mechanical recovery systems will need to be used to recover the oil. Once saturated lift carefully and place into the heavy duty plastic bags. Continue placing absorbent pads onto the oil and recovering until all oil has been removed.
ADDITIONAL INFORMATION	Further Supplies of Absorbent Boom may be obtained from other ports or INEOS FPS Burntisland Response Base. Mechanical containment and recovery equipment is available from INEOS FPS Burntisland Response Base for Tier 2 incidents.
WASTE DISPOSAL	All contaminated materials associated with the clean-up of the spill will be



Clearwater Forth

disposed of by a certified waste disposal company. All contaminated materials must be placed in the appropriate skips once on-site. They MUST NOT be placed in the dock's normal waste bins.

6.11: Response Guidance - Hazardous Substances Released to Water from the INEOS Grangemouth Jetties

The appropriate control and clean-up measures for the release of hazardous substances released into the docks will be dependent upon the fate and behaviour of the substance when in contact with water. Based on physical and chemical properties there are four categories of hazardous substance including ones which for a gas/vapour cloud, dissolve and mix with the water column, float on the surface and ones which sink.

Table 6.7 Properties and Behaviour of Substances handled at INEOS Jetties

Substance	Density	Boiling Point °C	Flash Point °C	Interaction with Water	Behaviour of Spill
Atmospheric Residue	0.9	-	>60	Immiscible	Will solidify
Benzene	0.88	80	-11	Immiscible	Floats; very rapid spreading; volatile
Butadiene	0.62	-4.5	-70	Insoluble	Vapour cloud
Raw C 4's	0.62	+/-12	-70	Insoluble	Vapour cloud
Condensate	0.79	25-150	-40	Immiscible	Floats; very rapid spreading; volatile
Derv	0.84	180-360	65	Immiscible	Floats; heavy will tend to sink
Ethane	0.506	-89	-135	Insoluble	Vapour cloud
Ethanol	0.79	78	13	Soluble	Mixes with water column
FAME	0.878-0.895	302.5 - 570	120 - 180	Immiscible	Floats, rapid spreading
Fuel Oil	.94-1.00	>200	66	Immiscible	Floats; heavy will tend to sink
Gas Oil/Diesel	0.84	180-360	56	Immiscible	Floats; rapid spreading; evaporates
Hexene	0.67	64	-25	Immiscible	Floats; very rapid spreading; volatile
Jet A-1 (ATK)	.7783	150-300	38	Immiscible	Floats; rapid spreading; evaporates
Kerosene	.8082	150-225	38	Immiscible	Floats; rapid spreading; evaporates
LDF	.6667	30-175	-40	Immiscible	Floats; very rapid spreading; volatile
LPGs	.57-2.02	-45	-18	Insoluble	Vapour cloud
Motor Spirit / Petrol	0.71	25-220	-40	Immiscible	Floats; very rapid spreading; volatile
C4 Raffinates	1.95	+/-12	-70	Insoluble	Vapour cloud
Propylene	0.51	-47	-108	Insoluble	Vapour cloud
Reformate	.7888	25-210		Immiscible	Floats; volatile
Styrene	0.9	146	31	Immiscible	Floats; will evaporate



6.11.1: Substances which Form a Gas / Vapour Cloud

Hazardous substances which are volatile are more likely to form a vapour cloud when released. Substances that are transported under pressure of in a refrigerated state are included in this group. These substances will spontaneously change to the gas state at ambient pressure and temperature if accidentally released. Liquids with a high vapour pressure may release vapour clouds when exposed to the air. The period of hazard associated with the vapour plume will depends on the gas/air ratio, amount of spillage and dispersion rate. In the vicinity of the vapour cloud there will be the danger of oxygen deficiency and asphyxiation and the potential for fire and explosion. These spills should be treated as fire hazards and reference should be made to the INEOS Grangemouth Site Emergency Plan.

The wearing of overalls, safety boots, helmets, gloves and eye protection is mandatory. Additional PPE such as the 1 piece green chemical suit, lifejacket etc. must be made available and worn subject to a risk assessment being carried out or the application of local site rules.

Main Characteristics	These chemicals have very low boiling points at ambient temperature and pressure. These liquids may cause severe skin burns.
Examples	Butadiene, Raw C 4's, LPGs, C4 Raffinates, Propylene, Ethane
First Actions	There will be an explosion risk. Evacuate all non-essential personnel from the immediate vicinity and downwind of the spill.Eliminate all possible sources of ignition or any other equipment which can generate a spark.If spillage is in a confined area, ensure adequate ventilation; the build- up of an excessive concentration of vapour must be prevented.
Protective Gear	Self-contained breathing apparatus, overalls, leather gloves, safety boots; (trousers/overalls should be worn outside the boots, not tucked inside, so that spillage on the trousers cannot easily enter the boots and produce a cold burn).
Second Actions	Large spills of these substances require specialist advice and equipment. Call the INEOS Fire Service. Allow any spillage to evaporate under controlled conditions.



6.11.2: Substances which Dissolve in Water

If the substance is completely water soluble, once it is released into and mixes with a body of water, effective control over the substance is lost. In this case the hazard will be to marine life, the degree of hazard depending on the eco-toxicity, biodegradability and bioaccumulation properties of the substance spilt.

MAIN CHARACTERISTICS	These compounds are generally highly flammable liquids. Thay are also soluble or miscible in water. Dilution and dispersion of the chemical will take place if the chemical enters the main dock area. This dilution and dispersion will eliminate the flammability hazard. For small releases concentrations are likely to reach harmless levels in relatively short periods.
EXAMPLES	Ethanol
FIRST ACTIONS	For large release of soluble chemicals it may be necessary to restrict marine traffic in the area of the release. Large releases of chemicals into the main docks area must also be reported to the Scottish Environment Protection Agency.
PERSONNAL PROTECTIVE EQUIPMENT	Self-contained breathing apparatus, overalls, rubber gloves, safety boots, lifejackets.
SECOND ACTIONS	For substances with more limited solubility in water, the dissolved portion will dilute and disperse whilst the un- dissolved portion could be recovered, if safe to do so, using skimmers or absorbents. Handing of absorbents saturated with hazardous substances must be carried out with full protective gear as chemicals absorbed will not be neutralised.

6.11.3: Substances which Float

Liquids that have a lower density than water will normally float and form a slick when released. Substances that float can be subdivided into four groups. These are as follows:

- Substances which float and form a slick over which a vapour cloud develops. These
 liquids will initially float on the water surface when spilt but will evaporate very
 rapidly. As the liquids evaporate a vapour cloud will form. The warmer and windier
 the ambient conditions, the more rapidly evaporation will occur. As the mixture in the
 vapour cloud will be heavier than air it may form a low-level vapour plume.
- Substances which float on water and form a slick with little evaporation or interaction with the water.
- Substances which float on water, form a slick and interact with the water to form an emulsion.
- Substances which float but which solidify when spilt at ambient temperatures below their pour point or which need to be heated to remain liquid.



6.11.3.1: Substances which Float & Form Vapour Cloud

MAIN	The liquids in this group are highly flammable, potentially
CHARACTERISTICS	explosive and may be harmful. They will form a <u>vapour cloud</u>
CHARACTERISTICS	when evaporating.
EXAMPLES	Benzene, Condensate, Hexene, LDF, Motor Spirit,
	Reformate, Styrene.
FIRST ACTIONS	There will be a fire and explosion hazard in confined spaces;
	all possible sources of ignition near the spill and vapour plume
	must be eliminated and kept out of the plume area until the
	vapour cloud has dispersed.
	Evacuate all non-essential personnel from the immediate
	vicinity and downwind of the spill.
	Senior personnel to carry out site assessment and gas level
	monitoring; designate a safe area. No personnel to approach
	downwind of plume without breathing apparatus.
	It is advisable to call the Fire Services / Fire Brigade for large
	spills of these flammable substances.
PERSONNAL	Overalls, gloves, safety boots, safety spectacles/goggles, Self-
PROTECTIVE	contained breathing apparatus, lifejackets.
EQUIPMENT	
SECOND ACTIONS	If safe to do so, attempt to contain the spill within the main
	dock area by booming off area to Grange Dock.
	No attempt should be made to spray the spill with dispersant
	or to recover hydrocarbons; the spill should be left to dissipate
	naturally.
EQUIPMENT	Booms, Vacuum tanker, skimmer, absorbents, waste disposal
REQUIRED	drums.
CLEAN UP	Low Flashpoint products will evaporate off very quickly; leave
RESPONSE:	spill to evaporate under controlled conditions until gas
ALL SPILLS	monitoring indicates that it is safe to re-enter area.
	Once it is safe to re-enter the area, attempt to corral residue
	into one area by booming, using absorbent boom or traditional
	booms. This will increase oil thickness for skimming. Direct
	hydrocarbons to appropriate area of main docks depending on
	wind direction. If there is little wind, direct hydrocarbons to
	area easiest access for equipment and manpower.
	Recover residual heavy ends using vacuum tanker and
	appropriate vacuum skimmer head. If vacuum tanker is
	unavailable use AIR DRIVEN pumps, skim and pump to
	temporary storage in 205 litre drums, fastanks or similar.
	Absorbents may be used to recover thinly spread or patches of
	chemicals/ hydrocarbons.
	crement, marocarbono



6.11.3.2: Substances which Float (no solidification)

MAIN	Included in this group are products with flashpoints of greater
CHARACTERISTICS	than 30 C. The liquids in this group are highly flammable,
	potentially explosive and may be harmful.
EXAMPLES	Derv, Gas Oil, Jet A-1, Kerosene, Light Fuel Oil.
FIRST ACTIONS	Eliminate all possible sources of ignition or any equipment
	which can generate a spark; do not allow any such equipment
	to be brought on site.
	Evacuate all personnel from the immediate vicinity and
	downwind of the spill area.
	Senior personnel to carry out site assessment and gas level
	monitoring; designate a safe area.
	It is advisable to call the Fire Services / Fire Brigade for large
	spills of these flammable substances due to the potential fire
PERSONNAL	risk. Overalls, gloves, safety boots, safety spectacles/goggles,
PROTECTIVE	lifejackets, 1 piece green chemical suit.
EQUIPMENT	inejackets, 1 piece green chemical suit.
SECOND ACTIONS	Attempt to contain the pollutants within the main dock area by
	booming off area to Grange Dock.
EQUIPMENT	Booms, air driven pumps, skimmers, absorbents, temporary
REQUIRED	storage.
CLEAN UP	Once area is safe use either sorbent or traditional booms to
RESPONSE:	attempt to corral pollutants into most appropriate area of the
ALL SPILLS	main docks as indicated by prevailing wind conditions. This will
	help to increase the thickness of pollutant for recovery by
	skimmer. If there is little wind, direct pollutants to areas of
	jetties that has easiest access for equipment and manpower.
	Use Komara skimmers, skim surface and pump pollutants into
	temporary storage, preferably vacuum tanker or 205 litre
	drums; continue until thickest concentrations of pollutants have been removed.
	Absorbents may be used to recover thinly spread or small
	quantities of pollutants.
	Soiled absorbents should be placed in lined skips or drums
	prior to disposal at approved sites.
	Handling of absorbents saturated with hazardous substances
	must be carried out with full protective gear, as chemicals
	absorbed will not be neutralised.



6.11.3.3: Substances which Float & May Solidify

	1
MAIN CHARACTERISTICS	These compounds are generally highly flammable liquids; likely to be solid or semi-solid at ambient temperatures; toxic hydrogen sulphide vapours given off when heated, e.g. during
	storage or transport; hot product may cause burns.
EXAMPLES	Heavy Fuel Oil, Atmospheric Residue.
FIRST ACTIONS	Eliminate all possible sources of ignition or any equipment that can generate a spark and ensure that no such equipment is brought on site. Evacuate all personnel from the immediate vicinity of the spill area. Senior personnel to carry out site assessment and monitor gas levels.
PERSONNAL PROTECTIVE EQUIPMENT	Overalls, gloves, safety boots, safety spectacles/goggles, lifejackets.
SECOND ACTIONS	Attempt to contain the pollutants within the main dock area by booming off area to Grange Dock.
EQUIPMENT REQUIRED	Booms, vacuum tanker & skimmers, JCB with rake attachment; garden forks and spades, temporary storage for recovered oil.
CLEAN UP RESPONSE: ALL SPILLS	Using booms to try to corral hydrocarbons into most appropriate area of the main docks, depending on accessibility for clean up equipment and prevailing wind conditions. Ensuring that it is safe to operate, recover heavy fuel oil by vacuum tanker, if liquid; take hoses from vehicle and insert into oil at the thickest place that can be reached quickly and safely. Remove as much of the surface oil as possible with the tanker. If solid, or for atmospheric residue, recover oil using mechanical means such as JCB with rake attachment, or manually using garden forks or spades. Recover hydrocarbons into lined skips or 205 litre drums for solid hydrocarbons and vacuum tanker or 205 litre drums for liquid hydrocarbons.



FORTH PORTS LIMITED

Section 7: Equipment Resources

7.1: Three Tiered Response System

Forth Ports Limited recognise that different spill scenarios require different levels of manpower and equipment response. In recognition of this, Forth Ports Limited have put in place a three tiered equipment and manpower response system which is detailed below. The response equipment is operated by fully trained response support teams. Please refer to Appendix 2 for further information regarding available equipment.

7.2: Tier 1 Equipment Resources and Mobilisation

7.2.1: Ports of Methil, Kirkcaldy, Burntisland, Grangemouth, Leith and Rosyth

Resources can be found in Appendix 2.

7.2.2: Firth of Forth

Tier 1 Resources include sorbent booms and pads and, for appropriate areas of the Firth of Forth, chemical dispersants. The chemical dispersant facilities will also act as a response for Tier 2 incidents.

7.3: Tier 2 Equipment Response

Tier 2 incidents would require Forth Ports' resources to be augmented with additional equipment and manpower.

Adler and Allan provide Tier 2 cover, also a mutual aid plan between Forth Ports Limited, INEOS FPS, INEOS Grangemouth and Shell/Exxon adds to the Tier 2 response for the sea area within the jurisdiction of Forth Ports. This includes the ports of Grangemouth, Leith, Methil, Kirkcaldy, Rosyth and Burntisland.

Forth Ports Limited, Adler and Allan, INEOS FPS, INEOS Grangemouth and Shell/Exxon, Braefoot Bay will provide a Tier 2 response, utilising the equipment as detailed in Appendix 2 – to which reference should be made.

INEOS FPS may also supply a Hound Point Response Vessel for Tier 2 incidents requiring its specific resources. The vessel can also assist in boom deployment for open water incidents.



7.3.1: Ports of Methil, Kirkcaldy, Grangemouth, Leith and Burntisland

These resources will be available from Adler and Allan on a call out basis, within 4 hours (during working hours) and 6 hours (outside working hours). A complete inventory is given in Appendix 2.

Table 7.1 TIER TWO RESPONSE CAPABILITY			
Response Capability	Mobilisation Procedure		
Full equipped 2 tonne light rapid response vehicle (RRV) and an experience supervisor and responder at site.	Mobilisation via Marine Management Team and effected by Forth and Tay Navigation Service or, if manned, by the		
Fully equipped 8.5 tonne heavy rapid response vehicle (RRV), an experienced	MEC. FTNS Emergency Tel : 01324 668 495		
supervisor and two responders available at site.	(24 hrs)		
Mobilisation of additional resources from National Base Network, including large stockpiles of equipment, ADT tanker and vacuum uplift tank fleets.			
Refer Appendix 2 for full listing			



Firth of Forth Tier 2 equipment resources and mobilisation procedures are provided below:

Table 7.2 TIER TWO R	ESPONSE CAPABILITY
Response Capability	Mobilisation Procedure
Forth Ports Limited Two tugs equipped with dispersant spraying capabilities	Mobilisation via Marine Management Team and effected by Forth and Tay Navigation Service or, if manned, by the MEC: FTNS Emergency Tel : 01324 668 495 (24
MT Fidra 21,000 litres VDC+ MT Hopetoun – Oil Spill Modelling Software	hrs)
Adler and Allan	Tel: 0800 592 827 (24 hours)
Trained manpower and equipment stockpiles at Montrose and Glasgow.	
Hound Point Response Vessels	Mobilisation via INEOS FPS Marine Manager
Side Sweep System	or Duty Incident Commander. Mobilisation of any asset is under the strict
Seamop 4090 Skimmer	authorisation of the INEOS FPS Marine
 Dispersant spraying system and Type 2/3 dispersant 	Management Team and effected by Forth and Tay Navigation Service or, if manned, by the MEC:
Absorbent materials	KSL: 01324 476719
• One vessel is classed for oil recovery with a capacity of 200m ³	Hound Point: 0131 331 6562 or 07786174093
 Two other vessels have oil recovery capability but are not classed. These have a capacity of 101m³ 	FTNS Emergency Tel : 01324 668 495 (24 hrs)
One workboat is available from the	MEC: 01324 498595
Hound Point Fleet which may be used for towing booms or upon request can have a dispersant system installed	One of the four tugs stationed at Hound Point Marine Terminal can be made available subject to operational requirements.
Oil Spill Modelling Software	
INEOS FPS Burntisland Response Base	Mobilisation via INEOS FPS Kinneil Shift
Trained manpower and extensive equipment stocks (for containment and recovery, dispersant spraying, and shoreline protection.	Team Lead. Mobilisation of any asset is under the strict authorisation of the INEOS FPS Marine Management Team and effected by Forth and Tay Navigation Service or, if manned, by the MEC:



Table 7.2 TIER TWO RESPONSE CAPABILITY			
Response Capability	Mobilisation Procedure		
Equipment includes:	KSL: 01324 476719		
 Containment booms for open water and inland waters, calm and protected waters 	FTNS Emergency Tel : 01324 668 495 (24 hrs) MEC: 01324 498595		
 Shore sealing booms for estuaries, rivers tidal flats and salt marshes 			
River and harbour booms			
(all booms include moorings, connectors and inflation pumps)			
 skimmers for use with a range of oil types from gas oil, crude oil to heavier fuel oils 			
temporary storage equipment for shoreline use			
workboat			
sorbent booms and pillows			
ancillary equipment (pumps, generators, lighting sets, vehicles)			
Refer Appendix 2 for full listing			
 INEOS Forties Pipeline System Dispersant Stocks These stocks are listed in Appendix 2 and are held on the Hound Point Marine Terminal tugs. Note that stocks include Dasic Slickgone NS 	Mobilisation via Ineos FPS Kinneil Shift Team Lead. Mobilisation of any asset is under the strict authorisation of the Ineos Marine Management Team (& FPS IMT) and effected by Forth and Tay Navigation Service or, if manned, by the MEC:		
is a wide spectrum dispersant effective on a	KSL: 01324 476719		
range of oil types	FTNS Emergency Tel : 01324 668 495 (24 hrs)		
	MEC: 01324 498595		
Shell / Exxon, Braefoot Bay Various pollution clean-up equipment.	Mobilisation via Shift Supervisor at Braefoot Bay Marine Terminal		
Refer Appendix 2 for full listing. Manpower resources to deploy equipment is not immediately available.	Contact via Shift Supervisor Tel: 01383 892123 (24 hours) or if unavailable via Marine Terminal Security		



Clearwater Forth

Table 7.2 TIER TWO RESPONSE CAPABILITY		
Response Capability	Mobilisation Procedure	
	Tel: 01383 892190	
The City of Edinburgh Council Miscellaneous vehicles, equipment and	Mobilisation via the Council Oil Pollution Control Officer.	
personnel.	Contact through the Councils emergency contact telephone/fax No's as listed in Forth Ports Emergency Contact Directory.	
Fife Council Stocks of chemical dispersant, spraying equipment, jetting machines, gully emptiers, absorbents, miscellaneous equipment.	Mobilisation via the Council Emergency Planning Officer on contact details as listed in Forth Ports Emergency Contact Directory.	
Falkirk Council	Mobilisation via Council Emergency Control on contact details as listed in Forth Ports	
Permanent store with small quantity of equipment for manual response e.g. protective clothing scrapers etc.	Emergency Contact Directory.	
East Lothian Council	Mobilisation via Emergency Planning Officer	
Manpower and plant	on contact details as listed in Forth Ports Emergency Contact Directory.	
Adler & Alan, Grangemouth	Contact: 24 hour callout	
Information as per Appendix 2, INEOS Grangemouth Tier 2 contractor.	Mobilise via INEOS Grangemouth Site Shift Manager (SSM)	
	Tel: 07879 432357	
	Internal: 6536	
	UHF: Channel 5	
Briggs Environmental Services	Mobilisation via BESL	
Trained manpower and equipment stockpiles at Burntisland, including various booms, skimmers, temporary storage, workboats, sorbents and ancillary equipment.	Tel: 0800 374 348 (24 hours)	



7.4: Tier 3 Equipment Resources

The Tier 3 response which could be mobilised in the event of a major oil spill comprises the national stockpiles of counter pollution resources maintained by the Maritime and Coastguard Agency (MCA). The Maritime and Coastguard Agency, Counter Pollution Branch would lead the government response to pollution at sea and assist local government with the onshore response to shoreline pollution. The pollution capability held by MCA includes aerial surveillance and dispersant response; at sea oil recovery; and stockpiles of beach cleaning equipment. Equipment resources held by the MCA Counter Pollution Branch at strategic locations around the UK are as follows:

Equipment	Location
Counter pollution at sea equipment	Salvage and chemical response equipment Dundee, Barnsley and Bristol
Shoreline clean-up equipment	Dundee, Barnsley and Bristol
Dispersant	Stockpiles (major and minor) at several locations around the UK (circa 1,400 tonnes consisting of seven different types)

The CPR branch also maintain an aerial surveillance and dispersant spraying capability. This capability includes:

- Aerial surveillance and dispersant spraying for oil spill incidents
- Regular airborne surveillance flights are undertaken to monitor pollution from shipping across the UK Counter Pollution Control Zone;
- Aircraft are regularly deployed following reports of incidents to assess the size and extent of any spill, and to identify any contravention of national or international law.
- A satellite surveillance programme over parts of the UK's Pollution Control Zone. Surveillance programmes are carried out in partnership between the U.K. and other European states.

MCA contracted aircraft operate both a pollution monitoring, surveillance and dispersant spraying.

The surveillance aircraft are fitted with the latest maritime surveillance system. The system is capable of the detection and evaluation of pollution on the sea both day and night, in all weathers.

The main components are a Sideways Looking Airborne Radar (SLAR) for large area, long-range detection (20 miles for sea surface and 40 miles for detection on shipping patrol), an Ultra Violet (UV) sensor for accurate area measurement and Thermal Infra



FORTH PORTS LIMITED

Red (IR) sensor for relative oil thickness measurement. There is also a Night Identification System, which enables the name and port of registration of any vessel to be taken in darkness. Digital video and still cameras provide the photographic evidence required for successful prosecutions of illegal polluters. The whole system is fully integrated with data being fed from the navigation and flight systems. The normal aircraft communications system is supplemented by marine band and HF radios. Data, pictures and information can be sent directly to ground stations using the Data Transfer System.

Mobilisation details for MCA equipment are provided below:

Table 7.4 TIER THREE RESPONSE CAPABILITY		
Response Capability Mobilisation Procedure		
Maritime and Coastguard Agency Pollution capability includes aerial surveillance, dispersant spraying response, at sea oil recovery, and beach cleaning stockpiles.	Pollution reports (POLREPS) to be sent without delay to MRCC Aberdeen. The on- call CPSO will then decide if MCA resources are required. MRCC Aberdeen – Tel: 01224 592 334	

7.5: Waste Disposal Companies

Table 7.5 Waste D	Disposal Contractors		
Augean	Mobilisation via Augean Treatment Ltd		
	Clark St Paisley		
	Tel: 01418 875689 (Office Hours)		
	Fax: 01418 877846		



Section 8: Emergency Contact Directory

All Emergency Contact details can now be found in the stand-alone document

- Forth Ports Limited Emergency Contacts Directory.

The most up to date copy is held by FTNS.



Section 9: Environmental Database and Priority Protection Areas: Forth Ports Harbour Area

9.1: Environmental Database

Table 9.1 provides an environmental sensitivity analysis of the Forth Ports Harbour area and its coastal fringes. The Firth of Forth is an extremely sensitive environment with a range of international, European and national conservation designations, sensitive shoreline types which provide habitats for scarce plant communities and overwintering waders and wildfowl, and rocky islands that hold nationally important numbers of seabirds. Along with resident and visiting populations of marine mammals and cetaceans and internationally protected migratory fish species. The Firth of Forth is also one of the most important shipping areas in Scotland, whilst amenity beaches, marinas and yachting activities form an integral part of the socio-economic environment.

The database contained in Table 9.1 provides the following:

Habitat Type – listed in order of decreasing vulnerability to oil spill damage on a scale of 1 in 10 in terms of potential vulnerability to oil spill damage, 1 indicating lesser vulnerability and likelihood of self-cleansing and 10 indicated very high vulnerability and inability to self-cleanse.

Ecological Value – presence and importance of bird populations and their seasonal variation; presence and importance of features of particular marine / botanical / geological conservation interest; usage as fishery nursery area with nursery period.

Conservation Status – presence of conservation designations of international, national and local nature conservation importance, including RAMSAR, and SPA (Special Protection Areas) sites, SAC's (Special Area of Conservation), SSSI's (Sites of Special Scientific Interest), RSPB (Royal Society for the Protection of Birds) sites and local nature reserves.

Socio-Economic Importance – commercial shipping presence and importance of commercially important shellfisheries and fin fisheries, presence of beaches of amenity value and other recreational activities.

Location of key environmentally sensitive areas are shown on Map 8 Priority Protection Areas.

Note that individual SSSI's have not been mapped as they cover the whole of the Harbour Area from Alloa Flats to Fife Ness and North Berwick and under UK and EU designations are treated as a single ecological unit. Maps of the SPA and Ramsar sites are provided at the end of Section 1 courtesy of NatureScot.

Additional environmental information can be found in Appendix 11 and Appendix 12 for the Ports of Grangemouth and Leith respectively.



Table 9.1 Environmental Sensitivity of the Firth of Forth

Habitat Types (Vulnerability Index 10-1 in order of decreasing vulnerability to oil spill damage; a rating of 10 indicates extremely high vulnerability to oil pollution whilst a rating of 1 indicates that the shoreline will not experience extreme damage and is likely to be self-cleansing)					
10 – Saltmarshes / Reedbeds	 ✓	7 - Gravel Beach			~
9 - Sheltered Tidal Flat	s ✓	6 - Mixed Sand & Gravel Beach	~	2 - Eroding Wave Cut (Shore) Platform	 Image: A start of the start of
8 - Sheltered Rocky Co	ast	5 - Exposed Compacted Tidal Flats	~	1 - Exposed Rocky Headland	
Rocky Shores		9.5	%		
Sand Shores and sh	ingle sh	ores 11%	6		
Tidal Flats(mud and	l compa	cted sand tidal flats) 74%	6		
Salt Marshes		4.5	%		
		Habitat Types			
	 Saltmarshes develop on intertidal land within the range of the normal spring tides, where colonisation by halophytic plants, i.e. plants which are adapted to high salinities are able to withstand immersion in sea water, takes place. Important areas of saltmarsh are supported at Kinneil Kerse, Skinflats, Tyninghame and Aberlady. Dumbarnie Links contains the largest area of saltmarsh on the north shore of Firth of Forth. The largest area of pioneer saltmarsh in the Forth occurs on Alloa Inch. Saltmarsh communities in the Forth are characteristically zoned from low to high water mark and are dominated by sea aster <i>Aster tripolium</i>, common saltmarsh grass <i>Puccinellia maritima</i>, saltmarsh rush <i>Juncus gerardii</i>, and sea club-rush <i>Scirpus maritimus</i>. Several of the saltmarsh plant communities are scarce in the east coast of Scotland. Beach head saltmarsh occurs at scattered localities at Blackness Bay, Burntisland Bay, Torry Bay, and Ruddons Point. Here, greater sea-<i>Spurrey spergularia</i> media, 				
SHELTERED TIDAL FLATS	 sea plantain <i>Plantago maritima</i>, glasswort <i>Salicornia europaea</i> and sea arrowgrass <i>Triglochin maritima</i> are common The Firth of Forth includes extensive sheltered tidal flats which are biologically very productive. The mudflats are invertebrate rich and form important feeding grounds for the abundant waders and wildfowl in the Forth. Mussel beds occur on the lower shores in some areas and marine algae such as Fucus, Ascophyllum and Enteromorpha species, and eelgrass Zostera species are supported on these mudflats. 				
	On the north bank Torry Bay mudflats are characterised by the polychaete worm <i>Manayunkia aestuarina</i> ; and support extensive carpets of the nationally scarce eelgrasses <i>Zostera angustifolia</i> , Z marina, Z noltii. The mudflats are interspersed with rocky and stony areas which support communities of marine algae Fucus, Ascophylium and Enteromorpha species. Scattered mussel beds occupy the lower intertidal shore at Torry Bay On the south bank extensive tidal mudflats occur at Skinflats, Kinneil Karse,				
	Blackne	ss Bay and the Forth Bridge to Gran e flats are nursery grounds for variou	ton sh	nores. It is also thought that some	
COMPACTED TIDAL FLATS		re extensive sandy areas throughou r Bay, Drum Sands, Gosford bay, Ab			



COARSE/FINE SAND BEACHES	The Firth of Forth has extensive sandy beaches at locations which include, on the north bank, Ellie, Earlsferry, Leven, Largo, Kirkcaldy,Kinghorn, Pettycur, Aberdour, and on the south bank Cramond, Portobello, Gullane, Yellow Craig, Berwick Bay and Milsey Bay.
ROCKY SHORE (including shingle beaches) /ROCKY SHORE PLATFORMS	Rocky shores (including shingle beaches) and rocky shore platforms occur extensively on the north and south banks of the Outer Firth. Locations of the north shore include Barnsmuir Coast, Crail, Anstruther, Pittenweem, St Monans, Kinghorn, Weymess, on the south shore and the Forth Islands: Isle of May, Inchmickery, Inchkeith, Fidra, Yellowcraig, Lamb, Craigleith, and Bass Rock.
	Ecological Value
WATERFOWL	The Firth of Forth supports abundant wildfowl and waders and is particularly important for its wintering bird species. The Firth of Forth is the second most important estuarine area for wintering birds in Scotland, and eleventh in the UK, and is significant both in terms of waterfowl density and abundance.
	Concentrations of waterfowl are found at virtually all inter-tidal areas in the estuary. However, certain areas are of particular importance. Internationally and nationally important numbers of wintering and moulting wildfowl and waders occur in the inner Forth, at Kinneil Kerse, Skinflats, Torry Bay and Alloa Inches. The invertebrate rich mudflats are used for feeding at low tide and higher ground including saltmarsh used as high tide roosts and feeding sites. Shelduck form a population of international importance, and nationally important numbers of wintering knot, redshank and great crested grebe occur here. Important populations of teal and goldeneye occur in the inner Forth.
	Several species of national importance utilise the shoreline, intertidal area and offshore waters of the Forth, including common and velvet scoter, divers, eider, bar- tailed godwit, cormorant, long-tailed duck, ringed plover, grey plover, oystercatcher, turnstone, dunlin, red-breasted merganser, grebe, and curlew. Regionally important wildfowl and waders include pochard, wigeon, golden plover, pintail, mallard and lapwing.
	Nationally important numbers of wintering divers, grebes and sea ducks frequent the offshore areas of the outer Forth. Wintering pinkfooted geese are supported at Aberlady Bay and Knot and Bar-tailed Godwit occur at Aberlady Bay and on the Burntisland - Kirkcaldy coast, where the largest concentration of waders on the north shore of the outer Forth can be found. The shallow, sheltered waters of Largo Bay attract nationally important numbers of eider, goldeneye, scaup (quarter of British wintering population) and red-breasted merganser. The rocky East Lothian coastline, between Gullane and Broadsands and North Berwick, supports nationally important numbers of turnstone and purple sandpiper.
	(Data sources : NatureScot citations of Firth of Forth, Forth Islands and Imperial Dock SPA sites; NatureScot citations from the Firth of Forth and Forth Islands SSSI's; Nature Scot citation for the Firth of Forth RAMSAR site)
SEABIRDS	The Firth of Forth and the Forth Islands supports international and nationally important populations of Sandwich tern, Roseate tern and Common tern. The roseate tern colony is the most northerly of only six regular British colonies.
	Imperial Dock at Leith Docks also supports breeding populations of Common tern, with this location supporting the largest Common Tern colony in the Forth and one of the largest colonies in the UK.
	The Forth Islands regularly support internationally important populations of the migratory species including 21,600 gannet, 2,400 shag, 1,500 lesser black-backed gull s, 14,000 puffin, 200 cormorant, 8,400 kittiwake, 16,000 guillemot and 1,400 razorbill. The Isle of May is the only large breeding seabird colony in Fife, supporting nationally important populations of Shags, Kittiwakes, Puffins, Guillemots and Eiders. The rocky islands of the Forth including Inchmickery, Bass Rock, Long Craig, Fidra



	and Lamb together from the largest breeding colony of seabirds in the Lothians.
	(Data sources : NatureScot citations of Firth of Forth, Forth Islands and Imperial Dock SPA sites; Scottish Natural Heritiage citations from the Firth of Forth and Forth Islands SSSI's and Isle of May)
MARINE MAMMALS	The Isle of May supports a breeding colony of grey seals <i>Halichoerus grypus</i> . The site is the largest east coast breeding colony of grey seals in Scotland and the 4 th largest breeding colony in the UK.
	Small numbers of common seals also occur in the Firth. Designated seal haul-out sites exist at Kinghorn Rocks, Inchkeith, Inchmickery and Cow & Calves and Craigleith.
	Bottle-nosed dolphin, minke whale and harbour porpoise can be found in the Firth. All cetaceans are European Protected Species under the Habitats Regulations.
BOTANICAL CONSERVATION IMPORTANCE	The Firth of Forth SSSI comprises an extensive intertidal and coastal habitats. Extensive mudflats make up much of the intertidal area with areas of sand, shingle, rock and boulders. Marine algae such as Fucus, Ascophyllum and Enteromorpha species, and eelgrass Zostera species are supported on these mudflats. Nationally scarce species include eelgrasses – narrow-leaved eelgrass <i>Zostera angustifolia</i> , eelgrass Z. marina, dwarf eelgrass Z. noltii, which are supported on the extensive mudflats. Locally rare sea wormwood <i>Artemisia maritima</i> can also be found in these areas.
	Associated coastal habitats include saltmarsh, grassland and sand dunes
	The Forth estuary is of special interest for the following habitats and species:
	Saltmarsh and sand dunes
	Important areas of saltmarsh are supported at Kinneil Kerse, Skinflats, Tyninghame and Aberlady. Dumbarnie Links contains the largest area of saltmarsh on the north shore of Firth of Forth. Several of the saltmarsh plant communities are scarce in the east coast of Scotland.
	The main areas of sand dune vegetation occur in the outer Firth. Between Gullane and Broadsands is the largest and most complex sand dune system in the Lothians, with its noteworthy lichen rich dune slacks. Aberlady Bay contains the most extensive complex of sand dune, saltmarsh and mudflat in SE Scotland.
	Fen and lagoon
	The intertidal bays of Skinflats and Kinneil Kerse support a range of other estuarine habitats and plant communities including brackish fen and coastal sluiced saline lagoons.
MARINE CONSERVATION IMPORTANCE	The Isle of May in the outer Forth is a Marine Special Area of Conservation for its reefs and grey seal populations. The Isle of May is an important site for its marine habitats and communities with habitats including sea inlets, salt steppes and islets. (It should be noted that just outwith the Forth the North Berwickshire and Northumberland SAC commences just to the south of Dunbar. It is designated for Grey Seal, Internatial mud and sand flats, reefs, caves and shallow inlets and bays).
GEOLOGICAL CONSERVATION IMPORTANCE	The coastline at Dunbar is of note for the outstanding complexity of rocky coastal landforms which it exhibits. Of particular interest is a series of rock platforms representing different relative sea levels in the area.
	The coastal margins of the Forth demonstrate an exceptional variety of rocks and fossils that have been crucial in understanding the palaeogeography and palaeoecology of Scotland during the Carboniferous geological period.
	The sedimentary rock sequence has worldwide significance for fossil remains. At Burntisland in Fife, the Abden Bone Bed has yielded a rich and diverse fish fauna, other 'fossil fish' localities include Ardross Castle also in Fife, Cheese Bay near



	Gullane and Wardie Shore. Wardie is of international importance, yielding at least eighteen species of fish, including sharks.	
	Geological Conservation Review sites are found along the Dunbar coast, Leith- Prestonpans area, Wardie, North Berwick and East Weyms-Anstruther	
MIGRATORY FISH	There is a designated Special Area of Conservation (SAC) in the River Teith for migratory species including Atlantic Salmon, Brook Lamprey, River Lamprey and Sea Lamprey.	
FISHERIES NURSERY AND/OR SPAWNING AREA	Significant nursery areas for flatfish exist in a number of nearshore waters including Largo Bay, Pettycur Bay to Buckhaven on the north coast and Drum Sands, Gosford and Aberlady Bays on the south coast.	
	Conservation Status	
RAMSAR SITE	The Firth of Forth RAMSAR site stretches from the Alloa Inches in the west to Fife	
Refer Map 5 at end of Section 9.1	Ness and Dunbar in the east. It is considered to act as a single ecological unit. The Firth of Forth is a designated RAMSAR qualifying for this designation by regularly supporting 95000 over-wintering waterfowl (refer Waterfowl).	
SPECIAL PROTECTION AREAS	Three sites in the Forth estuary have been have been designated as a Special Protection Areas (SPA) under the <i>EC Directive on the Conservation of Wild Birds</i> 1979. These sites are:	
Refer Map 4 at end of Section 9.1	Firth of Forth extending from Alloa Inches in the west to Fife Ness and Dunbar in the east. It is considered to act as a single ecological unit. Qualifying features are the support of overwintering populations of a range of wintering bird populations, including Slavioan grebe, pink-footed goose, shelduck, Goldeneye, knot, redshank, bar-tailed godwit, turnstone and sandwich tern.	
	Forth Islands including the islands of Inchmickery, Isle of May, Fidra, Lamb, Craigleth, Bass Rock and Long Craig (and their adjacent marine areas). Qualifying features include breeding populations of Sandwich tern, roseate tern and common tern, as well as internationally important populations of gannet, shag, lesser black- backed gull, puffin, cormorant, kittiwake, guillemot and razorbill	
	Imperial Dock Lock, Leith. Qualifying features are the breeding populations of Common tern, one of the largest populations in the UK.	
	The Outer Firth of Forth and St Andrews Bay Complex is an extensive SPA off the south-east coact of Scotland. It stretches from Abroath in the North to St Abb's Head in the South and encompasses the Firth of Forth, the outer Firth of Tay and St Andrews Bay. The waters in this SPA attract one of the largest and most diverse marine bird concentrations in Scotland and the site is classified for the protection of 21 seabird and waterbird species	
SITE OF SPECIAL SCIENTIFIC INTEREST	The Forth estuary has seven Sites of Special Scientific Interest (SSSIs) within it as follows: 1. Firth of Forth	
	The site stretches from the Alloa Inches in the west to Fife Ness and Dunbar in the east. It is considered to act as a single ecological unit. The site has been designated for its wide range of habitats supporting invertebrates, rare species eel grass, marine algae and provides overwintering feeding and roosting grounds for 95000 waders and wildfowl	
	2. Forth Islands	
	 Have a range of marine habitats that support breeding populations of Sandwich tern, roseate tern and common tern, as well as internationally important populations of gannet, shag, lesser black-backed gull, puffin, cormorant, kittiwake, guillemot and razorbil. 	
	3. Inchmickery	



FORTH PORTS LIMITED

Clearwater Forth

	• Site supports breeding populations of four species of tern, common arctic, sandwich and roseate.	
	4. Isle of May	
	 Site supports a large breeding colony for populations of shag, kittiwake, puffin, guillemot, and eiders. It is also one of only 3 breeding grey seals off the east coast of Britain. 	
	5. Barnsmuir Coast	
	 Site designated for saltmarshes that support plant communities that are scare on the east coast of Scotland. 	
	6. Fife Ness Coast	
	 Main reason for notification of the coast is the geological importance of coastal exposures (refer above) as well as saltmarshes of a type which is scare in Britain. 	
	7. Bass Rock	
	• Site supports one of the largest breeding seabird colonies in the Forth.	
COUNTRY PARK	Country Parks are statutorily declared and managed by local authorities under the Countryside Act 1968. There is a Country Park at Long Craig and at Tyinghame (John Muir Country Park).	
LOCAL NATURE RESERVES	Local Nature Reserves occur at Torry Bay, Skinflats, Kinneil Kerse, Aberlady Bay, and Bass Rock	
RSPB SITES	The Royal Society for the Protection of Birds (RSPB) non-statutory reserve sites on the rocky islands of Fidra, Inchmickery and Lamb and a site at Skinflats.	
WILDLIFE RESERVES & SITES	The Wildlife Trusts were established to promote non-statutory nature conservation at a local level in Britain. There are Scottish Wildlife Trust Reserves on the Firth of Forth including, including Long Craig Island, Kilminning Coast, and Barnyards Marsh (see www.swt.org.uk/visit/reserves).	
Socio-Economic Importance		
COMMERCIAL WATERWAYS, PORTS AND	The Forth is one of the most important shipping areas in Scotland one of the country's largest commercial waterways contributing very significantly to the economy of the surrounding regions.	
WHARVES	Much of the commercial shipping activity is associated with export of crude oil and refined products occurring from Grangemouth Docks, Hound Point Marine Terminal and Braefoot Bay. These facilities have approximately 1500 voyages per year collectively, although absolute numbers vary from year to year.	
	There are approximately 4000 vessels transiting to the various ports and anchorages in the Forth per annum, with vessel types including crude oil and product carriers, bulk carriers, ro-ro, offshore, general cargo, and naval vessels.	
SHELLFISHERIES	There is a significant, although declining, <i>Nephrops</i> fishery in the outer firth and creeling for lobster and crab along the coastal fringe. The East of Scotland Inshore Fisheries Group has aspiration to increase the coastal fisheries in the Forth.	
FINFISHERIES	Salmon fishing rights exist around the shores of the Firth that allows for netting of salmon out to 1300m from mean low water mark. However sites are presently unoccupied.	
	Coastal fishing is important from Crail, Anstruther, and Pittenweem.	
AMENITY BEACHES	There are numerous amenity beaches throughout the Forth and are used for recreational activities all year .These shorelines include Fife Ness, Crail, Anstruther, Elie, Pittenweem, St. Monans, Earlsferry, Largo,, Leven, Methil, Kirkcaldy, Kinghorn,	



	Pettycur, Burntisland, Aberdour, Cramond, Portobello, Port Setton, Longniddry, Gullane, Yellowcraig, North Berwick Bay and Milsey Bay
WATER CONTACT ACTIVITIES	Water contact activities tend to be associated with the shores from Fife Ness to North Queensferry on the north side and from Port Edgar to North Berwick on the south coast.
	Water contact sports are extremely popular in the Forth with sailing and yachting taking from the numerous marines and boat clubs. Other water contact activities include:
	Boat trips are made from a number of locations to the Forth Islands and Isle of May, boat trips to the Isle of May are made from Crail and Anstruther. Occasionally trips can be taken as far as Stirling.
	Dive sites occur at Isle of May, Fife Ness,
	Canoeing occurs off Anstruther and Cellardyke
	Surfing, sailboarding and water skiing takes place out of Ellie, Blackness Bay, Cramond, Port Edgar, Portobello, Musselburgh, Longniddry Beach, Prestonpans, Gosford Bay, Gullane Bents, and North Berwick
OTHER RECREATIONAL ACTIVITIES	Bird watching occurs from a range of locations including Largo Bay, Torry Bay, Skinflats area, Aberlady Bay,
MARINA OR MOORINGS	Moorings are widely spread throughout the Forth and a number are associated with yachting clubs; marinas and moorings are found at Crail, Anstruther, Earlsferry, Methil, Lower Largo, Kinghorn, Burntisland, Kirkcaldy, Burntisland, Aberdour, Dalgety Bay, North Queensferry, Bo'ness, Port Edgar, South Queensferry, Cramond, Granton, Cockenzie, Fishbarrow, North Berwick


Map 4: Clearwater Forth SPA Sites



Map 5: Clearwater Forth RAMSAR Sites





Map 6: Seabird Nesting Grounds



Map 7: Intertidal Foreshore Substrate



E	Boulders/Loose Rock
	Gravel
-	1ade Ground (Man Made)
P	1ud
E.P	1ud and Gravel
r	Not Present
F	Rock Platform
Grav	Rock Platform with Bank of rel
	Rock Platform with ders/Loose Rock
5	Sand
	Sand and Gravel
	Sand and Mud
	Inspecified



Map 8: Priority Protection Areas





Table 9. 2 Forth Ports Harbour Area: Priority Protection Areas

TABLE 9.2 FIRTH OF FORTH HARBOUR AREA : PRIORITY PROTECTION AREAS (Use with Firth of Forth Priority Protection Areas Map and Oil Spill Response Map) A – HIGH PRIORITY AREAS Main Period of Area Category **Key Sensitive Features & Importance** Sensitivity Areas of sheltered tidal flats with extensive saltmarsh habitat of national A1 Areas botanical importance / sites of national importance for bird populations Internationally important numbers of wintering waterfowl. July – March Skinflats regionally important for passage migrants Botanical conservation importance for estuarine habitats All vear including saltmarsh, brackish fen, coastal lagoon system Significant flatfish nursery area All year Internationally important numbers of wintering waterfowl, July – March **Kinneil Kerse** large flock of post-breeding moulting shelduck Botanical conservation importance for plant communities All year including pioneer saltmarsh, brackish marsh Significant flatfish nursery area All year □ Nationally important numbers of wintering waterfowl **Torry Bay** June – March Botanical conservation importance for saltmarsh All year □ Marine conservation importance for nationally scare All year eelgrasses, marine algae and invertebrate species All year Significant flatfish nursery area Nationally important seabird colonies April - September Inchmickery Nationally important numbers of wintering waders October – March Largo Bay Internationally important flocks of seaduck All year All year Significant flatfish nursery area All year Creeling for lobsters/crabs; periwinkles taken from shore April - September Several amenity beaches around Largo, Leven etc Nationally important numbers of wintering waterfowl October – March Aberlady Bay Important seabird breeding colonies April – September Botanical conservation importance for saltmarsh, mudflats, sand dunes Nationally important numbers of wintering waders, October – March Gullane Bay important eider moult site All year Important site for flocks of seaduck, divers and grebes April - September

□ Sandy beach of high amenity value & EC Designated



		Bathing Water; water-based recreational usage	
Bass Rock		Internationally important seabird colonies	February – August
Isle of May		Nationally important numbers of wintering waterfowl, and breeding eider ducks during summer months	October – March
		Nationally important seabird colonies	All year
		Important grey seal breeding and haul-out site	Autumn
		Marine conservation importance for exposed marine habitats, communities and species	All year
		Creeling for lobsters/crabs; periwinkles taken from shore	All year
A2 Areas		Water Intakes / Commercial Shellfish	Sites
Deepsea World, N. Queensferry		Water abstraction point for marine life centre	All year
A3 Areas		Nationally Important Seal Sites	
Inchkeith Island		Important grey seal haul-out site	Autumn
		Large numbers of breeding seabirds	All year
Forth Islands		Important grey seal haul-out sites	Autumn
(Eyebroughty,		Nationally important seabird colonies	All year
Fidra, Lamb and Craigleith)			
		B- MODERATE PRIORITY AREAS	
B1 Areas	Areas of sheltered tidal flats with small areas of saltmarsh habitat of local importance for bird populations		
Blackness Bay		Regionally important numbers of wintering waterfowl	October – March
		Marine conservation importance for locally rare plants including eelgrasses and marine algae	All year
Drum Sands		Regionally important numbers of wintering waterfowl	October – March
		Wintering flocks of gulls	November – January
		Significant flatfish nursery area	All year
		High recreational usage of beaches and water	April – September
		Mussel beds occasionally exploited	All year
Leith to		Regionally important numbers of wintering waterfowl	October – March
Prestonpans Shoreline		Mussel beds off Joppa coast occasionally exploited	All year
Gosford Bay		Regionally important numbers of wintering waterfowl	October – March
		Offshore waters hold important numbers of seaduck,	All year
		divers and grebes	April – September



B2 Areas	Areas of intensive use by pleasure boats / leisure	e craft / marinas
Port Edgar	Port Edgar marina, sailing school, windsurfing, canoeing	All year
Granton Harbour	Several yacht clubs, moorings	All year
Leith Docks	Major commercial port, moorings	All year
Milsey Bay	Moorings at North Berwick, windsurfing, dinghy sailing	All year
B3 Areas	Amenity beaches of high tourist us	e
Burntisland	Sandy beach of amenity value	April - September
Aberdour Silversands	Sandy beach of high amenity value & EC Designated Bathing Water	April – September
Pettycur	Sandy beach of high amenity value & EC Designated Bathing Water	April - September
Earlsferry	Sandy beach of amenity value	April – September
Yellowcraig	Sandy beach of high amenity value & EC Designated Bathing Water	April - September
Milsey Bay	Sandy beach of high amenity value & EC Designated Bathing Water	April - September



A.1. THE LEGAL PERSPECTIVE

International Oil Spill Response Convention: Oil Pollution, Preparedness, Response and Co-operation (OPRC) Convention 1990

The Oil Pollution Preparedness, Response, and Co-operation Convention (OPRC) was developed by the Marine Environment Protection Committee (MEPC) of the International Maritime Organisation and adopted by a diplomatic conference in November 1990. The Convention came into force internationally on 13 May 1995 and in the UK on 16 December 1997.

The Convention provides a framework for international co-operation for combating major oil pollution incidents and places various obligations on signatories. The mandatory requirements of the Convention are as follows:

Requirement	Compliance
UK registered ships and sea ports to hold Oil Pollution Emergency Plans	For ship board plans the requirement has been implemented through regulation 26 of The International Convention on the Prevention of Pollution from Ships (MARPOL 73/78) which applies to UK registered ships
	A statutory duty has been placed on ports and harbours to prepare and submit oil spill contingency plans to MCA.

<u>Article 3</u> – Oil Pollution Emergency plans

Article 4 - Oil Pollution Reporting Procedures

Requirement	Compliance
Ships and sea ports are required to report all actual or observed oil spills	The requirements are met through MARPOL and secondary legislation.

Article 5 – Action on Receiving an Oil Pollution Report

Requirement	Compliance
Assessments be made of all pollution reports, and for States affected or likely to be affected to be informed.	MCA assesses all pollution reports made in the UK. Other States are informed, as necessary, through agreements such as the Bonn Agreement and the Mancheplan to which the UK is a party.



<u>Article 6</u> – National and Regional Systems for Preparedness and Response

Requirement	Compliance
Designation of a competent national authority with responsibility for oil pollution preparedness and response, receipt and transmission of pollution reports, and, on behalf of the State, for requesting or deciding to render requested assistance.	Competent national authority for the UK is the MCA Counter Pollution and Response Branch.
Establish national contingency plan	UK has National Contingency Plan for response to marine pollution
Establish minimum level of pre-positioned combating equipment	MCA maintains stockpiles of beach cleaning and at sea equipment to respond to incidents around the UK coast.
Programme of exercises and training	MCA conducts own exercises and participates in those programmed by the Bonn Agreement. MCA also regularly involved in local authority, port authority and oil industry exercises.
Detailed plans and communications for responding to incidents	In addition to the National Contingency Plan the MCA has developed agreed plans through its bi- lateral and regional agreements. HM Coastguard and MCA are on call 24 hours a day.
Provision to the IMO of details of the competent authority, the national contingency plan and the resources which may be available to other States	Details of equipment available to the MCA are included in the EU Information System available to the IMO. A copy of the National Contingency Plan has been sent to the IMO. The availability of equipment to other states will depend on circumstances.

Article 7 – International Co-operation in Pollution Response

Requirement	Compliance
Subject to capabilities and availability, the provision of advise, technical support, and equipment when requested by another country	Requests for assistance from countries other than those with whom the UK has formal regional or bi- lateral agreements covering co-operation and support will be received by the Department for International Development who, in consultation with the MCA will decide, subject to Ministers, the UK response.

Article 8 – Research and Development

Requirement	Compliance
Promote and exchange results of research and	The MCA publishes the results of its research and
development, the establishment of links between	development and is working towards forging
research institutions, the promotion of international	international links with research institutions. The UK
symposia, and the development of standards for	will discuss compatible equipment and techniques
compatible equipment and techniques	through the forum of the Bonn Agreement.



A1.2 Prosecution of Offences

Any harbour authority who without reasonable cause:

- 1. Fails to submit or re-submit an oil pollution emergency plan in accordance with the requirements of the Merchant Shipping (Oil Pollution Preparedness, Response and Co-operation Convention) Regulations;
- 2. Does not maintain an oil pollution emergency plan, as approved (with alterations directed by the MCA or the Secretary of State, as the case may be, if so directed) under the regulations;
- 3. Fails to implement its oil pollution emergency plan in contravention of the regulations;

Shall be guilty of an offence punishable on summary conviction by a fine not exceeding the statutory maximum or on conviction on indictment by a fine.

A.1.2.1 MARPOL

Ports and harbours have the power to prosecute offences committed within their areas of jurisdiction. Under section 44 of the Merchant Shipping Act 1995 a harbour master who believes that oil has been discharged in contravention of section 131 into the harbour can detain the offending vessel for up to seven days so that proceedings can be instituted.

A1.3 Liability and Compensation for Pollution Damage

The ease with which those involved in clean up operations can obtain compensation depends upon the type and source of pollutant involved. Currently there are four distinct cases:

- 1. Where pollution is caused by persistent oil carried in a tanker, either as cargo or as a fuel, compensation is available under an international compensation regime. Note that the definition of a persistent oil is highly technical; crude oil and heavy fuel oil used by ships are both persistent oils, aviation fuel and petrol are non-persistent oils;
- 2. Where pollution is caused by persistent oil carried in any other type of ship (normally as fuel), there are special rules in UK legislation designed to make it easier for claimants to obtain compensation;
- *3.* Where pollution is caused by a pollutant from a ship other than persistent oil, claims are subject to the normal rules of civil common law;
- 4. Where pollution is caused by an unidentified source, no compensation can be obtained unless the claimant can prove that the source of the pollution was a tanker.



A1.4 Cost Recovery

A.1.4.1 Pollution caused by persistent oil carried in a tanker.

The international compensation regime for oil pollution damage from tankers is established by two international conventions: the International Convention on Civil Liability for Oil Pollution Damage (Civil Liability Convention) and the International Convention on the Establishment of an International Fund for Compensation for Oil Pollution Damage (Fund Convention). The former convention deals with the liability of tanker owners, the latter establishes the International Oil Pollution Compensation (IOPC) Fund. The Merchant Shipping Act 1995 implements the regime in the UK.

Under these conventions, the tanker owner and the IOPC Fund are strictly liable for the costs of reasonable clean up operations. Strict liability means that the claimant does not need to prove fault in order to obtain compensation. The tanker owner and the Fund may be exonerated from liability only if they can prove that the damage was due to one of a limited number of exceptional circumstances (e.g. an act of war).

Tanker owners generally have the right to limit liability to an amount determined by reference to the gross tonnage of the tanker. This amount varies from about £3.7 million for a small tanker (less than 5000 gross tons) to about £72.5 million for a very large tanker (over 140,000 gross tons). Tanker owners are required to maintain insurance to cover their potential liabilities and to carry a State – issued certificate on board to confirm that this insurance is in place. Most tanker owners obtain this insurance through a Protection and Indemnity (P&I) Club. Under the terms of the Civil Liability Convention, claimants have the right to claim directly against the insurer.

The IOPC Fund is an intergovernmental organisation, established by the Fund Convention, which generally pays compensation to supplement that available from the tanker owner. Payments of compensation and the administrative expenses of the IOPC Fund are financed by contributions levied on any person in a Fund-member state who receives an annual quantity of more than 150,000 tonnes of crude oil and heavy fuel oil following carriage at sea. The total amount of compensation available from the tanker owner and the IPOC Fund together is about £164 million (for all sizes of tanker).

Claims for clean up costs under the terms of the Civil Liability Convention should be submitted in the first instance to the tanker owner and/or to the relevant P&I Club. The identity of the P&I Club and contact details can normally be obtained from the tanker owner's local agent or master. To obtain compensation under the terms of the Fund Convention, claimants should submit their claims directly to the International Oil Pollution Compensation Fund. Details of the information that must be provided in a claim is provided in the National Contingency Plan for Marine Pollution from Shipping and Offshore Installations, produced by the MCA.



A.1.4.2 Pollution Caused by Persistent Oil Carried in Ships Other Than Tankers

At present, there are no comparable international arrangements on liability and compensation for damage caused by persistent fuel oil carried in ships other the tankers. The UK has introduced national legislation (Section 154 of the Merchant Shipping Act 1995) to make owners of ships, other than those to which the Civil Liability Convention applies, strictly liable for pollution damage caused by persistent oil. This provision makes it simpler for claimants to recover the costs of damage caused by the fuel carried by non-tankers, because claimants do not have to prove that the ship owner was at fault.

A.1.4.3 Pollution Caused by Pollutants Other Than Persistent Oil

There is currently no statutory law dealing with liability and compensation for pollution damage caused by substances other than persistent oil. Liability and compensation for pollution damage caused by substances other than persistent oil are currently governed by the ordinary rules of civil common law.

A.1.4.4 Pollution from Unidentified Source

Generally, compensation can only be obtained if the claimant knows its precise source. There is one exception to this, however; the IOPC Fund will pay compensation for reasonable clean up costs if the claimant can prove that the measures were taken in respect of pollution by persistent oil from a tanker.



A.2. CLEARWATER FORTH EQUIPMENT RESOURCE INVENTORIES

The following resources may be available for use under the Clearwater Forth Scheme. Use of these resources will depend on availability at the time of the incident.

A.2.5 Forth Ports Limited / Targe Towing Limited

TIER 1 EQUIPMENT	CAPABILITY
120 metres of 3M T270 oil sorbent boom	Tier 1 response kits located at the following ports: • Leith (detailed below)
 12 rolls of 3M oil sorbent pads (480mm x 44 metres) 	 Grangemouth Rosyth (also covering Methil, Kirkcaldy and Burntisland)
 200 heavy duty black plastic bags 	
 220 metres of 10mm polypropylene rope 	

TIER 1 EQUIPMENT-LEITH	CAPABILITY
• 2 x packs of rags	One person available 24 hours
• 150m sorbent boom	 3 personnel available within office hours
• 15 x rolls sorbent pads	
 2 coils of 8mm polypropylene rope 	
 Coil of 24mm polypropylene rope 	
Gloves, bin bags and knife	

In addition, there is 100m of 1500mm fence boom in stillage at Leith (loan stock from A&A).



TIER 2 EQUIPMENT	CAPABILITY
 MT Fidra (Operated by Targe Towing Limited) 	21,000 litres of VDC+ dispersant *Vessel has spray booms but no capacity to store recovered oil

INEOS Forties Pipeline System

A.2.6.1 INEOS FPS Hound Point Response Vessels

EQUIPMENT	CAPABILITY
 Ro-Boom Side Sweep System Seamop 4090 Skimmer 224m Ro-boom 1300 containment boom Dispersant spraying system 47,000 litres Type 2/3 dispersant Absorbent materials 'Hopetoun' 200m³ recovery capacity - classed 'Dalmeny' 100m³ recovery capacity – not classed Workboat available to assist with dispersant spraying Terminal spill kits 	 One of the four tugs stationed at Hound Point Marine Terminal will be available dependant on operational requirements at time of request. Two of these vessels have recovered oil storage tanks with capacity for 100m³. In addition one workboat from the Hound Point fleet will be available to assist in the deployment of booms.

TYPE OF DISPERSANT	QUANTITY	LOCATION
Y SLICKGONE NS	33,000 litres	TUG HOPETOUN
Y SLICKGONE NS	2 X 14,000 litres	TUGS, QUEENSFERRY & DALMENY



A.2.6.2 INEOS Forties Pipeline System

Extensive resources are available through the Forties Pipeline System. A full list is available on request and can be requested through the KSL to the FPS IMT.



Mobile Beach Response Unit			
(Located Adjacent to Shell Control Room)	Contents:		
	Air pump, hose and adapters		
	2 * lifejackets		
	Oil spill response kit		
	30ft MSO Matasorb boom		
	6 * Matasorb rolls (sheet type)		
	30 prs wellington boots		
	15 Orange PVC suits (medium)		
	15 Orange PVC suits (large)		
	18 packs red rubber gauntlet gloves		
	6 traffic cones		
	1 * Ferno folding stretcher		
	1 * first aid kit		
	20 * plastic shovels		
	1 * steel shovel		
	1 * pick axe and shaft		
	1 * mash hammer		
	6 * angle iron posts		
	6 * wooden stakes		
	2 * packs polythene sheets		
	2 * bags Sorboil		
	2 * warning tripods		
	1 * coil rope		
	6 * tow lines		
	1 * fire extinguisher		
	1 * spare wheel and tyre		
	Boom attachment magnetic float		
	1 * bag of shackles Tools, various		
Sorbent roll	5 * packs M95		
(Located in Compressor House)			
Oil Spill Response Kit (Certified container)	Contents		
· · · · · · · · · · · · · · · · · · ·	2 closing rings		
	1 pr neoprene oil resistant gloves		
	1 * protective `Tyveck Suit`		
	1 pair protective goggles		
	1 neoprene drain stopper		
	40ft Matasorb blanket 30"		
	25 * Matasorb Pads		
	75ft Matasorb blanket 30"		
	2 Polythene 3mm bags		
Flexiboom 110mm			
Shell Jetty	200m on Hydraulic Power Reel		
Flat bed trailer	200m on hand reel		
Adjacent to Control Room	200m on hand reel		



Clearwater Forth

Forth Logistics based at Port Edgar can be mobilised to attend Braefoot bay. Five boats and equipment are stored at South Queensferry Jetty:

Boats – Wave Dancer, Saint David, Saint Colme, Wave Spirit, Wave Train.

Equipment – 50m oil absorbent boom. Approx. 100 absorbent pads. Mooring magnets. Mooring cams

Several lengths of running line. Several VHF sets. Copy of Clearwater Forth Plan.

Tier 2 – Briggs Marine Environmental Services

Briggs Marine Environmental Services have extensive stockpiles of vessels and oil spill equipment at their Burntisland base. Refer to Braefoot Bay Marine Terminal Pollution Response Contingency Plan for full details.



A.2.4 INEOS Grangemouth Equipment

A.2.4.1 INEOS Tier 1/2 Equipment

	Resources	Location	Mobilisation
•	120 metres of TROIL GP450 Boom	Old Lock Berth On Reel	Contact: INEOS Hydrocarbons Shift Manager (HSM)
•	120 metres of VIKOMA	Boatmen's Area on Reel	Tel: 01324 476151 or
	FLEXI 500 Boom	bouinen's Area on Reel	0790 1622393
•	Various Absorbents	East & West Jetties	As above

A.2.4.2 Harbour Craft & Tugs Available to Assist in Pollution Response

Vessel	Location	Mobilisation	Remarks
Svitzer Alma	Svitzer Tug Base	VHF 14	Harbour Tugs capable of rapidly
Svitzer Lyndhurst	Carron Dock,	24hrs	deploying to an area of the dock such as
Roseberry Cross	Grangemouth Docks,		the East or West Cut and using their
			Voith units to prevent an oil spill from
			spreading to other areas of the dock
			until a boom can be rigged.
Grangemouth	East Cut,	VHF 14	Fleet of highly manoeuvrable
Boatmen - work	Grangemouth Docks	24hrs	workboats manned by professional
boats		482510	boatmen who are regularly trained in
			the deployment of oil booms and other
			equipment.
`Forth King`	Carron Dock	Forth Ports	Fast survey launch capable of
		Conservancy	supporting On-Scene Commander role
			within the docks.
`Moil`	Eastern Channel	Forth Ports	Maintenance barge.
		Grangemouth	8
		Engineering	
'Forth Sentinel'	Leith	Forth Ports	Plough Dredger
		Marine Team	
'Forth Puma, Forth	Granton	VHF 72	Pilot Cutters
Leopard, Forth		Pilot vessel	
Tiger'		Coxswains	



A.2.5 Adler and Allan

Adler and Allan are contracted by Forth Ports Limited to provide Tier 2 response in the Forth Ports Harbour Area. Assets are held by Adler and Allan at either Montrose or Glasgow Depot and are available on a 24/7 rapid mobilisation basis to meet all contractual obligations. Additional resources can be called on from regional response facilities and two regional UK waste management facilities.

8.5 tonnes pre-Loaded containment & Recovery

5 units are available with	the following contents:
----------------------------	-------------------------

8.5 tonnes rigid with tail lift	1
Inflatable Sea Boom 75i	200m
Rigid Fence Boom 50p	80m
Silverbeach 55 Shore sealing boom	80m
Minimax Weir Skimmer	1
Spate 75c diesel driven pump	1
Safety boat, oars, pump and outboard	1
Generator Honda EC4000B	1
Lighting set	1
Fastank On Land Storage	2000 Gallon
Blower Echo PB6000	1
Honda WP20X Water Pump	1
Anchors chains, buoys	5 sets
Rope	400m
Medical Kit	1
Extinguisher Powder 2Kg	2
Heavy duty waste bags	100
Rakes and shovels	3 of each
Towing Bridles	3
Sand bags	50
Stakes	6
Rammer	1
Sorbents – 3m booms	4
Sorbents - Roll	1
Sorbents - sheets	3 packs
PPE safety glasses, gauntlets, overalls	20 each
Notice boards, barrier tape	2 each
Мор	1
Decontamination tank	1
Polythene sheeting	Large roll
Fuel tanks	2
Tool kit and spares kit	1





2.0 Tonnes pre-Loaded Containment

2 Units available with the following contents:

Quantity	Item Description	
1	Sprinter or equivalent	
1	Safety Boat, Oars, Outboard	
10	Inflatable sea boom 10m	
5	inshore fence boom 10m (50p)	
1	air fan blower	
2	grab bags PPE	
1	1st aid kit	
1	2kg dry powder	
5	anchors / chains / buoys	
2	shovels	
2	rakes	
1	тор	
1	rope	
1	rope	
1	oily waste bags	
1	DPM	
2	towing bridles	
1	tool kit	
2	3m abs boom	
1	1 pack pads	
1	abs roll	
1	rubber gauntlets x 10	
1	disposable overall x 10	
1	safety goggles x 10	
1	sand bags empty x 25	
1	Barrier tape x 1	
2	Fuel Tank 4.5ltr petrol / 2 stroke	
5	Wooden stakes x 5	
1	post rammer	
1	Engine oil 1ltr	
2	lifejackets	
2	torches	
2	2 x petrol cans	
1	2 stroke oil	
2	Shore sealing boom 10m	
1	Water Pump	



Response Trailers- 1.0 Tonnes pre-Loaded Containment

4 Units available with the	the following contents:
----------------------------	-------------------------

Quantity	Item Description	
1	Box trailer towable by Land Rover or equivalent	
60	Inflatable Sea Boom	
metres		
50	Fence boom	
metres		
40	Shore Sealing Boom	
metres		
1	Petrol Air blower and adaptor	
1	Water pump	
5	Anchors, chains & tripping buoys	
1 coil	10mm rope x 200m	
1 coil	12mm rope x 200m	
3	Shovels	
3	Rakes	
100	Heavy duty blue waste bags	
1 roll	Polythene sheeting	
2	Boom towing bridles	
1	Tool Kit	
1	First Aid Kit	
4	Lengths of 3m oil absorbent boom	
3	Packs of oil absorbent sheets	
1	Oil absorbent roll	
10 pairs	Rubber gauntlets and disposal overalls	
5 pairs	Safety Glasses	
50	Sand bags (empty)	
1	Roll red and white barrier tape	



Minimum Sorbent Warehouse Inventory

Code	Description	Size	Qty per pack	No. packs
0112/NET	Γ/3 Drizit Netted Absorbent Boom	20 cm x 3m	4	100
0105/NET	Г/3 Drizit Netted Absorbent Boom	12.5cm x 3m	4	100
Absorbe	nt Cushions			
Code	Description	Size	Qty per pack	No. packs
0110	Drizit Oil Absorbent Cushions	55 x 35 x 10 cm	10	40
0110	Drizit Oil Absorbent Cushions (one off)	55 x 35 x 10 cm	1	150
Absorbe	nt Pads			
Code	Description	Size	Qty per pack	No. packs
0140	Drizit Oil Absorbent Pads	40cm x 52cm	200	300
0140/1	Drizit Oil Absorbent Pads	40cm x 50cm	200	100
Absorbe	nt Rolls			
Code	Description	Size	Qty per pack	No. packs
0142	Drizit Oil Absorbent Roll	100cm x 42m	1	120
0143	Drizit Oil Absorbent Mini Roll	50cm x 42m	1	120
0142/D	Drizit Oil Absorbent Double Roll	100cm x 42m	1	25
	Drizit Oil Absorbent Double Mini Roll	50cm x 42m	1	25

Absorbent Socks

Code	Description	Size	Qty per pack	No. packs
0130/125/10	Drizit Oil Absorbent Socks	7.5 x 125 cm	10	25
0130/300/5	Drizit Oil Absorbent Socks	7.5 x 300 cm	5	20
0130/125	Drizit Oil Absorbent Socks (one off)	7.5 x 125 cm	1	600
0130/300	Drizit Oil Absorbent Socks (one off)	7.5 x 300 cm	1	200



Booms

	Trident Silverboom 75i	1500m
	Trident Silverbeach 550	800m
	Vikoma Sentinel 750 200m powered reel system	200m
	Vikoma Sentinel 450	140m
	Vikoma Shoreguardian 550	500m
	Darcy Fenceboom (various sizes)	2000m
	Fence Boom 1500	600m
	Troil Boom	90m
	Single Ship Sweep system	2
Recover	y Skimmers	
	Minimax Weir Skimmers	6
	Dragonfly/ Minifly Weir skimmers	8
	Komara 12k System	2
	GT 185 Weir System with light oil adaptor	1
	Ro-Clean Diesel Driven Rope Mop	5
	Cowen Flowline towable Rope Mop and Separator unit	1
	Vikoma T Disc	1
	Air Rope Mop	1
Pump)S	
	Double Diaphragm 2 inch ATEX air driven pumps	4
	Double Diaphragm 1 inch ATEX air driven pumps	1
	Diesel Driven Wilden Pumps	3
	Submersible pumps	Numerous
	SPATE 75c Diesel Driven Pumps	7
	Trash Pumps	Numerous
	Peristaltic Pumps	Numerous
	Mobile High Capacity Diesel Driven Transfer Pump Units	6



Beach Vacuum / Powerpacks / Compressors and Blowers	Beach Vacuum / Powerpacks / Compressors and Blowers		
Vikoma PB600	12		
Vikoma Dual Pump and Powerpack	1		
PHAROS 30 Kw Powerpack	1		
Ro-Vac Beach Cleaning System	1		
Vikoma Powervac System	1		
Diesel Driven Compressors	Numerous		
Dispersant Systems			
Back Pack Sprayers	6		
Storage Equipment			
Fastank 2000	12		
Roll-over tanks	6		
Bowsers	Numerous		
Bunded tanks / IBC	Numerous		

Response Support Vehicles

200 Vehicles including HGVs, Trailers and Vans, ADR tankers, Vac Tankers, flat beds, HIABS and diggers

Ancillaries

- Hot and cold pressure washers Generators and lighting systems CAT Scanners Hand Augers Mobile drill unit Strimmers, ladders, cables, drop pipes, hoses Gas monitors, Ventilators, Tripod and winch sets, safety harnesses, lifejackets Intrinsically safe VHF
- Grab bags, PPE



A.2.5.1 Adler and Allan Mobilisation

The procedure for mobilising Adler and Allan is by a single telephone call to the 24 hour response number detailed in the Emergency Contacts Directory. The caller should pass detail the nature of the incident and will receive a return call within 10 minutes of receipt from the Duty Manager.

Adler and Allan provide an emergency oil spill response service to achieve a response time as follows:

Fully equipped 2 tonne LRRV with one supervisor and one responder at spill site within 4 hours from call (during working hours) and within 6 hours (outside working hours).

Fully equipped 8.3 tonne HRRV with one supervisor and two responders at spill site within 4 hours from call (during working hours) and within 6 hours (outside working hours).

Adler and Allan also provides safe and legal disposal of oil, oily materials resulting from spillage clean up operations; including the forwarding of consignment notes.



Clearwater Forth

A.2.8 Tier 3 Resources

United Kingdom ITOPF Country Profile (2014)

The MCA has on contract two dedicated surveillance aircraft; a Cessna F406 and a Cessna 404, located at East Midlands or Inverness Airports. The F406 can be fitted with a rapidly installed dispersant spray system. This can be used for test spraying of dispersant or for smaller oil spills.

For dispersant spraying, the MCA also includes two Lockheed Electra L188 aircraft, ready to operate at the nominated airfield within six hours of being called. Each aircraft can deliver up to 15 tonnes of dispersant.

The UK Government equipment stockpiles (boom, skimmers, dispersant spraying equipment, hot water washers and other associated equipment) are held primarily in Barnsley with smaller stores at Bristol and Dundee.



A.3. MEDIA STATEMENTS

A.3.1 Media Liaison

In the event of an oil spill that results in media attention Forth Ports Limited media consultants will handle the PR for Forth Ports Limited. This company will represent Forth Ports Limited to the media. For Tier 3 incidents there will be joint press releases between Forth Ports Limited and the MCA PR representatives.

A.3.2 The Media's Needs

The following summarises the media's interests in an oil spill event:

- first with news & meet deadlines
- publish details of casualties
- give human interest stories
- present facts including statistics
- bring stories to life with interviews and quotes
- show dramatic pictures
- describe events as they develop
- establish cause
- find new angles different from other coverage

A.3.3 Objectives in Dealing with the Media

The following should be borne in mind:

- To communicate quickly and honestly with all those affected by the emergency to:
- give safety information
- explain how your organisation is responding
- limit adverse comments and damage to reputation
- correct errors in reporting
- promote the positive aspects of your organisation.

NB: Unless you are designated as your organisation's spokesperson you are **NOT** authorised to offer a comment on behalf of the organisation therefore decline media requests and refer media requests to the Chief Harbour Master.



A.3.4 Sample Press Statements

Sample first public statement for a Clearwater Forth Harbour Oil Spill Incident

 Public Statement 1
 At
 _____(Time)
 _____(Date)

"An oil spill incident occurred at _____: ____ hours today within the Firth of Forth Harbour Area. The Harbour Area is operated by Forth Ports Limited.

First reports indicate that _____ amount of oil has been spilt. The cause of the spill is not known at this time.

Harbour operations have / have not been restricted at the present time. Forth Ports are presently dealing with the situation.

Further information will be made available in due course.

For further information telephone:______ (name)

On:______(number)



A.4. OIL SPILL TREATMENT PRODUCTS APPROVED FOR USE IN THE UNITED KINGDOM

For a listing of approved oil treatment products go to the Marine Management Organisation (MMO) website:

https://www.gov.uk/government/publications/approved-oil-spill-treatment-products_

The Marine Management Organisation (MMO) has been established to make a significant contribution to sustainable development in the marine area and to promote the UK government's vision for clean, healthy, safe, productive and biologically diverse oceans and seas.

MMO is an executive non-departmental public body (NDPB) established and given powers under the Marine and Coastal Access Act 2009 which brings together the key marine decision-making powers.

NB NatureScot is the statutory consultee in the event of an oil pollution incident occurring within territorial waters and has a duty to provide information and advice on the possible impacts of the incident and any proposed clean-up operations on the natural heritage interests in the area.



Clearwater Forth

A.5. PRO-FORMAS

A5.1 Incident Log

From incident start-up to stand down, record as applicable to your role:

- Key events and times
- Key decisions and why
- Start and finish of tasks
- External contacts made and times
- Equipment receipts
- Boat operations (start/stop time)
- Positioning booms/boats/tugs
- Start/stop of recovery
- Meetings (internal/external)
- Volumes of oil recovered
- Equipment defects/shortages
- Weather/tide/wind changes

Use proforma overleaf.



OIL SPILL RESPONSE LOG

Date	Time	Area	
Reference	Location	Туре	

Tide

Date	HW Time	HW Height	LW Time	LW Height

Weather

Time	Wind Direction	Wind Speed	Visibility	Daylight	Precipitation

Time	Narrative	Sitrep



Clearwater Forth

MCA Annual Return Proforma

OPRC Annual Return



Name of Port, Harbour or Oil Handling Facility:			
Annual Return Period:		to	
Plan Approval date:			(5 year life span of plans)
Summary of Incidents: (include da	ate source type and quantity of	fnoll	ution
Summary of Incluents: (include da	are, source, type and quantity of	i pom	
Summary of Exercises: (include da	ate and type of exercise conduc	ted)	
Pollution Training Undertaken (in	nclude date, MCA Level, Name	e & ce	ertificate No.)
	· · · · ·		/
Summary of Amendments: (includ	le date, amendment No. & iter	n(s) c	hanged)
Summary of Americanents: (more		in(5) C	nungoa)
Signed:	Print:		
Position:	Date:		

This form must be completed by Ports, Harbours and Oil Handling facilities at the end of each calendar year, nil returns are required, by the 31st January and returned to the Regional Counter Pollution & Salvage Officer. Continue on separate sheet if necessary.



co-ordinator:

FORTH PORTS LIMITED

Clearwater Forth

Post Exercise / Incident* Report



Name of Port/Harbour/Oil Handling Facility:

	Tier Level	Name	
(11,2 or 3) exercise / incident	[] 2 or 3)	exercise / incident	

Names of any other	
participating ports, harbours or	
oil handling facilities if joint	
equipment deployment	
exercise/incident	

Date	Time	
of exercise / incident	of exercise / incident	

Location of exercise/incident:	
Name of exercise / incident	

	-	
Name of personnel participating in	List of equipment	
exercise/incident and role played:	deployed:	

Name of any other organisations or authorities	
participating in exercise / incident:	

Details of amendments to be made to the Contingency Plan resulting from this exercise / incident:

(in addition to this form the revision list is to be updated & the appropriate pages within the plan amended & issued to all plan holders)

I can confirm that the details on this form provide a realistic summary of the exercise/incident. Any action points resulting from this exercise/incident have been dealt with accordingly, the relevant documents updated and copies provided to the appropriate bodies for their attention.

Authorised by (name in block capitals):		Position / Job Title:	
Signature:		Date:	

* Delete as applicable



Clearwater Forth

A5.4 POLREP

Part 1	Information which should be provided in an Initial Pollution Report			
A	Classification and Category of Report: (1) Doubtful (2) Probable (3) Confirmed			
В	DATE and TIME pollution observed/reported and identity of observer/reporter			
С	POSITION and EXTENT of pollution			
	(If possible, state range and bearing from some prominent landmark or Decca position and estimated amount of pollution, eg, size of polluted area; number of tonnes of oil spilled; or number of containers, drums etc lost. When appropriate, give position of observer relative to pollution)			
D	TIDE and WIND speed and direction			
Е	WEATHER conditions and SEA state			
F	CHARACTERISTICS of pollution (Give type of pollution, eg, oil, crude or otherwise; packaged or bulk chemicals; or garbage. For chemicals, give proper name or United Nations Number, if known. For all, give also appearance, eg, liquid; floating solid; liquid oil; semi-liquid sludge; tarry lumps; weathered oil; discolouration of sea; visible vapour; etc).			
G	SOURCE and CAUSE of pollution if known			
	(eg, from vessel or other undertaking. If from vessel, say whether as a result of apparent deliberate discharge or a casualty. If the latter, give a brief description. Where possible, give name, type, size, nationality and Port of Registry of polluting vessel. If vessel is proceeding on its way, give course, speed and destination, if known.)			
Н	VESSELS IN THE AREA (To be given if the polluter cannot be identified and the spill is considered to be of recent origin.)			
J	Whether PHOTOGRAPHS or SAMPLES have been taken and/or SAMPLES for analysis.			
К	REMEDIAL ACTION taken, or intended, to deal with the spillage			
L	FORECAST of likely effect of pollution (eg, arrival on beach, with estimated timing)			
М	NAMES of those informed other than addresses.			
Ν	Any OTHER relevant information (eg, names of other witnesses, references to other instances of pollution pointing to source.)			
Part 2	Supplementary Information to be provided later.			
	(This section may be disregarded when POLREPS are for UK internal distribution only.)			
0	RESULTS of SAMPLE analysis			
Р	RESULTS of PHOTOGRAPHIC analysis			
Q	RESULTS of SUPPLEMENTARY ENQUIRIES (eg, inspection by Surveyors, statements from ship's personnel etc, if applicable)			
R	RESULTS of MATHEMATICAL MODELS			

When sending follow-up POLREPS ensure that you mark the POLREP follow-up number.



Clearwater Forth

	OF PERSON TRANSMITTING	
REPORT		
CONTAC		
DETAILS	LS	
Α		
В		
С		
D		
E		
_		
F		
G		
н		
J		
К		
L		
М		
Ν		
Part 2	Supplementary Information to be provided later.	
0		
_		
Р		
Q		
R		

A5.5 Ports Incident Assessment



Clearwater Forth

Checkpoints	Points to Consider	Your Notes
Identify extent of area polluted	□ Which section of the dock is the spill in?	
Determine source of spill and type of hydrocarbons spilt	 Bunkering spill? Hose rupture Overfilling of tanks Small leak from hose Leak from fuel tanks? Leak from cargo tanks? Spill entering dock from Firth of Forth? Product type? Diesel Gas oil Heavy fuel oil Light fuel oil Hydraulic oil 	
Assess hazard potential of spill to response personnel	 Is there a potential for fire or explosion? Note that a large spill may carry with it the danger of toxic / noxious fumes. Access appropriate Safety Data Sheet(s) from Vessel/Terminal. 	
Establish how spill is progressing	Is spill ongoing?Is spill one-off event?	
Estimate approximate quantity of hydrocarbons spilt and potential final size	 Quantity released or rate of release? It may be possible to estimate this from equipment. If not use the table in Spill Assessment Section 5 which uses colour and area covered to provide an estimate. Note that the thickest areas will be at the downwind side of the slick as shown in diagram over the page. 	
Determine direction of movement of spilt oil	What is wind directionWhich dock corner is spill moving towards?	
Determine level of response required	 Assess level of response equipment required 	

A5.6 Incident Assessment Firth of Forth



The Checklist below lists the information that the Initial Responder may be required to on-pass to Dock Office/FTNS/MEC. NOTE THAT INITIAL CATEGORISATION OF THE INCIDENT MAY NEED TO BE REVISED DEPENDING ON THE INFORMATION OBTAINED FROM INCIDENT ASSESSMENT.

A. LOCATION AND TIME OF INCIDENT.				
Time:	Date:			
Type of incident:	Fire/Explosion		Collision	
	Grounding		Other	
	Confirmed /			
	Probable/doubtfu	I		
Source of spill: Tank	ker/Vessel		Jetty	Other
Identity of Observer / Reporter				
Any associated Num	ber of Deaths Nu	umber of Casualties	Other Emergency	?
	B. SPILLAC	GE DETAILS		
Approximate spill size:				
Type of oil e.g. heavy/medium/light/gasoline Characteristics e			.g. liquid/solid/tarry lumps	
A		Associated gas?		
Safety Risk		To personnel on	vessel	
		At jetty		
		Response personnel General public		
Who is responsible for the spill?		General public		
				YES / NO
If yes what types of assistance?				1257110
If yes what types of assistance:				
Are other organisations involved?				YES / NO
			State who	
Actions taken so far to contain incide	Actions taken so far to contain incident.			
Weather forecast updates – see continuation of proforma overle		a overleaf	leaf Wind direction	
			Wind strength	
			Visibility	
What level of Clearwater Forth Response is required?			TIER 1	
			TIER 2	
			TIER 3	

A5.7a Marine & Weather Conditions


STATUS OF WEATHER AND MARINE CONDITIONS				
Parameter	Actual	Predicted		
		6 hrs	12 hrs	24 hrs
Wind speed				
Wind direction from				
Sea State				
Present State of Tide (hrs Before/After HW)				
		M	aximum	
		Flood	Ebb	
Current Speed				
Current Direction (to)				

A5.7b Beaufort Wind Scales

Beaufort	Wind	Description	State of Sea	Probable
Scale	Speed			Wave
(Force)	(knots)			Height (m)
0	0 – 1	Calm	Like a mirror	0
1	1 – 3	Light Air	Ripples like scales are formed	0
2	4 – 6	Light Breeze	Small wavelets, short, more pronounced, not breaking	0.1
3	7 – 10	Gentle Breeze	Large wavelets, crests begin to break; a few white horses	0.4
4	11 – 16	Moderate Breeze	Small waves growing longer; fairly frequent white horses	1
5	17 – 21	Fresh Breeze	Moderate waves taking more pronounced form; many white horses, perhaps some spray	2
6	22 – 27	Strong Breeze	Large waves forming; white foam crests more extensive; probably some spray	3
7	28 – 33	Near Gale	Sea heaps up; white foam from breaking waves begins to blow into streaks	4
8	34 – 40	Gale	Moderately high waves of greater length; edge of crests breaks into spindrift; foam blown into well-marked streaks	5.5
9	41 – 47	Severe Gale	High waves with tumbling crests; dense streaks of foam; spray may affect visibility	7
10	48 – 55	Storm	Very high waves with long overhanging crests; dense streams of foam make surface of sea white. Heavy tumbling seas; visibility affected	9
11	56 – 63	Violent Storm	Exceptionally high sea waves, sea completely covered with long white patches of foam	11
12	64 and above	Hurricane	Air filled with foam and spray; sea completely white with driving spray; visibility very seriously affected	14

A5.8 Form to Report use of an Oil Treatment for Dispersant Use



Clearwater Forth

(Name of Port Authority/ Oil Handling Company)	
Incident No	Date
Volume and type of oil	
Location	
Remedial action taken	
Name and type of oil treatment product	
Date of manufacture	Efficacy last tested
	on
	(if applicable)
Comments on effectiveness	
Report made to MARINE SCOTLAND by	
<u> </u>	
Other remarks	



Clearwater Forth

A.3. PLACES OF REFUGE

Taken from the National Contingency Plan - A place of refuge means a place where a ship in need of assistance can take action to enable it to stabilise its condition and reduce the hazards to navigation, and to protect human life and the environment. IMO Resolution A.949(23) Guidelines on Places of Refuge for Ships in Need of Assistance provides further information and guidance, as does EU operational guidance on places of refuge.

Except in the most severe incident, a ship is likely to retain some of its cargo, bunkers and other pollutants. It may be desirable to carry out a cargo and bunker transfer operation from the stricken ship to prevent or minimise further spills. It may help to move the ship to a more sheltered area, such as a port, anchorage, or oil terminal. Ship to ship transfers are regulated by the Merchant Shipping (Ship to Ship transfers) (Amendment) Regulations 2012.

It is safer to carry out cargo and bunker transfer operations in sheltered areas. However, the decision to use an area moves the risk of pollution to an area that the incident might otherwise not have affected. The SOSREP is the designated UK competent authority to assign Places of Refuge. The SOSREP has in mind that time may be short and the damaged ship may not be in a condition to travel very far.

The process of identifying an appropriate place of refuge is driven by the circumstances of the incident, including such event-specific data as the weather, the geographical whereabouts of the incident and the type of threat posed by the vessel and its cargo. The CPS Branch will identify, in consultation with any Environment Groups, and as far as is practicable, and carefully consider potential places of refuge and conduct risk assessments of those potential locations prior to submission to the SOSREP who will make the final decision to assign a Place of Refuge.

Further, the MCA's Marine Survey and Inspection Branch provides trained Marine Casualty Officers who may be requested by the SOSREP to assess casualty vessels and determine the wider risk of any marine incident and future response.



A.7. TIER 2 RESPONSE CONTRACT

A Tier 2 response contract is in place with Adler and Allan and Forth Ports Limited to cover the Forth Ports Harbour Area as defined in this OSCP.

A list of Tier 2 resources can be located in Appendix 2.



A.8. MCA STOP NOTICES

For the up to date MCA STOp Notices follow this link:

https://www.gov.uk/government/publications/scientific-technical-and-operational-advicenotes-stop-notes

For example MCA STOp 4 / 2001

"GUIDELINES FOR THE PREPARATION OF COASTAL AND ESTUARINE BOOMING PLANS"

(referred to in Section 5)

Can be found in full by following this link:

https://assets.publishing.service.gov.uk/government/uploads/system/uploads/ attachment_data/file/908620/STOp4-2009.pdf



Clearwater Forth

A.9. ABBREVIATIONS

A&A	ADLER AND ALLAN
ACOPS	ADVISORY COMMITTEE ON POLLUTION OF THE SEA
BBMT	BRAEFOOT BAY MARINE TERMINAL
INEOS FPS	INEOS FORTIES PIPELINE SYSTEM
СЕРО	COUNCIL EMERGENCY PLANNING OFFICER
MRCC	COASTGUARD OPERATIONS CENTRE
CPSO	COUNTER-POLLUTION AND SALVAGE OFFICER
СНМ	CHIEF HARBOUR MASTER, FIRTH OF FORTH
CWF	CLEARWATER FORTH
FTNS	FORTH & TAY NAVIGATION SERVICE
HMCG	HER MAJESTY'S COASTGUARD
ITOPF	INTERNATIONAL TANKER OWNERS POLLUTION FEDERATION
ICS	INCIDENT COMMAND SYSTEM
LMIS	LLOYDS MARITIME INFORMATION SERVICE
MEC	MARINE EMERGENCY CENTRE
MoD	MINISTRY OF DEFENCE
МСА	MARITIME AND COASTGUARD AGENCY
NCP	NATIONAL CONTINGENCY PLAN FOR MARINE POLLUTION FROM SHIPPING
OPRC	MS (OIL POLLUTION PREPAREDNESS RESPONSE AND RECOVERY) REGS 1998
POLREP	POLLUTION REPORT
PoR	PLACE OF REFUGE
PMSC	PORT MARINE SAFETY CODE
RSPB	ROYAL SOCIETY FOR THE PROTECTION OF BIRDS
SCU	SALVAGE CONTROL UNIT
SEPA	SCOTTISH ENVIRONMENT PROTECTION AGENCY
SITREP	SITUATION REPORT
SOSREP	SECRETARY OF STATE'S REPRESENTATIVE
SSPCA	SCOTTISH SOCIETY FOR PREVENTION OF CRUELTY TO ANIMALS
ULCC	ULTRA LARGE CRUDE CARRIER
VLCC	VERY LARGE CRUDE CARRIER



A.10. Emergency Contacts Directory

The Emergency Contact Directory can be obtained from FTNS by calling 01324 498584 or contacting a member of Forth Ports marine management team.



Clearwater Forth

Clearwater Forth OSCP Page 1 Appendix 11

PORT OF GRANGEMOUTH

Forth Ports Limited / INEOS Grangemouth

A.11. Supplementary Information



Grangemouth Port Office Grangemouth Stirlingshire FK3 8UE 01324 498584

email <u>ftns@forthports.co.uk</u>

http://www.forthports.co.uk

A.11.1. The Location of the Port of Grangemouth

Port of Grangemouth is a non-tidal enclosed dock system to which access is available at all states of the tide depending on vessel draft and prevailing weather conditions. The port is located on the southern side of the Firth of Forth 30 kilometres west of Edinburgh. The port is a Statutory Harbour Authority owned and operated by Forth Ports Limited. Access to and from the Forth Estuary is via a system of lock gates, which are controlled by Forth Ports Limited. The Port Response Centre, from which the response would be managed, is located at the Marine Emergency Centre (MEC) at the Forth & Tay Navigation Service which is adjacent to the entrance lock gates as shown on the map.



Clearwater Forth





A.11.2. Response Management System

Spill Scenarios

Forth Ports Limited and INEOS Grangemouth have agreed the allocation of responsibility for overall management and conduct of the response effort. The division of responsibility for each scenario is also shown in the table.



Allocation of Incident Management Responsibility

RESPONSIBILITY FOR THE OVERALL MANAGEMENT OF RESPONSE ACTIVITIES RESTS WITH FORTH PORTS LTD

INCIDENT SCALE AND LOCATION	RESPONSE CENTRE(S) TO BE ACTIVATED	RESPONSE EQUIPMENT TO BE USED & LOCATION	RESPONSE GUIDELINES	REQUIRED LIAISON AND METHOD
Tier 1 – Release from INEOS Grangemouth Jetties (SCENARIO – 1)	Marine Emergency Centre (MEC) @ Forth & Tay Navigation Service (FTNS)	INEOS equipment at Jetties. Forth Ports equipment at the lock gates.	Guideline 1	Forth Ports' Duty Harbour Master will liaise directly with INEOS' response teams
Tier 2 – Release from INEOS Grangemouth Jetties (SCENARIO – 2)	Marine Emergency Centre (MEC) @ Forth & Tay Navigation Service (FTNS) INEOS would set up their Incident Management Team as required	As above plus A&A Tier 2 response	Guideline 1	An INEOS Marine Assurance Member will attend Forth Ports' MEC @ FTNS located at the Harbour Master's Office (see map)
Tier 1 – Eastern Channel (other than INEOS Jetties) (SCENARIO – 3)	Marine Emergency Centre (MEC) @ Forth & Tay Navigation Service (FTNS)	INEOS equipment at Jetties. Forth Ports equipment at the lock gates	Guideline 1	Forth Ports' Duty Harbour Master will co-ordinate the response
Tier 2 – Eastern Channel (other than INEOS Jetties) (SCENARIO – 4)	Marine Emergency Centre (MEC) @ Forth & Tay Navigation Service (FTNS)	As above plus A&A Tier 2 response	Guideline 1	A&A On-Call will attend Forth Ports' MEC @ FTNS located at the Harbour Master's Office



RESPONSIBILITY FOR THE OVERALL MANAGEMENT OF RESPONSE ACTIVITIES RESTS WITH FORTH PORTS LTD				
INCIDENT SCALE AND LOCATION	RESPONSE CENTRE(S) TO BE ACTIVATED	RESPONSE EQUIPMENT TO BE USED & LOCATION	RESPONSE GUIDELINES	LIAISON AND METHOD
Tier 1 – Grange Dock (SCENARIO – 5)	Marine Emergency Centre (MEC) @ Forth & Tay Navigation Service (FTNS)	INEOS equipment at Jetties. Forth Ports equipment at the lock gates	Guideline 2	Forth Ports' Duty Harbour Master will co-ordinate the response
Tier 2 – Grange Dock (SCENARIO – 6)	Marine Emergency Centre (MEC) @ Forth & Tay Navigation Service (FTNS)	As above plus A&A Tier 2 response	Guideline 2	A&A On-Call will attend Forth Ports' MEC @ FTNS located at the Harbour Master's Office
Tier 1 – Western Channel (SCENARIO – 7)	Marine Emergency Centre (MEC) @ Forth & Tay Navigation Service (FTNS)	INEOS equipment at Jetties Asset. Forth Ports equipment at the lock gates	Guideline 3	Forth Ports' Duty Harbour Master will co-ordinate the response
Tier 2 – Western Channel (SCENARIO – 8)	Marine Emergency Centre (MEC) @ Forth & Tay Navigation Service (FTNS)	As above plus A&A Tier 2 response.	Guideline 3	A&A On-Call will attend Forth Ports' MEC @ FTNS located at the Harbour Master's Office



INCIDENT SCALE AND LOCATION	RESPONSE CENTRE(S) TO BE ACTIVATED	RESPONSE EQUIPMENT TO BE USED & LOCATION	RESPONSE GUIDELINES	LIAISON AND METHOD
Tier 1 – Carron, Junction & Old Docks (SCENARIO – 9)	Marine Emergency Centre (MEC) @ Forth & Tay Navigation Service (FTNS)	INEOS equipment at Jetties. Forth Ports equipment at the lock gates	Guideline 4/5/6	Forth Ports' Duty Harbour Master will direct response teams
Tier 2 – Carron, Junction & Old Docks (SCENARIO – 10)	Marine Emergency Centre (MEC) @ Forth & Tay Navigation Service (FTNS)	As above plus A&A Tier 2 response	Guideline 4/5/6	A&A On-Call will attend Forth Ports' MEC @ FTNS located at the Harbour Master's Office

N.B. It can be noted that inherited incidents are always a possibility. This type of incident is difficult to plan for as there is little pre determination of the oil type, quantity or impact. There could be a potential spill from a river inlet which in turn will enter the Firth of Forth and cause CWF activation. Nevertheless, traffic is very uncommon on most river inlets and only usually consists of small pleasure/sailing boats.



A.11.3. Forth Ports/ INEOS Grangemouth Co-ordination

Liaison and co-ordination between Forth Ports Limited and INEOS Grangemouth would be required for the following reasons:

1. Incidents occurring at the INEOS Grangemouth Jetties (Scenarios 1+2) may result in the activation of the INEOS response organisation. To fulfil their corporate responsibilities, INEOS Grangemouth personnel may establish their Incident Command System. Meanwhile, the operational response to the incident would be conducted by the INEOS response teams, backed up by Adler & Alan for Tier 2 incidents. However, the management of any incident within the Port of Grangemouth will, at all times, be the executive responsibility of Forth Ports Limited. There will therefore be a need for the two organisations to co-ordinate their actions, press statements etc. During Tier 1 incidents, direct communications between the Duty Harbour Master and the response teams will be sufficient to ensure adequate liaison. A Tier 2 incident will require a greater degree of co-ordination. To achieve this, an INEOS Marine Assurance Member will attend Forth Ports' MEC at FTNS. The `Marine Assurance Member` will provide the link between INEOS' Grangemouth Incident Management Team, the teams conducting the response and Forth Ports' Overall Commander.

2. The operational response for all Tier 1 and 2 incidents, elsewhere in the port (Scenarios 3-10), will be carried out by Forth Ports and/or Adler and Allan. Again, the management of any incident within the Port of Grangemouth will, at all times, be the executive responsibility of Forth Ports Limited. To ensure that Forth Ports MEC at FTNS is provided with regular and accurate situation reports during Tier 2 incidents, all response teams will remain in direct communications with the Duty Harbour Master. Tier 2 incidents within the port but not associated with any of the INEOS Jetties would not require the INEOS Incident Management Team to be established. The A&A Supervisor will however attend Forth Ports' MEC at FTNS who will provide the link between the teams conducting the response and Forth Ports' Overall Commander. Tier 1 incidents not associated with INEOS Jetties will be co-ordinated by Forth Ports.

INEOS Response Organisation

INEOS' Emergency Response and Crisis Management describes two levels of incident response organisation. These teams are listed in the table below and their functional responsibilities given. The two-team levels are activated as required by the nature of the incident and they would closely co-ordinate their actions if all three are activated.

INEOS' 2 Tier Response Organisation			
Team	Team Leader	Team Function	
Incident Management Team	Incident Manager; responsible for overall management of the incident	 Initiate incident response Manages physical response to incident Provides co-ordination links with external authorities during incident. Mobilises specialist external resource 	



		requirements
Business Support Team	Business Support Manager; responsible for forming Business Support Team	 Assists with back-up support and will provide overall policy guidance. Manages ongoing business at Grangemouth. Develops & co-ordinates the business response to the incident.

- 2. The two levels of organisation are applied to Grangemouth as follows:
- 3. The Incident Management Team (IMT) will manage the physical response to incidents at the INEOS Jetties.
- 4. If additional business support is required, the Business Support Team (BST) at INEOS Grangemouth will become involved in the incident. This team will develop and co-ordinate the business response to the incident.

Forth Ports/ INEOS Grangemouth Liaison

Liaison and co-ordination between INEOS Grangemouth and Forth Ports Limited will be necessary during the response to pollution incidents within the Port of Grangemouth.







Clearwater Forth

A.11.4. Fast Facts

Port of Grangemouth			
	Photos	graph of the Port of Grangemouth	
Harbour Office contact details	Senior Harbour Master Port Office Central Dock Road Grangemouth FK3 8UE Telephone: 01324 498584		
	e-mail:	FTNS@forthports.co.uk	
Latitude & Longitude – harbour entrance	web site: 56 02.15 N 003 41'.0 W	www.forthports.co.uk	
Admiralty chart numbers	734, 735, 736, 737 & 74		
Maximum available draft	Oil Jetties 10.5m, Cargo		
Maximum available length	Overall size of lock: 237		
Maximum beam	As above		
Navigational access – <i>ie. buoyage</i>	Buoyed navigation chann	nel	
Environmental Sensitivities		River Forth SSSI's and SPA's	
Tugs		merous other tugs available in the area	
Pilotage	Compulsory over 45m		
Anchorages	1 2	chorages available on the Forth	
Repair facilities – <i>ie. dry docks and slipways</i>	Dry dock available: dimensions 105 x 16 x 4.8m		
Cargo handling facilities – <i>ie bulk, fuel, containers</i>	Bulk, fuel and containers		
Local authority	Falkirk Council		
Hazards – pipelines, overhead cables	Numerous subsea cables and pipelines in the inner Forth. Gas pipeline in the outer Forth. Two bridges with safe airdraft of 44m.		
Tidal Range	Impounded dock.		
ISPS compliant	Yes		



A.11.5. Products Handled

PRODUCT	JETTY USED			
Chemicals				
Benzene	Jetty No. 2, 3 or 4			
Butadiene	Jetty No. 3, 4			
Ethanol	Jetty No. 2 or 3			
Hexene	Jetty No. 4			
Propylene	Jetty No. 2, 3			
Raffinates	Jetty No. 3 or 4			
Styrene Monomer	Jetty No. 4			
Fame	Jetty No. 4, E1			
Refined Petro	bleum Products			
Fuel Oils	Jetty E1, E2, No. 2, 3, 4			
Gas Oils	Jetty E1, E2, No. 2, 3, 4			
Jet A1 (ATK)	Jetty E1, E2, No. 2, 3 4			
Kerosene	Jetty No. 2, 3, 4			
Light distillate Feedstock	Jetty E1, E2, No. 2 or 3			
LPG – Refrigerated	Old Lock Berth			
Motor Spirit	Jetty E1, E2, No. 2, 3, 4			
Ethane	Jetty No. 2			

At the Jetties there are refrigeration and storage facilities for 10,300 tonnes of propane and 9,700 tonnes of butane. All other imported / exported products pass to and from the jetties via pipeline to / from INEOS' Refining and Chemical Tank Farms.

The Jetties includes five jetties (Jetty E1, Jetty E2, Jetty No. 2, Jetty No.3, Jetty No. 4), and the Old Lock Berth that are all situated in the Eastern Channel near the entrance to the docks. The jetties on the eastern side of the docks (Jetties No. 2, 3, 4) have facilities for handling chemicals and most petroleum products. Jetties E1 and E2 on the western side of the docks are mainly used for handling fuel oils, gas oils, Jet A1, Light distillate Feedstock and Motor Spirit. The Old Lock Berth has facilities for handling refrigerated LPG and is operated by INEOS FPS.

The Jetties handle approximately 900 vessels each year. Vessels range in size from 1000 to 40000 DWT. Loading rate varies up to a maximum of approximately 1,000 tonnes per hour.



A.11.6. INEOS Grangemouth Incident Observer

EVERY EFFORT MUST BE MADE TO CONTAIN THE SPILL WITHIN THE HARBOUR					
INITIAL ACTIONS – ALL INCIDENTS					
STAGE	ACTIONS	INFORMATION			
Initial Actions ALL TIERS	 Immediately raise the alarm and notify HYDROCARBONS SHIFT MANAGER and FTNS Duty Harbour Master 	 Radio Ch. 5 Tel: ext 6151 or 07901 622393 01324 668495 			
Initial Actions ALL TIERS	Provide the following INFORMATION	 Location of incident Product type Estimated quantity Source of release 			
Initial Actions ALL TIERS	WARN personnel nearby				
Initial Actions ALL TIERS	If SAFE to do so attempt to stop or reduce release	Stop all TRANSFER operations			
	FURTHER ACTIONS – ALL TIE	RS			
Further Actions ALL TIERS	Act on instructions from HYDROCARBONS SHIFT MANAGER				
FINAL ACTIONS – ALL TIERS					
Final Actions ALL TIERS	• When released from the scene, proceed to the CONTROL ROOM and complete an incident report. Submit this to the HYDROCARBONS SHIFT MANAGER				



A.11.7. INEOS Grangemouth Jetties On-Scene Commander (HYDROCARBONS SHIFT MANAGER [HSM])

EVERY EFFORT MUST BE MADE TO CONTAIN THE SPILL WITHIN THE HARBOUR		
INITIAL ACTIONS – ALL TIERS		
STAGE	ACTIONS	INFORMATION
Initial Actions	Receive notification of oil / chemical	Location of incident
ALL TIERS	spill at Jetties Asset and obtain the following information	Product type
		Estimated quantity
		Source of release
		Actions taken
		Notifications made
Initial Actions	Open INCIDENT LOG	
ALL TIERS		
Initial Actions	Alert MARINE ASSURANCE ON-CALL	
ALL TIERS		
Initial Actions	NOTIFY Forth Ports DUTY HARBOUR MASTER	□ Tel: 01324 668495
ALL TIERS		
Initial Actions	Inform other vessels	
ALL TIERS		
Initial Actions	Assume role of ON SCENE COMMANDER	
ALL TIERS	CUMMANDER	
Initial Actions	 Proceed to SCENE of incident and if SAFE assess release and conduct a 	
ALL TIERS	HAZARD RISK ASSESSMENT	
Initial Actions	Ensure appropriate shut down	
ALL TIERS	operations are carried out (ACTIVATE DOCKS AREA SHUTDOWN SYSTEM IF NECESSARY)	



		,
Initial Actions ALL TIERS	Determine ACTIONS to be taken and RESOURCES required	
Initial Actions ALL TIERS	• If release involves highly FLAMMABLE substances, eliminate all ignition sources and call out INEOS FIRE SERVICE	 Notes: INEOS Fire Service will notify Central Scotland Fire & Rescue
Initial Actions	Notify the following	Jetty operators
ALL TIERS		 INEOS Jetty tank farm control room
	FURTHER ACTIONS	
Actions Further TIER 2	• Set up FORWARD INCIDENT SUPPORT ROOM if necessary at either East or West Jetties Office	
Further Actions	Mobilise Adler & Alan Tier 2 Responders	Tel: 01234 49 8584 Ch 14 (VHF)
TIER 2	Via FTNS Duty AHM	
Further Actions ALL TIERS	Ensure all statutory NOTIFICATIONS have been carried out	
FINAL ACTIONS – ALL TIERS		
Final Actions ALL TIERS	• Complete INCIDENT LOG detailing all events and communications and submit to Hydrocarbons Plant Manager.	



A.11.8. INEOS Grangemouth Jetty Technicians

EVERY EFFORT MUST BE MADE TO CONTAIN THE SPILL WITHIN THE HARBOUR			
INITIAL ACTIONS – ALL TIERS			
STAGE	ACTIONS	INFORMATION	
Initial Actions ALL TIERS	Receive notification of oil / chemical release at Jetties		
Initial Actions ALL TIERS	Carry out SHUTDOWN OPERATIONS / pollution response as directed by HYDROCARBONS SHIFT MANAGER		
	FURTHER ACTIONS – ALL TIERS		
Further Actions ALL TIERS	Carry out response as directed by the HYDROCARBONS SHIFT MANAGER		
FINAL ACTIONS – ALL TIERS			
Final Actions ALL TIERS	• When incident is declared closed report to HYDROCARBONS SHIFT MANAGER for further instructions		



A.11.9. INEOS Grangemouth Marine Assurance On-call

EVERY EFFORT MUST BE MADE TO CONTAIN THE SPILL WITHIN THE HARBOUR		
INITIAL ACTIONS – ALL TIERS		
STAGE	ACTIONS	INFORMATION
Initial Actions	Receive notification of oil / chemical	Location of incident
ALL TIERS	release at Jetties Asset obtain the following information	Product type
		Estimated quantity
		Source of release
		Actions taken
		Notifications made
Initial Actions TIER 2	Ensure HSM, SSM & FTNS Duty Harbour Master have been notified	Tel: 07879 432357 (SSM)
		Tel: 07901 622393 (HSM)
		6536 (internal) (SSM)
		6151 (internal) (HSM)
		Ch 5 (UHF)
		□ 01324 668495(FTNS)
Initial Actions	If incident is Category / Tier 1 and no further assistance is required,	
ALL TIERS	monitor situation and request updates	
	FURTHER ACTIONS – ALL TIERS	
	Assume role of OSC	



A.11.10 INEOS Grangemouth Site Shift Manager (SSM)

EVERY EFFORT MUST BE MADE TO CONTAIN THE SPILL WITHIN THE HARBOUR		
INITIAL ACTIONS – ALL TIERS		
STAGE	ACTIONS	INFORMATION
Initial Actions	Receive notification of oil / chemical	Location of incident
ALL TIERS	release at Jetties Asset obtain the following information	Product type
		Estimated quantity
		□ Source of release
		Actions taken
		Notifications made
Initial Actions TIER 2	 Notify Ensure Adler & Alan Oil Spill Response have been mobilised (via FTNS Duty AHM) 	 Tel: 01324 668495
Initial Actions TIER 2	• Notify DUTY INCIDENT MANAGER and determine need to establish INCIDENT MANAGEMENT TEAM.	 Tel: As per Duty Roster
Initial Actions ALL TIERS	• If incident is Category / Tier 1 and no further assistance is required, monitor situation and request updates	
	FURTHER ACTIONS – ALL TIE	RS
Further Actions ALL TIERS	• If incident requires establishment of INCIDENT MANAGEMENT TEAM (IMT) request FIRE & SECURITY CONTROL ROOM to effect callout of IMT	 FIRE & SECURITY CONTROL ROOM to provide ON CALL team with incident information and request IMT to assemble at INCIDENT MANAGEMENT ROOM
FINAL ACTIONS – ALL TIERS		



|--|

A.11.11. INEOS Grangemouth Duty Incident Manager

EVERY EFFORT MU	ST BE MADE TO CONTAIN THE SPILL WITHIN	THE HARBOUR
INITIAL ACTIONS -TIERS 2/3		
STAGE	ACTIONS	INFORMATION
Initial Actions TIERS 2/3	Receive notification from SITE SHIFT MANAGER obtain briefing, determine actions taken and confirm classification of incident	
Initial Actions TIERS 2/3	• Liaise with Forth Ports' OVERALL COMMANDER and determine appropriate response actions.	□ Tel: 01324 668495
Initial Actions TIERS 2/3	 Establish and maintain communications with INEOS ON - SCENE COMMANDER 	
Initial Actions TIERS 2/3	Delegate tasks to IMT	
Initial Actions TIERS 2/3	 Place on standby or call out equipment as required 	
Initial Actions TIERS 2/3	Assess availability of further INEOS manpower	
	FURTHER ACTIONS – TIERS 2	2/3
Further Actions	Ensure relevant external NOTIFICATIONS are carried out	
TIERS 2/3		
Further Actions TIERS 2/3	Ensure all media enquiries are handled by EXTERNAL AFFAIRS and CATCHLINE P.R	



Clearwater Forth

Further Actions TIERS 2/3	• Determine response manning requirements and subsistence needs of personnel at response site	
Further Actions TIERS 2/3	 Deal with personnel issues (injury etc.) 	
Further Actions TIERS 2/3	Ensure INEOS management is kept informed	
Further Actions TIERS 2/3	Consider implication for Petroineos REFINERY Operations	
Further Actions TIERS 2/3	Ensure BUSINESS and LEGAL issues are considered	
Further Actions TIERS 2/3	Monitor EFFECTIVENESS of the response	
	FINAL ACTIONS - TIERS 2/3	3
Final Actions TIERS 2/3	Declare the incident closed in consultation with Forth Ports' OVERALL COMMANDER	
Final Actions TIERS 2/3	Ensure all external authorities and INEOS staff are notified of incident closure	
Final Actions TIERS 2/3	Ensure all INCIDENT LOGS are completed and forwarded to appropriate authorities	



Г

A.11.12 INEOS Grangemouth Incident Management Team

EVERY EFFORT MUST BE MADE TO CONTAIN THE SPILL WITHIN THE HARBOUR INITIAL ACTIONS -TIER 2/3 INCIDENTS		
Initial Actions	On notification report to IMT	
TIER 2/3		
Initial Actions	Complete Incident Board and initiate checklist of actions	
TIER 2/3	Initiate checklist of actions	
Initial Actions	Allocate task of updating Incident Board	
TIER 2/3	DUdi U	
Initial Actions	Confirm liaison with Forth Ports	
TIER 2/3		
Initial Actions	Request ON SCENE COMMANDER to ensure that evidence of cause of	
TIER 2/3	incident is preserved	
	FURTHER ACTIONS – TIER 2	/3
Further	• EXTERNAL AFFAIRS on call to carry	
Actions	out duties as per MEDIA plan	
TIER 2/3		
Further Actions	Ensure notification and liaison with external authorities in consultation	
TIER 2/3	with Forth Ports Overall Commander	
Further Actions	Ensure provision of LOGISTIC support to Response Teams etc.	
TIER 2/3		



Clearwater Forth

Further Actions TIER 2/3	Ensure additional equipment and personnel are mobilised as required	
Further Actions TIER 2/3	Carry out further duties as requested by DUTY INCIDENT MANAGER	
	FINAL ACTIONS – TIER 2/3	
Final Actions TIER 2/3	Collate INCIDENT LOGS and carry out reporting procedures as detailed in INEOS GRANGEMOUTH INCIDENT MANAGEMENT PLAN	



A.11.13. INEOS Grangemouth Actions (Scenario 1)

EVERY EFF	EVERY EFFORT MUST BE MADE TO CONTAIN THE SPILL WITHIN THE HARBOUR	
INITIAL ACTIONS – ALL TIERS		
STAGE	ACTIONS	INFORMATION
Initial Actions TIER 1	On receiving call out obtain INCIDENT DETAILS	 Location of incident Product type Estimated quantity Source of release Actions taken Notifications made Call Back number for
Initial Actions ALL TIERS Initial Actions	 Place on standby / call out Forth Ports Personnel and Boatmen Make contact with INCIDENT REPORTER on Call Back number 	information Tel: 01324 668495 Tel: 01324 482510
TIER 1 Initial Actions TIER 2	 Notify Adler & Alan Oil Spill Response via Forth Ports Duty Harbour Master 	01324 668495 (FTNS)
Initial Actions TIER 1	 Proceed to Jetties and liaise with Jetty Technician. Carry out ASSESSMENT of incident if required. 	 Refer: Assume role of INCIDENT COMMANDER if required.
Initial Actions TIER 1	• If product IDENTITY is not known authorise sampling if SAFE to do so and arrange for chemical analysis	



FURTHER ACTIONS – ALL TIERS			
Further Actions	Determine appropriate response		
TIER 1			
Further Actions	Provide regular updates to Forth Ports' OVERALL COMMANDER		
TIER 1			
	FINAL ACTIONS – ALL TIERS		
Final Actions	Conduct thorough check of clean up		
TIER 1	results when incident is declared closed		
Final Actions	Prepare INCIDENT REPORT for Forth Ports' OVERALL COMMANDER		
TIER 1			



A.11.14. INEOS Grangemouth Marine Assurance On-Call

EVERY EFFORT MUST BE MADE TO CONTAIN THE SPILL WITHIN THE HARBOUR				
	INITIAL ACTIONS – ALL MARINE SPILLS			
STAGE	ACTIONS	INFORMATION		
Initial Actions ALL TIERS	On receiving call request incident details			
Initial Actions ALL TIERS	Proceed to Grangemouth IMR or MEC if activated. OTHERWISE proceed to incident site	 IMR or MEC location will depend upon level of support required 		
	FURTHER ACTIONS – ALL TIERS			
Further Actions ALL TIERS	• Liaise with Harbour Authority regards salvage, towage and cargo transfer etc.	□ Tel: 01324 668495		
Further Actions	Liaise with vessel owners, charterers etc. if required			
ALL TIERS				
Further Actions ALL TIERS	Liaise with marine contacts within and out-with INEOS			
Further Actions	Provide marine expertise to IMT as required			
ALL TIERS				
	FINAL ACTIONS – ALL TIERS			
Final Actions ALL TIERS	Provide expertise to subsequent marine investigations			



Reporting and Communication Roles





A.11.16. Control and Clean-Up Guidelines

Use of Guidelines

The following control and clean up guidelines will provide the following:

- A listing of equipment, its location and manpower available to respond to oil spills within Grangemouth Docks.
- Guidelines for responding to spills within Grangemouth Docks. The guidelines are based on the following 6 scenarios:

GUIDELINE	SCENARIO	
GUIDELINE 1	Spills in the Eastern Channel	
GUIDELINE 2	Spills in Grange Dock	
GUIDELINE 3	Spills in the Western Channel	
GUIDELINE 4	Spills in Carron Dock	
GUIDELINE 5	Spills in Old Dock	
GUIDELINE 6	Spills in Junction Dock	

NOTE: These response guidelines are written assuming the following:

- 1. The area has been declared safe to work in.
- 2. All response personnel are wearing appropriate personal protective equipment and are familiar with the health and safety guidance.

The Port of Grangemouth is an enclosed dock system and therefore use of dispersants is not valid due to the nature of the Port.



Response Guidelines-1 (Eastern Channel)

NO POLLUTION RESPON	SE SHOULD BE ATTEMPTED UNTIL IT IS SAFE TO DO SO
Winds from Westerly Sector	• A release from any of the INEOS Jetties or the CUOJ would be driven by the wind towards the LPG terminal and the Entrance Lock.
First Actions	Ensure lock gates are closed as soon as practical.
	Deploy booms to seal the entrance to the LPG berth and the Entrance locks.
Winds from Easterly Sector	• A release from any of the INEOS Jetties or the CUOJ would be driven by the wind towards the East Cut.
First Actions	Consider need to suspend lock operations
	 Deploy booms to prevent oil passing through the east cut into the Grange Dock.

Response Guidelines- 2 (Grange Dock)

NO POLLUTION RESPON	SE SHOULD BE ATTEMPTED UNTIL IT IS SAFE TO DO SO
Winds from Westerly Sector – Northern Section of Grange Dock	 A release from northerly section of Grange Dock would be driven towards the East Cut
Winds from Westerly Sector – Southern Section of Grange Dock	 A release from the southerly section of Grange Dock would also be driven towards the East Cut
First Actions	Deploy booms to seal the East Cut and prevent oil passing into the Eastern Channel

Winds from Easterly Sector – Northern Section of Grange Dock	•	A release from the northerly section of the Grange Dock would be driven towards the Western Channel and the West Cut
First Actions	•	Deploy booms to prevent oil passing through the West Cut
Winds from Easterly Sector – Southern Section of Grange Dock	•	A release from the southerly section of Grange Dock could be corralled and contained at the west end of the dock section.
First Actions	•	Deploy booms to corral and contain the oil.



Response Guidelines- 3 (Western Channel)

NO POLLUTION RESPONSE SH	IOULD BE ATTEMPTED UNTIL IT IS SAFE TO DO SO
Winds from Westerly Sector	A release within the Western Channel would be driven towards Grange Dock and the East Cut
First Actions	 Deploy booms to prevent oil passing through the East Cut Deploy booms where the dock width narrows (near the new Port Office) to prevent oil passing into Grange Dock
Winds from Easterly Sector	A release within the Western Channel would be driven towards the West Cut
First Actions	 Deploy booms to prevent oil passing through the West cut into Carron Dock.

Response Guidelines- 4 (Carron Dock)

NO POLLUTION RESPON	SE SHOULD BE ATTEMPTED UNTIL IT IS SAFE TO DO SO
Winds from Westerly Sector	 A release within Carron Dock would be driven towards the West Cut
First Actions	Deploy booms to prevent oil passing through the West Cut and into the Western Channel
Winds from Easterly Sector	A release within Carron Dock would be driven towards the Swing Bridge
First Actions	 Deploy booms to prevent oil passing underneath the Swing Bridge and into the Old Dock

Response Guidelines- 5 (Old Dock)

Winds from Westerly Sector	A release within Old Dock would be driven towards the Swing Bridge and the graving dock
First Actions	Deploy booms to prevent oil passing Underneath the Swing Bridge and into Carron Dock
Winds from Easterly Sector	A release within Old Dock would be driven towards Junction Dock
Winds from Easterly Sector First Actions	 A release within Old Dock would be driven towards Junction Dock Deploy booms to prevent oil passing Into Junction Dock



Response Guidelines- 6 (Junction Dock)

SE SHOULD BE ATTEMPTED UNTIL IT IS SAFE TO DO SO
A release within Junction Dock would be driven towards Old Dock and the Swing Bridge
 Deploy booms to prevent oil spreading from Junction Dock Deploy booms at the Swing Bridge to prevent oil entering Carron Dock
A release within Junction Dock would be driven towards the western end of Junction Dock
Deploy booms across the eastern end of Junction Dock to contain the oil within


A.11.17. Environmental Information

The following environmental information relates to oil pollution incidents within the Port of Grangemouth only. Part 1, Section 10 of the Clearwater Forth Plan highlights environmental information for areas adjacent to the Port of Grangemouth.

ARE THERE HABITAT TYPES SENSITIVE TO OIL POLLUTION?	YES	√	NO	
The following habitat types are vulnerable to oil pollution (listed in order of decreasing vulnerability): (1) saltmarsh, (2) sheltered tidal flats, (3) sheltered rocky coast, (4) gravel beach, (5) mixed sand and gravel beach, (6) exposed compacted tidal flats, (7) coarse/fine sand beaches, (8) eroding wave cut platform, (9) exposed rocky headland.	mudflats in Skinflats ar	the estuarin nd Kinneil Kei ast of the Po	as of inter tid e embaymer rse which are rt of Grangel	nts of e to the
ARE BIRDS PRESENT IN NATIONALLY OR INTERNATIONALLY IMPORTANT NUMBERS?	YES	√	NO	
(>1% EU population = International importance; >1% GB population = National importance).	Grangemou coastline of internationa and moultin vulnerable Skinflats su numbers of nationally in dunlin and regionally in species suc redshank o Kinneil Kers numbers of post breedi	E Skinflats an ally importan ng waders ar period is fror port interna wintering ki mportant nui golden plove mportant for h as greensh ccurring regu se supports in wintering sh ng moulting numbers of w	lats and surre d Kinneil Ker t numbers of nd wildfowl – m July – Mare ationally impe not and redsl mbers of she er. Skinflats is passage mig nank, ruff and	se support wintering most ch. ortant hank; lduck, s also grants, with d spotted y important rge flock of d nationally



ARE THERE FISH SPAWNING OR NURSERY GROUNDS?	YES	√	NO	
	notably plai	ignificant nu ice, in the sh id Kinneil Ke	allow wate	s for flatfish, ers of
ARE THERE NATIONAL CONSERVATION SITES?	YES	√	NO	
(i.e. National Nature Reserves; Sites of Special Scientific Interest; Local Nature Reserves; Areas of Special Protection; Areas of Outstanding Natural Beauty, National Parks, Country Parks).	Kerse, locat	nouth respec	est and eas	st of the Port
ARE THERE INTERNATIONAL CONSERVATION SITES?	YES	√	NO	
(i.e. Ramsar Sites – designated under the Convention on wetlands of international importance especially as waterfowl habitat; Special Protection Areas – designated under the 1979 EC Directive on the Conservation of Wild Birds; Special Areas of Conservation – designated under the 1992 EC Habitats Directive).	Grangemou Ramsar Site	ore adjacent ith is include and Specia	d in the "In I Protection	nner Forth"
ARE THERE OTHER CONSERVATION SITES?	YES	V	NO	
			1	
Geological Conservation Review Sites, Heritage Coasts, Sensitive Marine Areas, National Trust Sites, RSPB Sites, Wildfowl & Wetlands Trust		f Skinflats S ngemouth) is ve.		
(e.g. Nature Conservation Review Sites, Geological Conservation Review Sites, Heritage Coasts, Sensitive Marine Areas, National Trust Sites, RSPB Sites, Wildfowl & Wetlands Trust Sites). ARE THERE ANY COMMERCIAL FISHERIES?	A section of Port of Gran	ngemouth) is		
Geological Conservation Review Sites, Heritage Coasts, Sensitive Marine Areas, National Trust Sites, RSPB Sites, Wildfowl & Wetlands Trust Sites). ARE THERE ANY COMMERCIAL	A section of Port of Gran RSPB Resen	ngemouth) is	s operated	as as an
Geological Conservation Review Sites, Heritage Coasts, Sensitive Marine Areas, National Trust Sites, RSPB Sites, Wildfowl & Wetlands Trust Sites). ARE THERE ANY COMMERCIAL	A section of Port of Gran RSPB Reser	ngemouth) is	s operated	as as an

A map is available of all the designated sites in the vicinity of Grangemouth at the following website:

www.snh.gov.uk/publications-data-and-research/snhi-information-service/



Clearwater Forth

A.11.18. Oil Spill Risk Assessment

The Risk Assessments for CWF are now included in the Forth Ports Risk Assessment matrix which is kept live online. The latest version of Risk Assessment's can be found on the Forth Ports Website at <u>www.forthports.co.uk/marine/pmsc</u>.

Port of Grangemouth is a non-tidal impounded wet dock system to which access is available at all states of the tide depending on vessel characteristics and prevailing weather conditions. The port lies on a promontory which juts NE from the South side of the Firth of Forth 30 kilometres west of Edinburgh. The river Carron runs parallel to the West side of the promontory and the Grange Burn to the East. There are a number of anchorages with good holding ground available to a vessel on passage to Grangemouth in the River Forth.

The port is approached by a channel with a least width of 120m from the Hen and Chickens buoy and entered through a lock equipped with 3 sets of mitred gates forming 2 chambers of 90m and 112m lengths respectively. There are approach jetties protecting the locks on both sides. Larger vessels will berth at slack water due to the strength of the tidal currents. The maximum ship size normally accepted is 187m * 27.4m. The deepest berths in the port are in the Eastern Channel which can accommodate vessels of up to 11.00m draft. Leading from the Eastern Channel is the Grange Dock with a maximum draft of 7.7m and through the Western Channel the Carron Dock which has a maximum draft of 5.9m.

The port is owned and operated by Forth Ports Limited being a Statutory Harbour Authority and provides a total of 20 berths of 2350 metres total length. In addition there is a Common User Oil Jetty (CUOJ), an LPG private berth, 5 other private oil berths, layby berths and a dry dock. Approximate annual tonnage is 8.6 million tonnes and is comprised of a variety of cargoes detailed as follows: Containers and unit loads; Vehicles and wheeled cargoes; Dry bulks; Liquid bulk; Steel; Grain and Feedstuffs; Refrigerated products; Hazardous cargoes; Forest products; Oil and petroleum; General cargo; Project cargo.

The six private user berths are associated with INEOS Manufacturing Scotland Ltd. These berths lie within the jurisdiction of Forth Ports Limited, but are operated by INEOS Grangemouth (subject to the Forth Byelaws and General Directions for Navigation).

Grangemouth is in a compulsory pilotage area. Pilots licenced by Forth Ports as the Statutory Harbour Authority are available at all times for vessels using the port. Two tugs are based in the port and are available at all times; additional tugs are available from other ports in the Forth Estuary.



Potential Oil Spill Sources

Sources of oil spillage to the marine environment associated with activities at the Port of Grangemouth may be broadly divided into:

- Leak / failure of pipelines
- Leaks from valves and pipework on jetties
- Loading arm / connection seals leakage / failure
- Vessel tank overflow
- Human error during loading/bunkering operations
- Vessel sea valve leakage
- Structural damage to vessel due to collision or grounding
- Structural damage to vessel due to fire

Facilities Assessed

In order to provide an analysis of spill frequency for the Port of Grangemouth that is as specific as possible to the range of activities carried out in the port, quantitative risk analyses have been carried out for the following areas of risk:

INEOS Grangemouth Jetties
 Common User Oil Jetty
 Grange Dock
 Carron Dock
 Container Berths



Oil Spill Risk Assessment Results

The following risk assessment results have been produced using a combination of the vessel traffic data for berths within the Port of Grangemouth and historical oil spill frequency data. The historical data have been provided by BP Shipping and are based upon Lloyds Maritime Information Service (LMIS) and BP shipping casualty database which relates to tanker incidents.

	AT SEA	IN PORT
Frequency of Pollution Incidents (all sizes)	1.9E-04 (one event in every 5263 tanker days)	5.06E-04 (one event in every 1976 port calls)

Facility Specific Results

FACILITY	INEOS JETTIES
Spill Risk	7.1x10 ⁻¹
Estimated Event Frequency	1 event every 1.39 years
FACILITY	COMMON USER OIL JETTY
Spill Risk	5.4x10 ⁻²
Estimated Event Frequency	1 event every 18.2 years
FACILITY	GRANGE DOCK
Spill Risk	2.4x10 ⁻²
Estimated Event Frequency	1 event every 18.2 years
FACILITY	CARRON DOCK
Spill Risk	5.06x10 ⁻³
Estimated Event Frequency	1 event every 197.6 years
FACILITY	CONTAINER BERTHS
Spill Risk	2.13x10 ⁻¹
Estimated Event Frequency	1 event every 4.68 years



Slick Trajectory Analysis

In tidal areas, oil on water is affected by a combination of wind and tide. Spilt oil within Grangemouth Docks will only be affected by the wind. For this reason oil spill modelling is of little value for spills within the enclosed dock system. However, the potential exists for oil pollution to spread beyond the lock gates where it will be influenced by both the wind and tide. For this reason modelling has been carried out for a release beyond the lock gates. Deterministic slick trajectory modelling has been carried out using OSIS under a range of conditions. The modelling has been to predict times to shoreline impact for the purpose of establishing a minimum theoretical beaching time.

Slick Traject	ory Analysis. S	Summary of Results	
LOCATION:	0.25 NAUTICAL	MILES NORTH EAST	OF GRANGEMOUTH DOCKS ENTRANCE
Oil type and volume	State of Tide	Wind Direction & Speed	Location of Beaching and Time Taken
Heavy fuel oil 50 tonnes	Spring ebb.	225° (S.W) 09 Knots (F. 3)	Initial impact: Longannet Point Time taken: 1 hour 10 minutes
Forties blend 10 tonnes	Neap flood	090° (E) 09 Knots (F.3)	Initial impact: 0.8 nautical miles south of Kincardine Bridge Time taken: 5 hours 12 minutes
Forties blend 10 tonnes	Neap flood	300° (W.N.W) 09 Knots (F.3)	Initial impact: Foreshore of Grangemouth Refinery Time taken: 3 hours 49 minutes

Bunkering

Marine gas oil bunkers are available at the Port of Grangemouth. The controls which are in place to prevent pollution are similar to those listed in `Spill Prevention`. The Jetty Regulations for the private berths in the Eastern Channel operated by INEOS, contain a pre-bunkering checklist which must be completed 1 hr before the bunkering operation commences to verify that the controls are in place. These controls include the requirement for constant supervision and checking during the loading process, the maintenance of good communications and the continuous availability of counter pollution equipment. Bunkering does not take place at the CUOJ. In the Grange and Carron Dock bunkering is permitted provided that Notice to Mariners 3 of 2010 is strictly adhered to at all times. This notice imposes similar restrictions and controls to the Jetty Regulations. Taking into account the level of controls in place and the oil spill frequency data the risk of an incident from bunkering is assessed as low.



PORT OF LEITH

A.12. Supplementary Information

Forth Ports Limited

Imperial House

Leith Port Office

Albert Dock

Leith

Edinburgh

Tel 0131 555 8750



Clearwater Forth

A.12.1. Harbour Plan



Clearwater Forth OSCP Page 2 Appendix 12



A.12.2. Environmental Sensitivities and Priorities for Protection

Sensitive Areas in and Around the Port of Leith

The Imperial Dock Lock, within Port of Leith Harbour is a designated Special Protection Area. It qualifies as an SPA by regularly supporting a significant breeding population of European Importance of the species Common Tern. An average of 558 pairs return each year to breed between May and August, making this the largest colony in the Forth and one of the largest in the UK.

Although terns are generally sensitive to disturbance this colony appears to be resilient to disturbance from port activities and has been steadily increasing in size. A gantry crane was built on the quayside adjacent to the colony and although it has not been operated regularly, recently use of the crane seems to be increasing. Regular monitoring of the colony during the breeding season should highlight any increased disturbance from this source.



Imperial Dock SPA and Common Tern (inset)

Dispersant Use

It is not the Port of Leith's policy to use dispersants unless a 'force majeure' situation exists.



A.12.3. Booming Plans and Waste Disposal

Spills at Western Harbour:

Unless the wind is from N and NE direction, divisionary booming at the entrance to Imperial Dock is priority to minimise egress of oil into the Dock.

If spill is of heavy fuel oil immediate mobilisation of tier two equipment is required.

Spills at Imperial, Albert & Edinburgh Docks:

Spills in Imperial Dock should be contained by a boom across the entrance.

In general, spills should be contained in the smallest area possible. This can be achieved by drawing booms across corners of docks or around vessels to capture the oil. If this is not possible due to the prevailing weather conditions all spills should be contained in the dock area by means of shutting the lock gates.



A.12.4. Risk Assessment

The Risk Assessments for CWF are now included in the Forth Ports Risk Assessment matrix which is kept live online. The latest version of Risk Assessment's can be found on the Forth Ports Website at <u>www.forthports.co.uk/marine/safety</u>

Assessment Scope

This assessment covers operations carried out within the jurisdiction of Port of Leith operated by Forth Ports LTD. The Port of Leith is the largest deep water port in Scotland and is situated within lock gates on the south bank of the Firth of Forth, to the north of Edinburgh. It comprises a series of jetties, docks and dry docks in the eastern section of the Port and in the western section, the entrance lock gates which open into the Western Harbour, the largest area of open water within the Port.

Factors of Assessment

The Albert and Edinburgh docks are mainly used for laid up vessels such as offshore supply and safety boats. General ship repairs for visiting vessels are also undertaken at these docks. The Imperial Dock is the busiest with bulk cargoes being handled. However, dry cargo vessels can berth at any point of the dock system. Oil is no longer handled at the Imperial Dock. There are also deep water facilities for bulk and semi bulk cargoes. Large offshore multi-role support vessels conduct modifications for offshore projects and undertake repair and maintenance tasks. Visiting cruise liners currently dock at the Cruise Liner Terminal, adjacent to the berth of the Royal Yacht Britannia. Visiting vessels such as warships and cruise liners also make use of the facilities within Port of Leith. Naval, Fisheries Protection and Survey vessels also use the port. Tankers and very occasionally bunker barges also berth within the Port. Annual vessel numbers for the Port of Leith can be seen below:

Year	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020
Voyages	494	567	596	463	478	415	367	346	340	353	462

Over recent years there have been few oil spill incidents within the Port of Leith. One of the most notable spills involved the loss of 200 litres of Marine Diesel (2007).

Pre Arrival Checks

Harbour control discusses passage and berthing with all vessels prior to their entry into the Port. Pilotage is compulsory for vessels over 80m in length, vessels carrying dangerous goods and Pax (passenger) vessels. All vessels are required to report their operational condition in accordance with statutory regulations (Schedule 2), 24 hours prior to arrival; this is normally done through the ships agent.



Under the terms of chapter IX of SOLAS there is a mandatory enforcement of the ISM code (International Management Code for the Safe Operation of Ships and for Pollution Prevention). The international requirements require that all vessels (including cargo ships and Mobile Offshore Units all of 500 GT and over) will comply no later than 1st of July 2002.

FTNS enforces regulations to ensure all vessels approaching Port of Leith comply with the relevant regulations and legislation all of which are enforced prior to the vessel crossing the Eastern Limits. To comply with the "Port Marine Safety Code (PMSC)" a full risk assessment based on ALARP principle was carried out along with producing a formal safety management system and developing policies and procedures in accordance with the standards of the Code. Port passage plans are required to be completed by individual vessels. Port of Leith is also compliant with the ISPS Code.

Vessels in Transit

The statutory duty for reporting and dealing with pollution from any vessel en route to Port of Leith, prior to entering the harbour area, lies with the Harbour Master within the jurisdiction of Forth Ports and vessel owners. Reporting and response to any oil spill incident will be co-ordinated by the Clearwater Forth Plan.

Availability of Tugs and Private Vessels

There are 2 Forth Estuary Towage tugs based in the Port with additional tugs available elsewhere if required. Pilot vessels at Granton can also be mobilised.



FORTH PORTS LIMITED

Clearwater Forth

A.13. STATEMENTS OF PLAN APPROVAL

Statement from Consultee

of the perceived risk	e Clearwater Forth Oil Spill Contingency Plan gives a realistic assessment of Oil Pollution, and the response strategy required, for the areas covered
by this plan.	05.10
Name and Position	Caroline Burton, EPO
	Caroline Burton, EPO West Lothian Council

Statement from Consultee

Statement for MCA

I can confirm that the Clearwater Forth Oil Spill Contingency Plan gives a realistic assessment of the perceived risk of Oil Pollution, and the response strategy required, for the areas covered by this plan.

Signed	Malcolm Fraser
Name and Position	Area Officer – Forth
Representing	NatureScot
Date	16 June 2021



Statement from Consultee

Statement for MCA

I can confirm that the Clearwater Forth Oil Spill Contingency Plan gives a realistic assessment of the perceived risk of Oil Pollution, and the response strategy required, for the areas covered by this plan.

Signed	N. Cal
Name and Position	NER CORADO
Representing	SHELL
Date	11/6/2021

Statement from Consultee

Statement for MCA

I can confirm that the Clearwater Forth Oil Spill Contingency Plan gives a realistic assessment of the perceived risk of Oil Pollution, and the response strategy required, for the areas covered by this plan.

Signed	Paul Young
Name and Position	Paul Young, Senior Resilience Specialist
Representing	Resilience service, The City of Edinburgh Council
Date	14 June 2021



Clearwater Forth

Statement from Consultee

Statement for MCA

I can confirm that the Clearwater Forth Oil Spill Contingency Plan gives a realistic assessment of the perceived risk of Oil Pollution, and the response strategy required, for the areas covered by this plan.

Signed	Alex Baptie
Name and Position	Sandy Baptie. Emergency Planning, Risk & Resilience Manager
Representing	East Lothian Council
Date	230621

Statement from Consultee

Statement for MCA

I can confirm that the Clearwater Forth Oil Spill Contingency Plan gives a realistic assessment of the perceived risk of Oil Pollution, and the response strategy required, for the areas covered by this plan.

Signed	Roger May
Name and Position	Roger May Duty Officer MS Spillresponse
Representing	Marine Scotland
Date	11/06/21



Statement from Consultee

Statement for MCA

I can confirm that the Clearwater Forth Oil Spill Contingency Plan gives a realistic assessment of the perceived risk of Oil Pollution, and the response strategy required, for the areas covered by this plan.

SignedImage: Mail and PositionImage: Mail and PositionName and PositionBrian Mackay / INEOS Marine Assurance ManagerRepresentingINEOS GrangemouthDate14th June 2021

Statement from Consultee

Statement for MCA					
I can confirm that the Clearwater Forth Oil Spill Contingency Plan gives a realistic assessment of the perceived risk of Oil Pollution, and the response strategy required, for the areas covered by this plan.					
Signed	Mora				
Name and Position	John Moran – Marine Operations Manager				
Representing	Ineos FPS				
Date	18/06/21				

No statement of approval was received from either Fife Council or SEPA.

The lack of statement or comment from either party has been assumed as approval of the plan.



A.14. Marine Hazard Safety Data Sheets

Different products and chemicals require different responses if a spill occurs. This is because they vary in their general properties and also the hazards they present to response personnel. The data of these products is of importance to clean-up personnel and all personnel likely to be involved in a response should be aware of the contents of the hazard assessment sheets prior to any action on site. The data sheets contained in this below DO NOT contain comprehensive details of each product or chemical stored on-site. For further information refer to Product Data Sheets held on-site at Jetties, Terminal HSSE Specialists and/or INEOS Grangemouth IMT (if involved).

N.B: Material Safety Data Sheets are available from terminal operators

Hazard Assessment Data Sheet No. 1 ATMOSPHERIC RESIDUE

PRODUCT IDENTIFICATION					
Chemical Name	Atmospheric Residue	e			
Other Chemical / Trade Name	Atres				
Chemical Composition	Selected residues ob petroleum which cor hydrocarbons; up to hydrogen sulphide n	nsists of paraffinio 3% sulphur may	c, naphthenic and	aromatic	
UN Classification	UN Number : N/AUN Hazard Class : N/ASubsidiary Risks e.g. ADR/RID :Packaging Group: N/A				
Р	HSICAL PROPER	TIES			
Appearance and Odour	r Brown to black viscous liquid				
Relative Density (Specific Gravity)) 0.9 – 0.98 kg/l @ 15°C				
Solubility in water (mg/100ml)) Insoluble				
Boiling Point or Range	-				
Cł	EMICAL PROPER	RTIES			
Incompatibility / Reactivity	Avoid contact with	n strong oxidising	agents.		
Decomposition Products	Include oxides of generate smoke a				
Thermal Stability	Stable at ambient t	temperatures.			
	HAZARDS				
Hazard to personnel	Ingestion: large amounts will cause nausea & diarrhoea. Inhalation: irritant. Eye splash: irritant. Skin contact: long-term exposure results in dermatitis, and skin burns.				
Fire and Explosion Hazard	d Vapour in tank headspaces should be regarded as potentially flammable.			otentially	
Flashpoint	Not less than 60°	C (PMCC)			
Explosive Limits	Upper Limit:		Lower Limit:		



Hazard Assessment Data Sheet No. 2

BENZENE

PRODUCT IDENTIFICATION					
Chemical Name	Benzene				
Other Chemical / Trade Name	Benzol, Benolene, Pl	hynyl Hydride, Co	al naphtha		
Chemical Composition	C ₆ H ₆ (Aromatic hydro	ocarbon)			
UN Classification	UN Number : 1114UN Hazard Class : 3.2Subsidiary Risks e.g. ADR/RID :Packaging Group:				
PHSICAL PROPERTIES					
Appearance and Odour	Clear colourless lic N.B. ODOUR does				
Relative Density (Specific Gravity)	0.88				
Solubility in water (mg/100ml)) Immiscible in water (0.17% at 20°C)				
Boiling Point or Range	ge 80°C				
C	HEMICAL PROPE	RTIES			
Incompatibility / Reactivity	Reacts vigorously acids + halogens.	with oxidising ma	aterials, concentra	ted mineral	
Decomposition Products	None unusual; bu carbon dioxide.	rning will produce	e smoke, carbon r	nonoxide and	
Thermal Stability	Very stable at amb	ient temperature	5.		
	HAZARDS				
Hazard to personnel	el Ingestion: highly toxic, and carcinogenic. Inhalation: irritation, but repeated inhalation may lead to severe or even fatal blood diseases. Eye splash: irritant Skin contact: irritant, prolonged contact may result in dermatitis.				
Fire and Explosion Hazard	d Highly flammable, dangerous when exposed to heat or flame; moderate to severe explosion hazard in confined spaces.				
Flashpoint	t -11°C				
Explosive Limits	S Upper Limit: 8% Lower Limit: 1.4%				



Hazard Assessment Data Sheet No. 3

BUTADIENE

PRODUCT IDENTIFICATION				
Chemical Name	Butadiene			
Other Chemical / Trade Name	Buta-1,3-diene, 1,3-	butadiene, vinyl e	ethylene	
Chemical Composition	CH ₂ : CH-CH:CH ₂ (C ₄ I	H ₆)		
UN Classification	UN	UN Hazard	Subsidiary	Packaging
	Number : 1010Class :SubsidiaryPackaging2ADR/RID : 3			
PHSICAL PROPERTIES				
Appearance and Odour	Colourless liquid o	r gas; mild, arom	atic odour.	
Relative Density (Specific Gravity)	Liquid 0.62, gas 1.87 i.e. heavier than air			
Solubility in water (mg/100ml)) Insoluble (735mg/litre at 20°C)			
Boiling Point or Range	e -4.5°C			
CHEMICAL PROPERTIES				
Incompatibility / Reactivity				
Decomposition Products	-			
Thermal Stability	Very unstable; avo	id exposure to air		
	HAZARDS			
Hazard to personnel	Ingestion: irritant Inhalation: irritant; narcotic at high concentrations Eye splash: irritant Skin contact: irritant; cold burns			
Fire and Explosion Hazard	Severe explosion hazard; extremely flammable gas; on prolonged contact with air will form peroxides which are explosive. May explode when heated under pressure.			
Flashpoint	t -70°C			
Explosive Limits	Given Straight Straig			



Hazard Assessment Data Sheet No. 4

RAW C4's

PRODUCT IDENTIFICATION					
Chemical Name	Butenes				
Other Chemical / Trade Name	Mixed C4s, crude C4	ls, raw C4s			
Chemical Composition	A mixture of C4 para components are n-b isobutene, butadiene	utane, butene-1,			
UN Classification	UN Number : 1965UN Hazard Class : 2Subsidiary Risks e.g. ADR/RID : 3Packaging Group:				
PHSICAL PROPERTIES					
Appearance and Odour	Colourless liquid o	or gas; hydrocarb	on odour		
Relative Density (Specific Gravity)	Liquid 0.60, gas 1.87 i.e. heavier than air				
Solubility in water (mg/100ml)) Insoluble				
Boiling Point or Range	e -12 to + 12°C				
C	HEMICAL PROPE	RTIES			
Incompatibility / Reactivity	Very reactive; poly substances, amine alcohol's, glycol's, anhydrides.	es, alkanolamines	, halogenated com	npounds,	
Decomposition Products	Uncontrolled polyr produce smoke ar				
Thermal Stability	Unstable; avoid ex	posure to air.			
	HAZARDS				
Hazard to personnel	el Inhalation: irritant; narcotic at high concentrations. Eye splash: irritant; cold burns. Skin contact: irritant; cold burns.				
Fire and Explosion Hazard	Severe explosion l	hazard; extremely	y flammable gas.		
Flashpoint	-70°C				
Explosive Limits	Upper Limit: 120	%	Lower Limit:	1.6%	



Hazard Assessment Data Sheet No. 5

CONDENSATE

PRODUCT IDENTIFICATION					
Chemical Name	Condensate				
Other Chemical / Trade Name	Forties condensate,	North Sea conder	nsate		
Chemical Composition	Complex mixture of paraffin's, naphthen be present.				
UN Classification	UN Number : 1208UN Hazard Class : 3.1Subsidiary Risks e.g. ADR/RID : N/APackaging Group: II				
	PHSICAL PROPER	TIES			
Appearance and Odour	Clear virtually colourless volatile low viscosity liquid, characteristic odour.				
Relative Density (Specific Gravity)) 0.66 – 0.67 kg/l @ 15°C				
Solubility in water (mg/100ml)	Practically insoluble				
Boiling Point or Range	e 25 to - 150°C				
С	HEMICAL PROPE	RTIES			
Incompatibility / Reactivity	Can react with str	ong oxidising age	ents		
Decomposition Products	May include oxide generate smoke a				
Thermal Stability	Stable at ambient t	temperatures.			
	HAZARDS				
Hazard to personnel	Ingestion: large amounts will cause nausea & diarrhoea. Inhalation: irritant & drowsiness. Aspiration: excessive fume intake results in lung damage. Eye splash: irritant. Skin contact: long-term exposure results in dermatitis, and skin burns.				
Fire and Explosion Hazard	Highly flammable – danger of fire and explosion; vapour/air mixture explosive				
Flashpoint	Typically below -40°C				
Explosive Limits	Upper Limit 7%	Upper Limit 7% Lower Limit 1.1%			



Hazard Assessment Data Sheet No. 6

DERV

PRO	DUCT IDENTIFI	CATION			
Chemical Name	DERV (Diesel Engine	e Road Vehicle)			
Other Chemical / Trade Name	Diesel; PB Gas Oil R	V; National Diese	I		
Chemical Composition	A mixture of hydroc aromatics & naphthe some amounts of flo	enes. Winter gra	de products may		
UN Classification	UN Number : 1202UN Hazard Class : 3.3Subsidiary Risks e.g. ADR/RID : 3.4Packaging 				
PHSICAL PROPERTIES					
Appearance and Odour	r Pale yellow liquid				
Relative Density (Specific Gravity)) 0.84 – 0.86 kg/l @ 15°C				
Solubility in water (mg/100ml)) Will float on water surface; will evaporate especially when temperatures are warm.				
Boiling Point or Range	180 to - 360°C				
C	HEMICAL PROPE	RTIES			
Incompatibility / Reactivity	Will react with str	ong oxidising age	ents, and nitric aci	id.	
Decomposition Products	Include oxides of combustion will go carbon monoxide.	enerate smoke ar			
Thermal Stability	Stable at ambient	temperatures.			
	HAZARDS				
Hazard to personnel	el Ingestion: Hazardous Inhalation: irritant Asphiration: highly hazardous Eye splash: irritant Skin contact: irritant and can cause dermatitis				
Fire and Explosion Hazard	d High hazard, combustible.				
Flashpoint	t Approx. 65°C				
Explosive Limits	Upper Limit		Lower Limit		



ETHANOL

PRODUCT IDENTIFICATION				
Chemical Name	Ethanol			
Other Chemical / Trade Name	Alcohol, ethyl alcoho	bl		
Chemical Composition	C ₂ H ₅ OH (Aliphatic al	cohol)		
UN Classification	UN Number : 1170UN Hazard Class : 3.2Subsidiary Risks e.g. ADR/RID : 6.1Packaging Group:			
PHSICAL PROPERTIES				
Appearance and Odour	Clear, colourless liquid; ethereal, wine like odour.			
Relative Density (Specific Gravity)	0.8			
Solubility in water (mg/100ml)	Completely miscible with water.			
Boiling Point or Range	e 78°C			
CHEMICAL PROPERTIES				
Incompatibility / Reactivity	Reacts violently w nitrate, which resu potassium oxides platinum-black cat	ults in explosion. and potassium.	Can react violently	y with
Decomposition Products	None unusual; bui dioxide.	rning will produce	e carbon monoxide	e + carbon
Thermal Stability	Stable at ambient t	emperatures.		
	HAZARDS			
Hazard to personnel	Ingestion: Harmful narcotic, may result in loss of consciousness and can be fatal. Has a toxic affect on the central nervous system. Inhalation: intoxicating; Eye splash: irritant.			
Fire and Explosion Hazard	Highly flammable, potentially explosive.			
Flashpoint	13°C			
Explosive Limits	Upper Limit 19%	0	Lower Limit 3	.3%



Hazard Assessment Data Sheet No. 8

FUEL OIL

PRODUCT IDENTIFICATION					
Chemical Name	Fuel Oil				
Other Chemical / Trade Name	Light FO SG, Light Marine FO; Medium FO 25S / SG, Medium Marine FO; Heavy FO 10S / 20S / 30S / DH / SG, Heavy Marine FO; Bunker FO; Baglan Bay FO; Heavy FO CEGB; Low / High Sulphur FO; Heavy FO 3.5C [Note: FO = Fuel Oil].				
Chemical Composition	Selected residues obtained from petroleum oils which consist of paraffinic, naphthenic and aromatic hydrocarbons; traces of H ₂ S may be present.				
UN Classification	UN Number : 1202UN Hazard Class : 3Subsidiary Risks e.g. ADR/RID : 3.4Packaging Group: N/A				
PHSICAL PROPERTIES					
Appearance and Odour	 Light Fuel Oil – brown, free flowing liquid; Medium Fuel Oil – brown/black, less flowing liquid; Heavy Fuel Oil – black, viscous liquid. 				
Relative Density (Specific Gravity) (kg/l @ 15°C)					
Solubility in water (mg/100ml)	Insoluble				
Boiling Point or Range	>200°C				
CI	HEMICAL PROPE	RTIES			
Incompatibility / Reactivity	Can react with str	ong oxidising age	ents.		
Decomposition Products	May include oxide combustion will ge carbon monoxide.	enerate smoke ar			
Thermal Stability	Stable at ambient t	emperatures.			
	HAZARDS				
Hazard to personnel	Ingestion: minor; Inhalation: irritant; Eye splash: irritant; Skin contact: long-term exposure results in dermatitis, and skin burns when hot.				
Fire and Explosion Hazard	I Flammable				
Flashpoint	Not less than 66°C (PMCC)				
Explosive Limits	Upper Limit		Lower Limit		



Hazard Assessment Data Sheet No. 9

DIESEL / GAS OIL

PRODUCT IDENTIFICATION				
Chemical Name	Diesel / Gas Oil			
Other Chemical / Trade Name	Diesel, Gas Oil LS, G Oil	ias Oil SG, Domes	sticol 35, UK Dies	o, Marine Gas
Chemical Composition	Mixture of hydrocarbons predominantly paraffinic but with some aromatics andnaphthenes; small quantities of red dye and quinizarin as required by HM Customs and Excise will be in product not intended for use on public roads within the UK; small quantities of additives may also be present such as cold flow and cetane number improvers and anti-static additives. UN UN Hazard Subsidiary Packaging			
UN Classification	UN Number : 1202	UN Hazard Class : 3.3	Subsidiary Risks e.g. ADR/RID : 3.4	Packaging Group: III
PHSICAL PROPERTIES				
Appearance and Odour	 Diesel – straw/amber/gold coloured liquid; Gas oil – red liquid 			
Specific Gravity	0.820 – 0.870 kg/	l @ 15°C		
Solubility in water (mg/100ml)	Insoluble			
Typical Point Range	180 - 360°C			
Cł	EMICAL PROPER	RTIES		
Incompatibility / Reactivity	Avoid contact with	n strong oxidising	agents.	
Decomposition Products	Include oxides of combustion will ge carbon monoxice.			
Thermal Stability	Stable at ambient t	emperatures.		
	HAZARDS			
Hazard to personnel	Ingestion: harmful. Inhalation: irritant. Eye splash: irritant. Skin contact: long-term exposure results in dermatitis, and skin burns when hot.			
Fire and Explosion Hazard	rd Flammable			
Flashpoint	t 56°C minimum (PMCC)			
Explosive Limits	Upper Limit		Lower Limit	



HEXENE

PRODUCT IDENTIFICATION					
Chemical Name	Hexene				
Other Chemical / Trade Name	1-Hexene, Hex-1-er	ne			
Chemical Composition	C_3H_6 (Alkene / olefir	n – unsaturated h	ydrocarbon)		
UN Classification	UN Number : 2370UN Hazard Class : 3.1Subsidiary Risks e.g. ADR/RID : 3.3Packaging Group: III				
F	PHSICAL PROPER	TIES			
Appearance and Odour	Colourless liquid.				
Relative Density (Specific Gravity)	0.67				
Solubility in water (mg/100ml)	Insoluble				
Typical Point Range	e 64°C				
C	HEMICAL PROPE	RTIES			
Incompatibility / Reactivity	May react with st	rong oxidising age	ents.		
Decomposition Products					
Thermal Stability	Stable at ambient	temperatures.			
	HAZARDS				
Hazard to personnel	 Ingestion: may be harmful by ingestion. Inhalation: irritant; vapour is narcotic in high concentrations and can act as an asphyxiant. Eye splash: irritant Skin contact: irritant 				
Fire and Explosion Hazard	Highly flammable.				
Flashpoint	-25°C				
Explosive Limits	Upper Limit 7%		Lower Limit	1.2%	



JET A-1

PRODUCT IDENTIFICATION					
Chemical Name	Jet A-1				
Other Chemical / Trade Name	Aviation Turbine Ker	osene (ATK), Jet	A-1 with AL38, A	/TUR	
Chemical Composition	Complex mixture of hydrocarbons principally C9 to C16 primarily composed of straight run distillates; may contain small amounts of proprietary additives such as antioxidants, anti-static and anti-icing additives, corrosion inhibitors and metal deactivators.				
UN Classification	UN Number : 1863 UN Hazard Class : 3.3 Subsidiary Risks e.g. ADR/RID : 3.3				
P	HSICAL PROPER	TIES			
Appearance and Odour	r Clear, colourless to pale yellow, low viscosity liquid.				
Relative Density (Specific Gravity)) 0.77 minimum – 0.830 maximum kg/l @ 15°C				
Solubility in water (mg/100ml)) Insoluble				
Typical Point Range	150 - 300°C				
CI	HEMICAL PROPER	RTIES			
Incompatibility / Reactivity	May react with str	ong oxidising age	ents.		
Decomposition Products	May include oxide generate smoke a				
Thermal Stability	Stable at ambient t	emperatures.			
	HAZARDS				
Hazard to personnel	Ingestion: large amounts result in nausea & diarrhoea. Inhalation: irritant. Eye splash: irritant. Skin contact: long-term exposure results in dermatitis.				
Fire and Explosion Hazard	Flammable.				
Flashpoint	: >38°C (PMCC)				
Explosive Limits	Upper Limit		Lower Limit		



KEROSENE

PRODUCT IDENTIFICATION					
Chemical Name	Kerosene – Standard Grade and Premium Grade				
Other Chemical / Trade Name	Standard Grade: Kerosene SG, Marine T Kerosene, Solvent 300, Domesticol 28 Premium Grade: Pink Paraffin, Signal Oil, PG PGBP (pink), Kerosene LS, Paraffin.l				
Chemical Composition	Mixture of hydrocart but with some arom coumarin for HM Cu	atics; small quant	ities of markers s	uch as	
UN Classification	UN Number : 1223UN Hazard Class : 3.3Subsidiary Risks e.g. ADR/RID : 3.3Packaging Group: III				
P	HSICAL PROPER	TIES			
Appearance and Odour	Colourless, pale yellow (standard grade) or pink (premium grade) coloured liquid.				
Relative Density (Specific Gravity)	Standard grade : maximum 0.820 kg/l @ 15°C Premium grade : maximum 0.805 kg/l @ 15°C				
Solubility in water (mg/100ml)	Insoluble				
Typical Point Range	150 - 225°C (maximum 300°C)				
Ci	HEMICAL PROPER	RTIES			
Incompatibility / Reactivity	May react with str	ong oxidising age	ents.		
Decomposition Products	May include oxide generate smoke a				
Thermal Stability	Stable at ambient t	emperatures.			
	HAZARDS				
Hazard to personnel	Ingestion: large amounts result in nausea & diarrhoea. Inhalation: irritant. Skin contact: irritant, & long-term exposure results in dermatitis. Eye splash: irritant.				
Fire and Explosion Hazard	Flammable.				
Flashpoint	Standard grade : 38°C premium grade : 43°C				
Explosive Limits	Upper Limit Lower Limit				



Hazard Assessment Data Sheet No. 13 LIGHT DISTILLATE FEEDSTOCK

PRODUCT IDENTIFICATION					
Chemical Name	Light Distillate Feedstock (LDF 115/01)				
Other Chemical / Trade Name	Refinery Grade LDF 19				
Chemical Composition	Complex mixture of straight run petroleu		nging from C4 to (C11, based on	
UN Classification	UN Number : UN Hazard Class : Subsidiary Risks e.g. ADR/RID : 3.1				
F	HSICAL PROPER	TIES			
Appearance and Odour	r Clear pale yellow liquid				
Relative Density (Specific Gravity)) 0.66 – 0.67 kg/l @ 15°C				
Solubility in water (mg/100ml)) Insoluble				
Typical Point Range	30 - 175°C				
CI	HEMICAL PROPE	RTIES			
Incompatibility / Reactivity	Can react with str	ong oxidising age	ents.		
Decomposition Products	May include oxide generate smoke a				
Thermal Stability	Stable at ambient t	temperatures.			
	HAZARDS				
Hazard to personnel	el Ingestion: nor normally fatal. Inhalation: irritant (see aspiration) Aspiration: highly dangerous Eye splash: irritant. Skin contact: long-term exposure results in dermatitis				
Fire and Explosion Hazard	Highly flammable.				
Flashpoint	t Typically -40°C				
Explosive Limits	Upper Limit 7% Lower Limit 1.1%				



Clearwater Forth

Hazard Assessment Data Sheet No. 14

LPG

PRODUCT IDENTIFICATION					
Chemical Name	LPG				
Other Chemical / Trade Name	RLPG (refrigerated LPG). The term LPG "liquefied petroleum gases" includes all grades of butane, propane and mixtures thereof.				
Chemical Composition	Complex mixture of hydrocarbons ranging from C4 to C11, principally paraffin's naphthenes and aromatics; small quantities of benzene and n-hexane may be present.				
UN Classification	UN Number : 1978 UN Hazard Class : 2 Subsidiary Risks e.g. ADR/RID : 2(b)				
PHSICAL PROPERTIES					
Appearance and Odour	Clear colourless liquid or invisible gas; gaseous at normal ambient temperature and pressure.				
Relative Density (Specific Gravity)	Liquid 0.57; gas 2	.02			
Solubility in water (mg/100ml)	Insoluble				
Typical Point Range	e -45°C				
CI	HEMICAL PROPER	RTIES			
Incompatibility / Reactivity	Strong oxidising a	gents.			
Decomposition Products	Combustion will generate oxides of carbon.				
Thermal Stability	If storage vessels are subjected to excessive heat, product will expand and may cause storage vessel pressure relief valves to open and discharge highly flammable vapour.				
	HAZARDS				
Hazard to personnel	Inhalation: fatal (asphyxia) Skin contact: cold burns.				
Fire and Explosion Hazard	d Highly flammable; severe explosion hazard in an enclosed space in the presence of a source of ignition.				
Flashpoint	t <-18°C				
Explosive Limits	Upper Limit 10% Lower Limit 2.2%				



Clearwater Forth

Hazard Assessment Data Sheet No. 15

MOTOR SPIRIT – LEADED/UNLEADED

PRODUCT IDENTIFICATION					
Chemical Name	Motor Spirit – Leaded / Unleaded				
Other Chemical / Trade Name	Leaded Petrol – Premium Grade (4 star), Unleaded Petrol – Premium Unleaded Grade, Supergreen Unleaded Grade, Gasoline, Motor Gasoline, Motor spirit				
Chemical Composition	Complex mixture of hydrocarbons ranging from C4-C12, consisting primarily of highly branched olefins, naphthenes and aromatics. Oxygenates, e.g. MTBE, and up to 5% benzene may be present. Small quantities of performance enhancing materials may also be added and in the case of leaded petrol's these will include small amounts of alkyl lead compounds.				
UN Classification	UN Number : 1203	UN Hazard Class : 3	Subsidiary Risks e.g. 3.1(a)	Packaging Group: II	
F	PHSICAL PROPER	TIES			
Appearance and Odour	Clear virtually colo	ourless liquid			
Relative Density (Specific Gravity)	0.715 – 0.78 kg/l	@ 15°C			
Solubility in water (mg/100ml)	Insoluble				
Typical Point Range	25 - 220°C				
C	HEMICAL PROPER	RTIES			
Incompatibility / Reactivity	May react with stro	ong oxidising age	nts.		
Decomposition Products	May include oxides smoke and hazardo				
Thermal Stability	Stable at ambient t	emperatures.			
	HAZARDS				
Hazard to personnel	Ingestion: large amounts result in nausea & diarrhoea. Inhalation: irritant and drowsiness. Asphiration: excessive intake of fumes results in lung injury. Skin contact: irritant. Eye splash: irritant.				
Fire and Explosion Hazard	Highly Flammable				
Flashpoint	t <-40°C (PMCC)				
Explosive Limits	G Upper Limit Lower Limit				



Hazard Assessment Data Sheet No. 16C4 RAFFINATE

PRODUCT IDENTIFICATION					
Chemical Name	C4 Raffinate				
Other Chemical / Trade Name	Raffinates 1 and 2, B	utadiene raffinate	e, PIB raffinate		
Chemical Composition	Mixture of C4 paraffins, olefins and acetylenes. Principal components are: n-butane, isobutane/butene, butene-1, CIS and transbutene-2				
UN Classification	UN UN Hazard Subsidiary Packaging Number : Class : Risks e.g. Group: ADR/RID:				
l l l l l l l l l l l l l l l l l l l	PHSICAL PROPER	TIES			
Appearance and Odour	Colourless liquid o	or gas with hydrod	carbon odour		
Relative Density (Specific Gravity)	1.95				
Solubility in water (mg/100ml)	Insoluble in water				
Typical Point Range	e -12 to + 12°C				
C	HEMICAL PROPE	RTIES			
Incompatibility / Reactivity	Reactive with oxidi concentrated nitric		ng sulphuric acid	and	
Decomposition Products	-				
Thermal Stability	-				
	HAZARDS				
Hazard to personnel	Ingestion: Irritation. May cause loss of consciousness. Eye splash: Irritant Skin contact: Cold burns, can cause frost bite.				
Fire and Explosion Hazard	Extremely flamma	ble, severe explo	sion hazard		
Flashpoint	t -70°C				
Explosive Limits	Upper Limit Lower Limit 1.6%				



PROPYLENE

PRODUCT IDENTIFICATION					
Chemical Name	Propylene				
Other Chemical / Trade Name	Propene, methylethylene				
Chemical Composition	CH ₃ .CH:CH ₂ (Content: 92 – 99.7)	% propylene + 8	– 0.3% propane)		
UN Classification	UN Number : 1077UN Hazard Class : 2Subsidiary Risks e.g. 				
	PHSICAL PROPER	TIES			
Appearance and Odour	Colourless gas or	liquid; slight, cha	racteristic odour.		
Relative Density (Specific Gravity)	0.51				
Solubility in water (mg/100ml)	Negligible (0.26%	w/w at 20°C)			
Typical Point Range	ge -47.7°C				
С	HEMICAL PROPE	RTIES			
Incompatibility / Reactivity	Reacts vigorously v acids, halogens + i		ing agents, nitric a	and sulphuric	
Decomposition Products	Irritating fumes.				
Thermal Stability	Stable – hazardous Dangerous when e				
	HAZARDS				
Hazard to personnel	Inhalation: May result in loss of consciousness due to CNS depression and oxygen deficiency (asphyxiant). Eye splash: Irritant; causes frostbite. Skin contact: irritant, can cause frostbite.				
Fire and Explosion Hazard	d Highly flammable. Vapours heavier than air, may travel, be ignited at remote locations and flash back. Explosive air vapours mixtures may occur.				
Flashpoint	t <18°C				
Explosive Limits	Upper Limit 11% Lower Limit 2%				



Clearwater Forth

Hazard Assessment Data Sheet No. 18

REFORMATE

PR	PRODUCT IDENTIFICATION				
Chemical Name	Reformate				
Other Chemical / Trade Name	Light Cat Reformate, Heavy Cat Reformate, Full Range Cat Reformate, Platformate.				
Chemical Composition	Complex mixture of principally aromatics benzene may be pre-	, paraffin's and n			
UN Classification	UN Number : 1268 UN Hazard Class : 3.1 Subsidiary Risks e.g. ADR/RID: 3.1				
	PHSICAL PROPER	TIES			
Appearance and Odour	· Clear, light green	low viscosity liqu	id		
Relative Density (Specific Gravity)	0.78 – 0.88 kg/l @) 15°C			
Solubility in water (mg/100ml))				
Typical Point Range	25 - 210°C				
c	HEMICAL PROPE	RTIES			
Incompatibility / Reactivity	May react with stro	ong oxidising age	nts.		
Decomposition Products	May include oxides smoke and hazardo				
Thermal Stability	Stable at ambient t	emperatures			
	HAZARDS				
Hazard to personnel	Ingestion: large amounts result in nausea & diarrhoea. Asphiration: lung injury and cancer. Inhalation: irritant, drowsiness and cancer. Skin contact: irritant, & Long-term exposure results in dermatitis and burns. Eye splash: irritant.				
Fire and Explosion Hazard	Highly flammable	- danger of fire a	and explosion.		
Flashpoint	Less than ambient				
Explosive Limits	G Upper Limit Lower Limit				



STYRENE

PRODUCT IDENTIFICATION					
Chemical Name	Styrene				
Other Chemical / Trade Name	Styrene monomer; vinylbenzene.				
Chemical Composition	$C_6H_5CH:CH_2$				
UN Classification	UN Number : 2055UN Hazard Class : 3.3Subsidiary Risks e.g. ADR/RID:Packaging Group:				
le l	PHSICAL PROPER	TIES			
Appearance and Odour	Colourless or pale yellow oily liquid, with a penetrating disagreeable odour.				
Relative Density (Specific Gravity)	0.9				
Solubility in water (mg/100ml)	Negligible				
Typical Point Range	146°C				
С	HEMICAL PROPE	RTIES			
Incompatibility / Reactivity	Polymerises violent polymerisation at >		utocatalytic exoth	ermic	
Decomposition Products	Burning will produc	e carbon, carbon	monoxide and ca	arbon dioxide.	
Thermal Stability	Very unstable – slo heated.	wly polymerises	on exposure to lig	ht, rapidly if	
	HAZARDS				
Hazard to personnel	Ingestion: poisonous. Toxic effect on central nervous system. Inhalation: can cause respiratory distress Eye splash: can cause severe eye injury Skin contact: dermatitis				
Fire and Explosion Hazard	Flammable; moderate explosion hazard by ignition of vapour in an enclosed space or if polymerisation occurs.				
Flashpoint	t 31°C				
Explosive Limits	Upper Limit 6% Lower Limit 1.1%				



Clearwater Forth

Hazard Assessment Data Sheet No. 19

FAME

PRO	DUCT IDENTIFIC	CATION			
Chemical Name	Fatty Acid Methyl Ester				
Other Chemical / Trade Name	FAME, biodiesel, RME				
Chemical Composition	The substance consists mainly of saturated and unsaturated fatty acids methyl ester (chain length C16- C18, origin: vegetable oils). The substance may contain residuals of glycerol and partial glycerides (total < 3.5%) and traces of methanol (< 0.2%). To improve the properties the substance may contain additives in small concentrations: Cold flow improvers consisting mainly of oligomers of vinyl acetate and other monomers and oxidation stabilizers containing mainly steric hindered phenols. The single active components do not exceed a concentration of 1000 mg/kg (0.1%) in relation to the whole substance.				
UN Classification	UN Number : N/A	UN Hazard Class : N/A	Subsidiary Risks e.g. ADR/RID :	Packaging Group: N/A	
F	PHSICAL PROPER	TIES			
Appearance and Odour	Yellowish liquid				
Relative Density (Specific Gravity)	878 – 895 kg/m3	@ 15°C			
Solubility in water (mg/100ml)	0.023 g/l				
Boiling Point or Range	a 302.5 – 570 C				
C	HEMICAL PROPER	RTIES			
Incompatibility / Reactivity	Stable at ambient	temperature. No	hazardous reaction	ons known.	
Decomposition Products	In combustion em monoxide.	its toxic fumes of	carbon dioxide /	carbon	
Thermal Stability	Substance is stable and handling condi				
	HAZARDS				
Hazard to personnel	Ingestion: No sign of toxicity Inhalation: irritant. Eye splash: irritant. Skin contact: eye contact will cause some irritation.				
Fire and Explosion Hazard	d Flammable.				
Flashpoint	t 120 – 180 C				
Explosive Limits	Upper Limit:		Lower Limit:		



ETHANE

PRO	PRODUCT IDENTIFICATION				
Chemical Name	Ethane				
Other Chemical / Trade Name	C2H6				
Chemical Composition	Ethane is an organic chemical compound with chemical formula C ₂ H ₆ . At standard temperature and pressure, ethane is a colourless, odourless gas. Like many hydrocarbons, ethane is isolated on an industrial scale from natural gas and as a petrochemical by-product of petroleum refining. Its chief use is as feedstock for ethylene production.				
UN Classification	UN Number : N/A	UN Hazard Class : N/A	Subsidiary Risks e.g. ADR/RID :	Packaging Group: N/A	
PHSICAL PROPERTIES					
Appearance and Odour	Colourless gas				
Relative Density (Specific Gravity)	0.54				
Solubility in water (mg/100ml)	61 mg/l				
Boiling Point or Range	-88 C				
C	HEMICAL PROPER	RTIES			
Incompatibility / Reactivity	Oxidizing agents. ethane explode sp been known to ex	ontaneously; chl			
Decomposition Products	At high temperatu form hydrogen. Th dioxide. Carbon m	nermal decompos			
Thermal Stability	Stable under norma	al conditions			
	HAZARDS				
Hazard to personnel	Contact with liquic	l may cause cold	burns/frostbite.		
Fire and Explosion Hazard	EXTREMELY FLAMMABLE GAS. Forms explosive mixtures with air and oxidizing agents.				
Flashpoint	- 135 C TCC				
Explosive Limits	Upper Limit: Lower Limit:				